



# CHENMKO ENTERPRISE CO.,LTD

Halogens free devices

## SURFACE MOUNT SCHOTTKY DIODE ARRAY

VOLTAGE 30 Volts CURRENT 0.2 Ampere






**APPLICATION**  
\* Ultra high speed switching

**FEATURE**  
\* Small surface mounting type. (SC-88/SOT-363)  
\* High speed. ( $T_{RR}=2.5nSec$  Typ.)  
\* Suitable for high packing density.  
\* Maximum total power dissipation is 230mW.  
\* Peak forward current is 300mA.  
\* Schottky diode array ( Dual common anode).

**CONSTRUCTION**  
\* Silicon epitaxial planar

**MARKING**  
\* DW1



RATINGS	SYMBOL	BAT54DWGP	UNITS
Maximum Recurrent Peak Reverse Voltage	VRRM	30	Volts
Maximum RMS Voltage	VRMS	21	Volts
Maximum DC Blocking Voltage	VDC	30	Volts
Maximum Average Forward Rectified Current	Io	0.2	Amps
Peak Forward Surge Current at 1Sec.	IFSM	0.6	Amps
Typical Junction Capacitance between Terminal (Note 1)	CJ	10	pF
Maximum Reverse Recovery Time (Note 2)	TRR	5.0	nSec
Maximum Operating Temperature Range	TJ	+150	°C
Storage Temperature Range	TSTG	-55 to +150	°C

**ELECTRICAL CHARACTERISTICS** ( At TA = 25°C unless otherwise noted )

CHARACTERISTICS	SYMBOL	BAT54DWGP	UNITS
Maximum Instantaneous Forward Voltage at If= 100mA	VF	1.0	Volts
Maximum Average Reverse Current at Vr= 25V	IR	2.0	uAmps

NOTES : 1. Measured at 1.0 MHz and applied reverse voltage of 1.0 volts.  
2. Measured at applied forward current of 10mA and reverse current of 10mA.  
3. ESD sensitive product handling required.

## RATING CHARACTERISTIC CURVES ( BAT54DWGP )

FIG. 1 - FORWARD CHARACTERISTICS




FIG. 2 - REVERSE CHARACTERISTICS




FIG. 3 - TYPICAL JUNCTION CAPACITANCE




FIG. 4 - TYPICAL FORWARD CURRENT DERATING CURVE

