



CHENMKO ENTERPRISE CO.,LTD

Halogens free devices

**SURFACE MOUNT
SWITCHING DIODE**

VOLTAGE 80 Volts CURRENT 0.1 Ampere

CHN217GP

APPLICATION

- * Ultra high speed switching

FEATURE

- * Small surface mounting type. (SOT-23)
- * Two diode elements are connected in series (VFX2) per circuit.
- * Maximum total power dissipation is 200mW.
- * Peak forward current is 300mA.


CONSTRUCTION

- * Silicon epitaxial planar


MARKING

- * A7

CIRCUIT



SOT-23



Dimensions in millimeters

SOT-23

MAXIMUM RATINGS (At TA = 25°C unless otherwise noted)

RATINGS	SYMBOL	CHN217GP	UNITS
Maximum Recurrent Peak Reverse Voltage	V _{RRM}	80	Volts
Maximum RMS Voltage	V _{RMS}	56	Volts
Maximum DC Blocking Voltage	V _{DC}	80	Volts
Maximum Average Forward Rectified Current	I _O	0.1	Amps
Peak Forward Surge Current at 1 uSec	I _{FSM}	4.0	Amps
Typical Junction Capacitance between Terminal (Note 1)	C _J	2.0	pF
Maximum Operating Temperature Range	T _J	+150	°C
Storage Temperature Range	T _{STG}	-55 to +150	°C

ELECTRICAL CHARACTERISTICS (At TA = 25°C unless otherwise noted)

CHARACTERISTICS	SYMBOL	CHN217GP	UNITS
Maximum Instantaneous Forward Voltage at I _F = 100mA	V _F	1.20	Volts
Maximum Average Reverse Current at V _R = 70V	I _R	0.2	uAmps

NOTES : 1. Measured at 1.0 MHz and applied reverse voltage of 6.0 volts.
2. ESD sensitive product handling required.

2001-6

RATING CHARACTERISTIC CURVES (CHN217GP)

FIG. 1 FORWARD CHARACTERISTICS




FIG. 2 REVERSE CHARACTERISTICS




FIG. 3 TYPIC JUNCTION CAPACITANCE

