



CHENMKO ENTERPRISE CO.,LTD

Halogens free devices

SURFACE MOUNT
P-Channel Enhancement Mode Field Effect Transistor
VOLTAGE 60 Volts CURRENT 13 Ampere

CHM20P06PAGP

APPLICATION

- * Servo motor control.
- * Power MOSFET gate drivers.
- * Other switching applications.


FEATURE

- * Small flat package. (TO-252)
- * High density cell design for extremely low R_{DS(ON)}.
- * Rugged and reliable.


CONSTRUCTION

- * P-Channel Enhancement

CIRCUIT



D-PAK(TO-252)



Dimensions in inches and (millimeters)

TO-252

Absolute Maximum Ratings

T_A = 25°C unless otherwise noted

Symbol	Parameter	CHM20P06PAGP	Units
V _{DSS}	Drain-Source Voltage	-60	V
V _{GSS}	Gate-Source Voltage	±20	V
I _D	Maximum Drain Current - Continuous	-13	A
	- Pulsed (Note 3)	-40	
P _D	Maximum Power Dissipation	42	W
T _J	Operating Temperature Range	-55 to 150	°C
T _{STG}	Storage Temperature Range	-55 to 150	°C

Note : 1. Surface Mounted on FR4 Board , t <=10sec

2. Pulse Test , Pulse width <= 300us , Duty Cycle <= 2%

3. Repetitive Rating , Pulse width limited by maximum junction temperature

4. Guaranteed by design , not subject to production testing

Thermal characteristics

R _{θJA}	Thermal Resistance, Junction-to-Ambient (Note 1)	50	°C/W
------------------	--	----	------

2006-02

RATING CHARACTERISTIC CURVES (CHM20P06PAGP)

Electrical Characteristics $T_A = 25^\circ\text{C}$ unless otherwise noted

Symbol	Parameter	Conditions	Min	Typ	Max	Units
--------	-----------	------------	-----	-----	-----	-------

OFF CHARACTERISTICS

BV_{DSS}	Drain-Source Breakdown Voltage	$V_{GS} = 0 \text{ V}, I_D = -250 \mu\text{A}$	-60			V
I_{DSS}	Zero Gate Voltage Drain Current	$V_{DS} = -48 \text{ V}, V_{GS} = 0 \text{ V}$			-1	μA
I_{GSSF}	Gate-Body Leakage	$V_{GS} = 20\text{V}, V_{DS} = 0 \text{ V}$			+100	nA
I_{GSSR}	Gate-Body Leakage	$V_{GS} = -20\text{V}, V_{DS} = 0 \text{ V}$			-100	nA

ON CHARACTERISTICS (Note 2)

$V_{GS(th)}$	Gate Threshold Voltage	$V_{DS} = V_{GS}, I_D = -250 \mu\text{A}$	-1		-3	V
$R_{DS(ON)}$	Static Drain-Source On-Resistance	$V_{GS}=-10\text{V}, I_D=-4.5\text{A}$		92	105	$\text{m}\Omega$
		$V_{GS}=-4.5\text{V}, I_D=-3.9\text{A}$		120	150	
g_{FS}	Forward Transconductance	$V_{DS} = -5\text{V}, I_D = -3\text{A}$		2		S

SWITCHING CHARACTERISTICS (Note 4)

Q_g	Total Gate Charge	$V_{DS}=-30\text{V}, I_D=-4.5\text{A}$ $V_{GS}=-10\text{V}$		21	29	nC
Q_{gs}	Gate-Source Charge			3		
Q_{gd}	Gate-Drain Charge			6		
t_{on}	Turn-On Time	$V_{DD} = -30\text{V}$ $I_D = -1.0\text{A}, V_{GS} = -10 \text{ V}$ $R_{GEN} = 6 \Omega$		11	45	nS
t_r	Rise Time			9	30	
t_{off}	Turn-Off Time			46	150	
t_f	Fall Time			22	75	

DRAIN-SOURCE DIODE CHARACTERISTICS AND MAXIMUM RATINGS

I_s	Drain-Source Diode Forward Current	(Note 1)			-13	A
V_{SD}	Drain-Source Diode Forward Voltage	$I_s = -4.5\text{A}, V_{GS} = 0 \text{ V}$ (Note 2)			-1.3	V