



CHENMKO ENTERPRISE CO.,LTD

Halogens free devices

SURFACE MOUNT

P-Channel Enhancement Mode Field Effect Transistor

VOLTAGE 30 Volts CURRENT 33 Ampere

CHM4311PAGP

APPLICATION

- * Servo motor control.
- * Power MOSFET gate drivers.
- * Other switching applications.


FEATURE

- * Small flat package. (TO-252)
- * Super high density cell design for extremely low R_{DS(ON)}.
- * High power and current handing capability.


CONSTRUCTION

- * P-Channel Enhancement

CIRCUIT



D-PAK(TO-252)



Dimensions in inches and (millimeters)

TO-252

Absolute Maximum Ratings

T_A = 25°C unless otherwise noted

Symbol	Parameter	CHM4311PAGP	Units
V _{DSS}	Drain-Source Voltage	-30	V
V _{GSS}	Gate-Source Voltage	±20	V
I _D	Maximum Drain Current - Continuous	-33	A
	- Pulsed (Note 3)	-100	
P _D	Maximum Power Dissipation	36	W
T _J	Operating Temperature Range	-55 to 150	°C
T _{STG}	Storage Temperature Range	-55 to 150	°C

Note : 1. Surface Mounted on FR4 Board , t <=10sec

2. Pulse Test , Pulse width <= 300us , Duty Cycle <= 2%

3. Repetitive Rating , Pulse width limited by maximum junction temperature

4. Guaranteed by design , not subject to production testing

Thermal characteristics

R _{θJA}	Thermal Resistance, Junction-to-Ambient (Note 1)	50	°C/W
------------------	--	----	------

2009-12

ELECTRICAL CHARACTERISTIC (CHM4311PAGP)

Electrical Characteristics $T_A = 25^\circ\text{C}$ unless otherwise noted

Symbol	Parameter	Conditions	Min	Typ	Max	Units
--------	-----------	------------	-----	-----	-----	-------

OFF CHARACTERISTICS

BV_{DSS}	Drain-Source Breakdown Voltage	$V_{\text{GS}} = 0 \text{ V}, I_D = -250 \mu\text{A}$	-30			V
$I_{\text{DS}}^{\text{SS}}$	Zero Gate Voltage Drain Current	$V_{\text{DS}} = -30 \text{ V}, V_{\text{GS}} = 0 \text{ V}$			-1	μA
I_{GSSF}	Gate-Body Leakage	$V_{\text{GS}} = 20 \text{ V}, V_{\text{DS}} = 0 \text{ V}$			+100	nA
I_{GSSR}	Gate-Body Leakage	$V_{\text{GS}} = -20 \text{ V}, V_{\text{DS}} = 0 \text{ V}$			-100	nA

ON CHARACTERISTICS (Note 2)

$V_{\text{GS}(\text{th})}$	Gate Threshold Voltage	$V_{\text{DS}} = V_{\text{GS}}, I_D = -250 \mu\text{A}$	-1		-3	V
$R_{\text{DS}(\text{ON})}$	Static Drain-Source On-Resistance	$V_{\text{GS}} = -10 \text{ V}, I_D = -10 \text{ A}$		14	18	$\text{m}\Omega$
		$V_{\text{GS}} = -4.5 \text{ V}, I_D = 9 \text{ A}$		23	30	
g_{FS}	Forward Transconductance	$V_{\text{DS}} = -5 \text{ V}, I_D = -11 \text{ A}$		21		S

Dynamic Characteristics

C_{iss}	Input Capacitance	$V_{\text{DS}} = -15 \text{ V}, V_{\text{GS}} = 0 \text{ V}, f = 1.0 \text{ MHz}$		2020		pF
C_{oss}	Output Capacitance			395		
C_{rss}	Reverse Transfer Capacitance			202		

SWITCHING CHARACTERISTICS (Note 4)

Q_g	Total Gate Charge	$V_{\text{DS}} = -15 \text{ V}, I_D = -7 \text{ A}$ $V_{\text{GS}} = -4.5 \text{ V}$		16.4	22	nC
Q_{gs}	Gate-Source Charge			5.8		
Q_{gd}	Gate-Drain Charge			6.5		
t_{on}	Turn-On Time	$V_{\text{DD}} = -10 \text{ V}$ $I_D = -1.0 \text{ A}, V_{\text{GS}} = -10 \text{ V}$ $R_{\text{GEN}} = 6 \Omega$		16	30	nS
t_r	Rise Time			7	15	
t_{off}	Turn-Off Time			105	200	
t_f	Fall Time			40	80	

DRAIN-SOURCE DIODE CHARACTERISTICS AND MAXIMUM RATINGS

I_s	Drain-Source Diode Forward Current	(Note 1)			-3.2	A
V_{SD}	Drain-Source Diode Forward Voltage	$I_s = -3.2 \text{ A}, V_{\text{GS}} = 0 \text{ V}$ (Note 2)			-1.2	V

RATING CHARACTERISTIC CURVES (CHM4311PAGP)

Typical Electrical Characteristics

Figure 1. Output Characteristics




Figure 2. Transfer Characteristics




Figure 3. Gate Charge




Figure 4. On-Resistance Variation with Temperature




Figure 5. Gate Threshold Variation with Temperature

