

**Halogens free devices**

**CHENMKO ENTERPRISE CO.,LTD**

**SURFACE MOUNT**

**Dual Enhancement Mode Field Effect Transistor**

**N-channel: VOLTAGE 30 Volts CURRENT 7 Ampere**

**P-channel: VOLTAGE 30 Volts CURRENT 6.2 Ampere**

**CHM8968JGP**

#### APPLICATION

- \* Servo motor control.
- \* Power MOSFET gate drivers.
- \* Other switching applications.


#### FEATURE

- \* Small flat package. (SO-8 )
- \* Super high dense cell design for extremely low R<sub>DS(ON)</sub>.
- \* Lead free product is acquired.
- \* High power and current handing capability.


#### CONSTRUCTION

- \* N-Channel & P-Channel Enhancement in the package

#### CIRCUIT



**SO-8**



Dimensions in millimeters

**SO-8**

#### Absolute Maximum Ratings

T<sub>A</sub> = 25°C unless otherwise noted

Symbol	Parameter	N-Channel	P-Channel	Units	
V <sub>DSS</sub>	Drain-Source Voltage	30	-30	V	
V <sub>GSS</sub>	Gate-Source Voltage	±20	±20	V	
I <sub>D</sub>	Maximum Drain Current - Continuous	7.0	-6.2	A	
	- Pulsed (Note 3)	28	-25		
P <sub>D</sub>	Maximum Power Dissipation	2000			
T <sub>J</sub>	Operating Temperature Range	-55 to 150			
T <sub>STG</sub>	Storage Temperature Range	-55 to 150			

Note : 1. Surface Mounted on FR4 Board , t <=10sec

2. Pulse Test , Pulse width <= 300us , Duty Cycle <= 2%

3. Repetitive Rating , Pulse width limited by maximum junction temperature

4. Guaranteed by design , not subject to production testing

#### Thermal characteristics

R <sub>θJA</sub>	Thermal Resistance, Junction-to-Ambient (Note 1)	62.5	°C/W
2006-08			

## ELECTRICAL CHARACTERISTIC ( CHM8968JGP )

**N-Channel Electrical Characteristics**  $T_A = 25^\circ\text{C}$  unless otherwise noted

Symbol	Parameter	Conditions	Min	Typ	Max	Units
--------	-----------	------------	-----	-----	-----	-------

### OFF CHARACTERISTICS

$\text{BV}_{\text{DSS}}$	Drain-Source Breakdown Voltage	$V_{\text{GS}} = 0 \text{ V}, I_D = 250 \mu\text{A}$	30			V
$I_{\text{DSS}}$	Zero Gate Voltage Drain Current	$V_{\text{DS}} = 24 \text{ V}, V_{\text{GS}} = 0 \text{ V}$			1	$\mu\text{A}$
$I_{\text{GSSF}}$	Gate-Body Leakage	$V_{\text{GS}} = 20\text{V}, V_{\text{DS}} = 0 \text{ V}$			+100	nA
$I_{\text{GSSR}}$	Gate-Body Leakage	$V_{\text{GS}} = -20\text{V}, V_{\text{DS}} = 0 \text{ V}$			-100	nA

### ON CHARACTERISTICS (Note 2)

$V_{\text{GS(th)}}$	Gate Threshold Voltage	$V_{\text{DS}} = V_{\text{GS}}, I_D = 250 \mu\text{A}$	1		3	V
$R_{\text{DS(ON)}}$	Static Drain-Source On-Resistance	$V_{\text{GS}}=10\text{V}, I_D=7\text{A}$		22	28	$\text{m}\Omega$
		$V_{\text{GS}}=4.5\text{V}, I_D=6\text{A}$		30	40	
$g_{\text{FS}}$	Forward Transconductance	$V_{\text{DS}} = 5\text{V}, I_D = 7\text{A}$		25		S

### SWITCHING CHARACTERISTICS (Note 4)

$Q_g$	Total Gate Charge	$V_{\text{DS}}=15\text{V}, I_D=5.8\text{A}$ $V_{\text{GS}}=10\text{V}$		12	15.9	nC
$Q_{\text{gs}}$	Gate-Source Charge			1.3		
$Q_{\text{gd}}$	Gate-Drain Charge			2.3		
$t_{\text{on}}$	Turn-On Time	$V_{\text{DD}}= 15\text{V}$ $I_D = 1.0\text{A}, V_{\text{GS}}= 10 \text{ V}$ $R_{\text{GEN}}= 2.7 \Omega$		8	16	nS
$t_r$	Rise Time			5	10	
$t_{\text{off}}$	Turn-Off Time			25	50	
$t_f$	Fall Time			5	10	

### DRAIN-SOURCE DIODE CHARACTERISTICS AND MAXIMUM RATINGS

$I_s$	Drain-Source Diode Forward Current	(Note 1)			1.3	A
$V_{\text{SD}}$	Drain-Source Diode Forward Voltage	$I_s = 1.3\text{A}, V_{\text{GS}} = 0 \text{ V}$ (Note 2)			1.2	V

## ELECTRICAL CHARACTERISTIC ( CHM8968JGP )

**P-Channel Electrical Characteristics**  $T_A = 25^\circ\text{C}$  unless otherwise noted

Symbol	Parameter	Conditions	Min	Typ	Max	Units
--------	-----------	------------	-----	-----	-----	-------

### OFF CHARACTERISTICS

$BV_{DSS}$	Drain-Source Breakdown Voltage	$V_{GS} = 0 \text{ V}, I_D = -250 \mu\text{A}$	-30			V
$I_{DSS}$	Zero Gate Voltage Drain Current	$V_{DS} = -30 \text{ V}, V_{GS} = 0 \text{ V}$			-1	$\mu\text{A}$
$I_{GSSF}$	Gate-Body Leakage	$V_{GS} = 20 \text{ V}, V_{DS} = 0 \text{ V}$			+100	nA
$I_{GSSR}$	Gate-Body Leakage	$V_{GS} = -20 \text{ V}, V_{DS} = 0 \text{ V}$			-100	nA

### ON CHARACTERISTICS (Note 2)

$V_{GS(th)}$	Gate Threshold Voltage	$V_{DS} = V_{GS}, I_D = -250 \mu\text{A}$	-1		-3	V
$R_{DS(ON)}$	Static Drain-Source On-Resistance	$V_{GS} = -10 \text{ V}, I_D = -6.2 \text{ A}$		27	33	$\text{m}\Omega$
		$V_{GS} = -4.5 \text{ V}, I_D = -4 \text{ A}$		40	52	
$g_{FS}$	Forward Transconductance	$V_{DS} = -10 \text{ V}, I_D = -4 \text{ A}$		5		S

### SWITCHING CHARACTERISTICS (Note 4)

$Q_g$	Total Gate Charge	$V_{DS} = -15 \text{ V}, I_D = -6.2 \text{ A}$ $V_{GS} = -10 \text{ V}$		18.7	24.8	nC
$Q_{gs}$	Gate-Source Charge			3.7		
$Q_{gd}$	Gate-Drain Charge			2.3		
$t_{on}$	Turn-On Time	$V_{DD} = -15 \text{ V}$ $I_D = -1.0 \text{ A}, V_{GS} = -10 \text{ V}$ $R_{GEN} = 6 \Omega$		12	24	nS
$t_r$	Rise Time			5	10	
$t_{off}$	Turn-Off Time			57	114	
$t_f$	Fall Time			21	42	


### DRAIN-SOURCE DIODE CHARACTERISTICS AND MAXIMUM RATINGS

$I_s$	Drain-Source Diode Forward Current	(Note 1)			-6.2	A
$V_{SD}$	Drain-Source Diode Forward Voltage	$I_s = -1 \text{ A}, V_{GS} = 0 \text{ V}$ (Note 2)			-1.2	V


## RATING CHARACTERISTIC CURVES ( CHM8968JGP )

### N-Channel Typical Electrical Characteristics


**Figure 1. Output Characteristics**




**Figure 2. Transfer Characteristics**




**Figure 3. Gate Charge**



**Figure 4. On-Resistance Variation with Temperature**




**Figure 5. Gate Threshold Variation with Temperature**




## RATING CHARACTERISTIC CURVES ( CHM8968JGP )

### P-Channel Typical Electrical Characteristics


**Figure 1. Output Characteristics**




**Figure 2. Transfer Characteristics**



**Figure 3. Gate Charge**



**Figure 4. On-Resistance Variation with Temperature**



**Figure 5. Gate Threshold Variation with Temperature**

