



CHENMKO ENTERPRISE CO.,LTD

SURFACE MOUNT

Dual P-Channel Enhancement Mode Field Effect Transistor
VOLTAGE 30 Volts CURRENT 7.9 Ampere

CHM8311JGP

Halogen free devices

APPLICATION

- * Servo motor control.
- * Power MOSFET gate drivers.
- * Other switching applications.


FEATURE

- * Small flat package. (SO-8)
- * Super high dense cell design for extremely low R_{DS(ON)}.
- * High power and current handing capability.
- * Lead free product is acquired.


CONSTRUCTION

- * P-Channel Enhancement

CIRCUIT



SO-8



Dimensions in millimeters

SO-8

Absolute Maximum Ratings

T_A = 25°C unless otherwise noted

Symbol	Parameter	CHM8311JGP	Units
V _{DSS}	Drain-Source Voltage	-30	V
V _{GSS}	Gate-Source Voltage	±20	V
I _D	Maximum Drain Current - Continuous	-7.9	A
	- Pulsed (Note 3)	-31.6	
P _D	Maximum Power Dissipation	2000	mW
T _J	Operating Temperature Range	-55 to 150	°C
T _{STG}	Storage Temperature Range	-55 to 150	°C

Note : 1. Surface Mounted on FR4 Board , t <=10sec

2. Pulse Test , Pulse width <= 300us , Duty Cycle <= 2%

3. Repetitive Rating , Pulse width limited by maximum junction temperature

4. Guaranteed by design , not subject to production testing

Thermal characteristics

R _{θJA}	Thermal Resistance, Junction-to-Ambient (Note 1)	62.5	°C/W
2006-02			

RATING CHARACTERISTIC CURVES (CHM8311JGP)

Electrical Characteristics $T_A = 25^\circ\text{C}$ unless otherwise noted

Symbol	Parameter	Conditions	Min	Typ	Max	Units
--------	-----------	------------	-----	-----	-----	-------

OFF CHARACTERISTICS

BV_{DSS}	Drain-Source Breakdown Voltage	$V_{GS} = 0 \text{ V}, I_D = -250 \mu\text{A}$	-30			V
I_{DSS}	Zero Gate Voltage Drain Current	$V_{DS} = -24 \text{ V}, V_{GS} = 0 \text{ V}$			-1	μA
I_{GSSF}	Gate-Body Leakage	$V_{GS} = 20 \text{ V}, V_{DS} = 0 \text{ V}$			+100	nA
I_{GSSR}	Gate-Body Leakage	$V_{GS} = -20 \text{ V}, V_{DS} = 0 \text{ V}$			-100	nA

ON CHARACTERISTICS (Note 2)

$V_{GS(th)}$	Gate Threshold Voltage	$V_{DS} = V_{GS}, I_D = -250 \mu\text{A}$	-1		-3	V
$R_{DS(ON)}$	Static Drain-Source On-Resistance	$V_{GS} = -10 \text{ V}, I_D = -7 \text{ A}$		16	20	$\text{m}\Omega$
		$V_{GS} = -4.5 \text{ V}, I_D = -5.8 \text{ A}$		25	33	
g_{FS}	Forward Transconductance	$V_{DS} = -10 \text{ V}, I_D = -7 \text{ A}$		15		S

SWITCHING CHARACTERISTICS (Note 4)

Q_g	Total Gate Charge	$V_{DS} = -15 \text{ V}, I_D = -7 \text{ A}$ $V_{GS} = -4.5 \text{ V}$		16.4	22	nC
Q_{gs}	Gate-Source Charge			5.8		
Q_{gd}	Gate-Drain Charge			6.5		
t_{on}	Turn-On Time	$V_{DD} = -10 \text{ V}$ $I_D = -1.0 \text{ A}, V_{GS} = -10 \text{ V}$ $R_{GEN} = 6 \Omega$		16	30	nS
t_r	Rise Time			7	15	
t_{off}	Turn-Off Time			105	200	
t_f	Fall Time			40	80	

DRAIN-SOURCE DIODE CHARACTERISTICS AND MAXIMUM RATINGS

I_s	Drain-Source Diode Forward Current	(Note 1)			-2.1	A
V_{SD}	Drain-Source Diode Forward Voltage	$I_s = -2.1 \text{ A}, V_{GS} = 0 \text{ V}$ (Note 2)			-1.2	V