



MACMIC

August 2011

PRELIMINARY

MM16F020KC

200V 16A FRED



RoHS Compliant

**PRODUCT FEATURES**

- Ultrafast Recovery Time
- Soft Recovery Characteristics
- Low Recovery Loss
- Low Forward Voltage
- High Surge Current Capability
- Low Leakage Current

**APPLICATIONS**

- Freewheeling, Snubber, Clamp
- Inversion Welder
- PFC
- Plating Power Supply
- Ultrasonic Cleaner and Welder
- Converter & Chopper
- UPS

**DESCRIPTION**

FRED from MacMic utilizes advanced processing techniques to achieve ultrafast recovery times and higher forward current. Its soft recovery characteristics and high reliability suit for wide industrial applications.

**ABSOLUTE MAXIMUM RATINGS** $T_C=25^\circ\text{C}$  unless otherwise specified

Symbol	Parameter	Test Conditions	Values	Unit
$V_R$	Maximum D.C. Reverse Voltage		200	V
$V_{RRM}$	Maximum Repetitive Reverse Voltage		200	V
$I_{F(AV)}$	Average Forward Current	$T_C=110^\circ\text{C}$ , Per Diode	8	A
		$T_C=110^\circ\text{C}$ , Per Package	16	A
$I_{F(RMS)}$	RMS Forward Current	$T_C=110^\circ\text{C}$ , Per Diode	12	A
$I_{FSM}$	Non-Repetitive Surge Forward Current	$T_J=45^\circ\text{C}$ , $t=10\text{ms}$ , 50Hz, Sine	100	A
$P_D$	Power Dissipation		50	W
$T_J$	Junction Temperature		-40 to +150	$^\circ\text{C}$
$T_{STG}$	Storage Temperature Range		-40 to +150	$^\circ\text{C}$
Torque	Module-to-Sink	Recommended (M3)	1.1	N·m
$R_{\theta JC}$	Thermal Resistance	Junction-to-Case	2.5	$^\circ\text{C}/\text{W}$
Weight			2.1	g

**ELECTRICAL CHARACTERISTICS** $T_C=25^\circ\text{C}$  unless otherwise specified

Symbol	Parameter	Test Conditions	Min.	Typ.	Max.	Unit
$I_{RM}$	Reverse Leakage Current	$V_R=200\text{V}$	--	--	15	$\mu\text{A}$
		$V_R=200\text{V}$ , $T_J=125^\circ\text{C}$	--	--	250	$\mu\text{A}$
$V_F$	Forward Voltage	$I_F=8\text{A}$	--	0.87	1.0	V
		$I_F=8\text{A}$ , $T_J=125^\circ\text{C}$	--	0.78	--	V
$t_{rr}$	Reverse Recovery Time	$I_F=1\text{A}$ , $V_R=30\text{V}$ , $dI/dt=-200\text{A}/\mu\text{s}$	--	20	--	ns
$t_{rr}$	Reverse Recovery Time	$V_R=100\text{V}$ , $I_F=8\text{A}$ $dI/dt=-200\text{A}/\mu\text{s}$ , $T_J=25^\circ\text{C}$	--	25	--	ns
$I_{RRM}$	Max. Reverse Recovery Current		--	3.0	--	A
$t_{rr}$	Reverse Recovery Time	$V_R=100\text{V}$ , $I_F=8\text{A}$ $dI/dt=-200\text{A}/\mu\text{s}$ , $T_J=125^\circ\text{C}$	--	40	--	ns
$I_{RRM}$	Max. Reverse Recovery Current		--	5.5	--	A




Fig1. Forward Voltage Drop vs Forward Current





Fig2. Reverse Recovery Time vs  $di_F/dt$ Fig3. Reverse Recovery Current vs  $di_F/dt$ Fig4. Reverse Recovery Charge vs  $di_F/dt$ 

Fig5. Dynamic Parameters vs Junction Temperature




Fig6. Transient Thermal Impedance





Fig 7. Diode Reverse Recovery Test Circuit and Waveform



Dimensions in Millimeters and (Inchs)

Fig 8. Package Outline