



N & P-Channel 25-V (D-S) MOSFET

These miniature surface mount MOSFETs utilize High Cell Density process. Low $r_{DS(on)}$ assures minimal power loss and conserves energy, making this device ideal for use in power management circuitry. Typical applications are DC-DC converters, power management in portable and battery-powered products such as computers, printers, PCMCIA cards, cellular and cordless telephones.

- Low $r_{DS(on)}$ Provides Higher Efficiency and Extends Battery Life
- Miniature TSOP-6 Surface Mount Package Saves Board Space

V_{DS} (V)	$r_{DS(on)}$ (Ω)	I_D (A)
25	0.45 @ $V_{GS} = 4.5V$	1.2
	0.72 @ $V_{GS} = 2.5V$	1.0
-25	1.0 @ $V_{GS} = -4.5V$	-0.85
	1.70 @ $V_{GS} = -2.5V$	-0.75



ABSOLUTE MAXIMUM RATINGS ($T_A = 25^\circ C$ UNLESS OTHERWISE NOTED)					
Parameter		Symbol	N-Channel	P-Channel	Units
Drain-Source Voltage		V_{DS}	25	-25	V
Gate-Source Voltage		V_{GS}	8	-8	
Continuous Drain Current ^a	$T_A = 25^\circ C$	I_D	1.2	-0.9	A
	$T_A = 70^\circ C$		0.95	-0.65	
Pulsed Drain Current ^b		I_{DM}	± 3.5	± 2.5	
Continuous Source Current (Diode Conduction) ^a		I_S	1	-1	A
Power Dissipation ^a	$T_A = 25^\circ C$	P_D	1.25		W
	$T_A = 70^\circ C$		0.8		
Operating Junction and Storage Temperature Range		T_J, T_{stg}	-55 to 150		$^\circ C$

THERMAL RESISTANCE RATINGS				
Parameter		Symbol	Maximum	Units
Maximum Junction-to-Ambient ^a	$t \leq 5$ sec	R_{THJA}	100	$^\circ C/W$

Notes

- a. Surface Mounted on 1" x 1" FR4 Board.
- b. Pulse width limited by maximum junction temperature

SPECIFICATIONS (T _A = 25°C UNLESS OTHERWISE NOTED)							
Parameter	Symbol	Test Conditions	Limits				Unit
			Ch	Min	Typ	Max	
Static							
Drain-Source Breakdown Voltage	V _{(BR)DSS}	V _{GS} = 0 V, I _D = 250 uA	N	25			V
		V _{GS} = 0 V, I _D = -250 uA	P	-25			
Gate-Threshold Voltage	V _{GS(th)}	V _{GS} = V _{DS} , I _D = 250 uA	N	0.65	0.81	1.5	V
		V _{GS} = V _{DS} , I _D = -250 uA	P	-0.65	-0.83	-1.5	
Gate-Body Leakage Current	I _{GSS}	V _{DS} = 0 V, V _{GS} = 8 V	N			100	uA
		V _{DS} = 0 V, V _{GS} = -8 V	P			-100	
Zero Gate Voltage Drain Current	I _{DSS}	V _{DS} = 20 V, V _{GS} = 0 V	N			1	uA
		V _{DS} = 20 V, V _{GS} = 0 V, T _J = 55°C				10	
On-State Drain Current ^A	I _{D(on)}	V _{DS} = 5 V, V _{GS} = 4.5 V	N	1			A
		V _{DS} = -5 V, V _{GS} = -4.5 V	P	-1			
Drain-Source On-Resistance ^A	r _{DS(on)}	V _{GS} = 4.5 V, I _D = 0.5 A	N		0.35	0.45	Ω
		V _{GS} = 2.5 V, I _D = 0.2 A			0.45	0.72	
		V _{GS} = -4.5 V, I _D = -0.41 A	P		0.860	1.09	
		V _{GS} = -2.5 V, I _D = -0.2 A			1.15	1.50	
Forward Transconductance ^A	g _{fs}	V _{DS} = 5 V, I _D = 0.5 A	N		1.45		S
		V _{DS} = -5 V, I _D = 0.4 A	P		0.9		
Dynamic^b							
Total Gate Charge	Q _g	N-Channel V _{DS} =5V, V _{GS} =4.5V, I _D =0.5A P-Channel V _{DS} =-5V, V _{GS} =-4.5V, I _D =-0.25A	N		1.64	2.3	nC
			P		1.1	1.5	
Gate-Source Charge	Q _{gs}		N		0.4		
			P		0.33		
Gate-Drain Charge	Q _{gd}		N		0.45		
			P		0.26		
Switching							
Turn-On Delay Time	t _{d(on)}	N-Chaneel V _{DD} =6V, V _{GS} =4.5V, I _D =0.5A , R _{GEN} =50Ω, P-Channel V _{DD} =-6V, V _{GS} =-4.5V, I _D =-0.41A R _{GEN} =50Ω	N		3	6	nS
			P		7	21	
Rise Time	t _r		N		8.5	18	
			P		9	19	
Turn-Off Delay Time	t _{d(off)}		N		17	30	
			P		55	112	
Fall-Time	t _f		N		13	25	
			P		35	71	

Notes

- a. Pulse test: PW <= 300us duty cycle <= 2%.
- b. Guaranteed by design, not subject to production testing.

Analog Power (APL) reserves the right to make changes without further notice to any products herein. APL makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does APL assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. "Typical" parameters which may be provided in APL data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. APL does not convey any license under its patent rights nor the rights of others. APL products are not designed, intended, or authorized for use as components in systems intended for surgical implant into the body, or other applications intended to support or sustain life, or for any other application in which the failure of the APL product could create a situation where personal injury or death may occur. Should Buyer purchase or use APL products for any such unintended or unauthorized application, Buyer shall indemnify and hold APL and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that APL was negligent regarding the design or manufacture of the part. APL is an Equal Opportunity/Affirmative Action Employer.

Typical Electrical Characteristics (N-Channel)




Figure 1. On-Region Characteristics.




Figure 2. On-Resistance Variation with Drain Current and Gate Voltage.




Figure 3. On-Resistance Variation with Temperature.




Figure 4. On Resistance Variation with Gate-To-Source Voltage.




Figure 5. Transfer Characteristics.




Figure 6. Body Diode Forward Voltage Variation with Source Current and Temperature.

Typical Electrical Characteristics (N-Channel)




Figure 7. Gate Charge Characteristics.




Figure 8. Capacitance Characteristics.




Figure 9. Maximum Safe Operating Area.




Figure 10. Single Pulse Maximum Power Dissipation.

Normalized Thermal Transient Junction to Ambient




Figure 11. Transient Thermal Response Curve (sec)

Typical Electrical Characteristics (P-Channel)




Figure 12. On-Region Characteristics.




Figure 13. On-Resistance Variation with Drain Current and Gate Voltage.




Figure 14. On-Resistance Variation with Temperature.




Figure 15. On Resistance Variation with Gate-To- Source Voltage.




Figure 16. Transfer Characteristics.




Figure 17. Body Diode Forward Voltage Variation with Source Current and Temperature.

Typical Electrical Characteristics (P-Channel)




Figure 18. Gate Charge Characteristics.




Figure 19. Capacitance Characteristics.




Figure 20. Maximum Safe Operating Area.




Figure 21. Single Pulse Maximum Power Dissipation.

Normalized Thermal Transient Junction to Ambient






Figure 22. Transient Thermal Response Curve.

Package Information

TSOP-6: 6LEAD



Dim	MILLIMETERS			INCHES		
	Min	Nom	Max	Min	Nom	Max
A	0.91	–	1.10	0.036	–	0.043
A ₁	0.01	–	0.10	0.0004	–	0.004
A ₂	0.84	–	1.00	0.033	0.038	0.039
b	0.30	0.32	0.45	0.012	0.013	0.018
c	0.10	0.15	0.20	0.004	0.006	0.008
D	2.95	3.05	3.10	0.116	0.120	0.122
E	2.70	2.85	2.98	0.106	0.112	0.117
E ₁	1.55	1.65	1.70	0.061	0.065	0.067
e	1.00 BSC			0.0394 BSC		
L	0.35	–	0.50	0.014	–	0.020
L ₁	0.60 Ref			0.024 Ref		
L ₂	0.25 BSC			0.010 BSC		
R	0.10	–	–	0.004	–	–
θ	0°	4°	8°	0°	4°	8°
θ ₁	7° Nom			7° Nom		