

## Dual P-Channel 20-V (D-S) MOSFET

### Key Features:

- Low  $r_{DS(on)}$  trench technology
- Low thermal impedance
- Fast switching speed



### Typical Applications:

- Battery Powered Instruments
- Portable Computing
- Mobile Phones
- GPS Units and Media Players



PRODUCT SUMMARY		
$V_{DS}$ (V)	$r_{DS(on)}$ (m $\Omega$ )	$I_D$ (A)
-20	79 @ $V_{GS} = -4.5V$	-4.2
	110 @ $V_{GS} = -2.5V$	-3.6

DFN2x2-6L



P-Channel MOSFET

ABSOLUTE MAXIMUM RATINGS ( $T_A = 25^\circ C$ UNLESS OTHERWISE NOTED)				
Parameter		Symbol	Limit	Units
Drain-Source Voltage		$V_{DS}$	-20	V
Gate-Source Voltage		$V_{GS}$	$\pm 8$	
Continuous Drain Current <sup>a</sup>	$T_A = 25^\circ C$	$I_D$	-4.2	A
	$T_A = 70^\circ C$		-3.3	
Pulsed Drain Current <sup>b</sup>		$I_{DM}$	-10	
Continuous Source Current (Diode Conduction) <sup>a</sup>		$I_S$	-2.3	A
Power Dissipation <sup>a</sup>	$T_A = 25^\circ C$	$P_D$	2.1	W
	$T_A = 70^\circ C$		1.3	
Operating Junction and Storage Temperature Range		$T_J, T_{stg}$	-55 to 150	$^\circ C$

THERMAL RESISTANCE RATINGS				
Parameter		Symbol	Maximum	Units
Maximum Junction-to-Ambient <sup>a</sup>	$t \leq 10$ sec	$R_{\theta JA}$	60	$^\circ C/W$
	Steady State		110	

Notes

- a. Surface Mounted on 1" x 1" FR4 Board.
- b. Pulse width limited by maximum junction temperature

## Electrical Characteristics


Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
<b>Static</b>						
Gate-Source Threshold Voltage	$V_{GS(th)}$	$V_{DS} = V_{GS}, I_D = -250 \mu A$	-0.4			V
Gate-Body Leakage	$I_{GSS}$	$V_{DS} = 0 V, V_{GS} = \pm 8 V$			$\pm 100$	nA
Zero Gate Voltage Drain Current	$I_{DSS}$	$V_{DS} = -16 V, V_{GS} = 0 V$			1	uA
		$V_{DS} = -16 V, V_{GS} = 0 V, T_J = 55^\circ C$			10	
On-State Drain Current	$I_{D(on)}$	$V_{DS} = -5 V, V_{GS} = -4.5 V$	-10			A
Drain-Source On-Resistance	$r_{DS(on)}$	$V_{GS} = -4.5 V, I_D = -3.4 A$			79	m $\Omega$
		$V_{GS} = -2.5 V, I_D = -2.9 A$			110	
Forward Transconductance	$g_{fs}$	$V_{DS} = -15 V, I_D = -3.4 A$		10		S
Diode Forward Voltage	$V_{SD}$	$I_S = -1.2 A, V_{GS} = 0 V$		-0.74		V
<b>Dynamic</b>						
Total Gate Charge	$Q_g$	$V_{DS} = -10 V, V_{GS} = -4.5 V,$ $I_D = -3.4 A$		7.6		nC
Gate-Source Charge	$Q_{gs}$			1.5		
Gate-Drain Charge	$Q_{gd}$			2.5		
Turn-On Delay Time	$t_{d(on)}$	$V_{DD} = -10 V, R_L = 2.9 \Omega, I_D = -3.4 A,$ $V_{GEN} = -4.5 V, R_{GEN} = 6 \Omega$		7		ns
Rise Time	$t_r$			21		
Turn-Off Delay Time	$t_{d(off)}$			31		
Fall Time	$t_f$			22		
Input Capacitance	$C_{iss}$	$V_{DS} = -15 V, V_{GS} = 0 V, f = 1 MHz$		677		pF
Output Capacitance	$C_{oss}$			92		
Reverse Transfer Capacitance	$C_{rss}$			80		

## Notes


- Pulse test: PW  $\leq$  300us duty cycle  $\leq$  2%.
- Guaranteed by design, not subject to production testing.

**Analog Power (APL) reserves the right to make changes without further notice to any products herein. APL makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does APL assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. "Typical" parameters which may be provided in APL data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. APL does not convey any license under its patent rights nor the rights of others. APL products are not designed, intended, or authorized for use as components in systems intended for surgical implant into the body, or other applications intended to support or sustain life, or for any other application in which the failure of the APL product could create a situation where personal injury or death may occur. Should Buyer purchase or use APL products for any such unintended or unauthorized application, Buyer shall indemnify and hold APL and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that APL was negligent regarding the design or manufacture of the part. APL is an Equal Opportunity/Affirmative Action Employer.**


Typical Electrical Characteristics




1. On-Resistance vs. Drain Current




2. Transfer Characteristics




3. On-Resistance vs. Gate-to-Source Voltage



4. Drain-to-Source Forward Voltage




5. Output Characteristics



6. Capacitance


Typical Electrical Characteristics




7. Gate Charge




8. Normalized On-Resistance Vs Junction Temperature



9. Safe Operating Area




10. Single Pulse Maximum Power Dissipation



11. Normalized Thermal Transient Junction to Ambient

Package Information



SYMBOL	DIMENSIONS IN MILLIMETERS			DIMENSIONS IN INCHES		
	MIN.	NOM.	MAX.	MIN.	NOM.	MAX.
A	0.70	0.75	0.80	0.028	0.030	0.032
A1	0.00	0.02	0.05	0.000	0.001	0.002
A3	---	0.20 ref	---	---	0.008 ref	---
b	0.25	0.30	0.35	0.010	0.012	0.014
D	2.00 BSC			0.079 BSC		
D2	0.60	0.65	0.70	0.024	0.026	0.028
D3	0.60	0.65	0.70	0.024	0.026	0.028
E	2.00 BSC			0.079 BSC		
E2	0.81	0.86	0.91	0.032	0.034	0.036
⊕	0.65 BSC			0.026 BSC		
L	0.25	0.30	0.35	0.010	0.012	0.014
F	0.20 REF			0.008 REF		
f	45°			45°		
G	0.15	0.20	0.25	0.006	0.008	0.010
ddd	0.15			0.006		
bbb	0.10			0.004		