

## PowerMOS transistor TOPFET

BUK108-50GS

### DESCRIPTION

Monolithic temperature and overload protected power MOSFET in a 3 pin plastic surface mount envelope, intended as a general purpose switch for automotive systems and other applications.

### APPLICATIONS

General controller for driving

- lamps
- motors
- solenoids
- heaters

### QUICK REFERENCE DATA

SYMBOL	PARAMETER	MAX.	UNIT
$V_{DS}$	Continuous drain source voltage	50	V
$I_D$	Continuous drain current	15	A
$P_D$	Total power dissipation	40	W
$T_j$	Continuous junction temperature	150	°C
$R_{DS(ON)}$	Drain-source on-state resistance $V_{IS} = 10 \text{ V}$	100	$\text{m}\Omega$

### FEATURES

- Vertical power DMOS output stage
- Low on-state resistance
- Overload protection against over temperature
- Overload protection against short circuit load
- Latched overload protection reset by input
- 10 V input level
- Low threshold voltage also allows 5 V control
- Control of power MOSFET and supply of overload protection circuits derived from input
- ESD protection on input pin
- Overvoltage clamping for turn off of inductive loads

### FUNCTIONAL BLOCK DIAGRAM





Fig.1. Elements of the TOPFET.


### PINNING - SOT404

PIN	DESCRIPTION
1	input
2	drain
3	source
mb	drain

### PIN CONFIGURATION



### SYMBOL



## PowerMOS transistor TOPFET

BUK108-50GS

### LIMITING VALUES

Limiting values in accordance with the Absolute Maximum Rating System (IEC 134)

SYMBOL	PARAMETER	CONDITIONS	MIN.	MAX.	UNIT
$V_{DSS}$	Continuous off-state drain source voltage <sup>1</sup>	$V_{IS} = 0 \text{ V}$	-	50	V
$V_{IS}$	Continuous input voltage	-	0	11	V
$I_D$	Continuous drain current	$T_{mb} \leq 25 \text{ }^\circ\text{C}; V_{IS} = 10 \text{ V}$	-	15	A
$I_D$	Continuous drain current	$T_{mb} \leq 100 \text{ }^\circ\text{C}; V_{IS} = 10 \text{ V}$	-	9.5	A
$I_{DRM}$	Repetitive peak on-state drain current	$T_{mb} \leq 25 \text{ }^\circ\text{C}; V_{IS} = 10 \text{ V}$	-	60	A
$P_D$	Total power dissipation	$T_{mb} \leq 25 \text{ }^\circ\text{C}$	-	40	W
$T_{stg}$	Storage temperature	-	-55	150	$^\circ\text{C}$
$T_j$	Continuous junction temperature <sup>2</sup>	normal operation	-	150	$^\circ\text{C}$
$T_{sold}$	Lead temperature	during soldering	-	250	$^\circ\text{C}$

### OVERLOAD PROTECTION LIMITING VALUES

With the protection supply provided via the input pin, TOPFET can protect itself from two types of overload.

SYMBOL	PARAMETER	CONDITIONS	MIN.	MAX.	UNIT
$V_{ISP}$	Protection supply voltage <sup>3</sup>	for valid protection	5	-	V
$V_{DDP(T)}$	<b>Over temperature protection</b>				
	Protected drain source supply voltage	$V_{IS} = 10 \text{ V}$	-	50	V
$V_{DDP(P)}$	<b>Short circuit load protection</b>				
	Protected drain source supply voltage <sup>4</sup>	$V_{IS} = 10 \text{ V}$	-	20	V
		$V_{IS} = 5 \text{ V}$	-	35	V
$P_{DSM}$	Instantaneous overload dissipation	$T_{mb} = 25 \text{ }^\circ\text{C}$	-	0.6	kW

### OVERVOLTAGE CLAMPING LIMITING VALUES

At a drain source voltage above 50 V the power MOSFET is actively turned on to clamp overvoltage transients.

SYMBOL	PARAMETER	CONDITIONS	MIN.	MAX.	UNIT
$I_{DROM}$	Repetitive peak clamping current	$V_{IS} = 0 \text{ V}$	-	15	A
$E_{DSM}$	Non-repetitive clamping energy	$T_{mb} \leq 25 \text{ }^\circ\text{C}; I_{DM} = 15 \text{ A}; V_{DD} \leq 20 \text{ V}; \text{inductive load}$	-	200	mJ
$E_{DRM}$	Repetitive clamping energy	$T_{mb} \leq 95 \text{ }^\circ\text{C}; I_{DM} = 4 \text{ A}; V_{DD} \leq 20 \text{ V}; f = 250 \text{ Hz}$	-	20	mJ

### ESD LIMITING VALUE

SYMBOL	PARAMETER	CONDITIONS	MIN.	MAX.	UNIT
$V_C$	Electrostatic discharge capacitor voltage	Human body model; $C = 250 \text{ pF}; R = 1.5 \text{ k}\Omega$	-	2	kV

<sup>1</sup> Prior to the onset of overvoltage clamping. For voltages above this value, safe operation is limited by the overvoltage clamping energy.

<sup>2</sup> A higher  $T_j$  is allowed as an overload condition but at the threshold  $T_{j(TO)}$  the over temperature trip operates to protect the switch.

<sup>3</sup> The input voltage for which the overload protection circuits are functional.

<sup>4</sup> The device is able to self-protect against a short circuit load providing the drain-source supply voltage does not exceed  $V_{DD(P)}$  maximum.  
For further information, refer to OVERLOAD PROTECTION CHARACTERISTICS.

**PowerMOS transistor  
TOPFET**
**BUK108-50GS**
**THERMAL CHARACTERISTICS**

SYMBOL	PARAMETER	CONDITIONS	MIN.	TYP.	MAX.	UNIT
$R_{th\ j\cdot mb}$	<b>Thermal resistance</b> Junction to mounting base	-	-	2.5	3.1	K/W
	Junction to ambient	minimum footprint FR4 PCB (see fig. 33)		50	-	K/W

**STATIC CHARACTERISTICS**
 $T_{mb} = 25^\circ C$  unless otherwise specified

SYMBOL	PARAMETER	CONDITIONS	MIN.	TYP.	MAX.	UNIT
$V_{(CL)DSS}$	Drain-source clamping voltage	$V_{IS} = 0 V; I_D = 10 \text{ mA}$	50	-	-	V
	Drain-source clamping voltage	$V_{IS} = 0 V; I_{DM} = 1 A; t_p \leq 300 \mu s; \delta \leq 0.01$	-	-	70	V
	Zero input voltage drain current	$V_{DS} = 12 V; V_{IS} = 0 V$	-	0.5	10	$\mu A$
$I_{DSS}$	Zero input voltage drain current	$V_{DS} = 50 V; V_{IS} = 0 V$	-	1	20	$\mu A$
$I_{DSS}$	Zero input voltage drain current	$V_{DS} = 40 V; V_{IS} = 0 V; T_j = 125^\circ C$	-	10	100	$\mu A$
$R_{DS(ON)}$	Drain-source on-state resistance	$I_{DM} = 7.5 A; t_p \leq 300 \mu s; \delta \leq 0.01$	-	65	100	$m\Omega$
		$V_{IS} = 10 V$	-	85	125	$m\Omega$
		$V_{IS} = 5 V$	-			

**OVERLOAD PROTECTION CHARACTERISTICS**

TOPFET switches off when one of the overload thresholds is reached. It remains latched off until reset by the input.

SYMBOL	PARAMETER	CONDITIONS	MIN.	TYP.	MAX.	UNIT
$E_{DS(TO)}$	<b>Short circuit load protection<sup>1</sup></b> Overload threshold energy	$T_{mb} = 25^\circ C; L \leq 10 \mu H$	-	0.2	-	J
$t_{d\ sc}$	Response time	$V_{DD} = 13 V; V_{IS} = 10 V$	-	0.8	-	ms
$V_{DD} = 13 V; V_{IS} = 10 V$						
$T_{j(TO)}$	<b>Over temperature protection</b> Threshold junction temperature	$V_{IS} = 10 V; \text{from } I_D \geq 0.5 A^2$	150	-	-	$^\circ C$

<sup>1</sup> The short circuit load protection is able to save the device providing the instantaneous on-state dissipation is less than the limiting value for  $P_{DSM}$ , which is always the case when  $V_{DS}$  is less than  $V_{DSP}$  maximum. Refer to OVERLOAD PROTECTION LIMITING VALUES.

<sup>2</sup> The over temperature protection feature requires a minimum on-state drain source voltage for correct operation. The specified minimum  $I_D$  ensures this condition.

## PowerMOS transistor TOPFET

BUK108-50GS

### INPUT CHARACTERISTICS

$T_{mb} = 25^\circ\text{C}$  unless otherwise specified. The supply for the logic and overload protection is taken from the input.

SYMBOL	PARAMETER	CONDITIONS	MIN.	TYP.	MAX.	UNIT
$V_{IS(TO)}$	Input threshold voltage	$V_{DS} = 5\text{ V}; I_D = 1\text{ mA}$	1.0	1.5	2.0	V
$I_{IS}$	Input supply current	$V_{IS} = 10\text{ V}$ ; normal operation	-	0.4	1.0	mA
$V_{ISR}$	Protection reset voltage <sup>1</sup>		2.0	2.6	3.5	V
$V_{ISR}$	Protection reset voltage	$T_j = 150^\circ\text{C}$	1.0	-	-	
$I_{ISL}$	Input supply current	$V_{IS} = 10\text{ V}$ ; protection latched	1.0	2.5	5.0	mA
$V_{(BR)IS}$	Input clamp voltage	$I_I = 10\text{ mA}$	11	13	-	V
$R_{IG}$	Input series resistance	to gate of power MOSFET	-	4	-	kΩ

### TRANSFER CHARACTERISTICS

$T_{mb} = 25^\circ\text{C}$

SYMBOL	PARAMETER	CONDITIONS	MIN.	TYP.	MAX.	UNIT
$g_{fs}$	Forward transconductance	$V_{DS} = 10\text{ V}; I_{DM} = 7.5\text{ A}$ $t_p \leq 300\text{ }\mu\text{s}$ ; $\delta \leq 0.01$	5	9	-	S
$I_{D(SC)}$	Drain current <sup>2</sup>	$V_{DS} = 13\text{ V}; V_{IS} = 10\text{ V}$	-	40	-	A

### SWITCHING CHARACTERISTICS

$T_{mb} = 25^\circ\text{C}$ .  $R_L = 50\Omega$ . Refer to waveform figures and test circuits.

SYMBOL	PARAMETER	CONDITIONS	MIN.	TYP.	MAX.	UNIT
$t_{d(on)}$	Turn-on delay time	$V_{DD} = 13\text{ V}; V_{IS} = 10\text{ V}$ resistive load $R_L = 4\Omega$	-	1	-	μs
$t_r$	Rise time		-	4	-	μs
$t_{d(off)}$	Turn-off delay time	$V_{DD} = 13\text{ V}; V_{IS} = 0\text{ V}$ resistive load $R_L = 4\Omega$	-	10	-	μs
$t_f$	Fall time		-	5	-	μs
$t_{d(on)}$	Turn-on delay time	$V_{DD} = 13\text{ V}; V_{IS} = 10\text{ V}$ inductive load $I_{DM} = 3\text{ A}$	-	1	-	μs
$t_r$	Rise time		-	0.5	-	μs
$t_{d(off)}$	Turn-off delay time	$V_{DD} = 13\text{ V}; V_{IS} = 0\text{ V}$ inductive load $I_{DM} = 3\text{ A}$	-	15	-	μs
$t_f$	Fall time		-	0.5	-	μs

### REVERSE DIODE LIMITING VALUE

SYMBOL	PARAMETER	CONDITIONS	MIN.	MAX.	UNIT
$I_s$	Continuous forward current	$T_{mb} \leq 25^\circ\text{C}; V_{IS} = 0\text{ V}$	-	15	A

<sup>1</sup> The input voltage below which the overload protection circuits will be reset.

<sup>2</sup> During overload before short circuit load protection operates.

## PowerMOS transistor TOPFET

BUK108-50GS

### REVERSE DIODE CHARACTERISTICS

 $T_{mb} = 25^\circ\text{C}$ 

SYMBOL	PARAMETER	CONDITIONS	MIN.	TYP.	MAX.	UNIT
$V_{SDS}$	Forward voltage	$I_S = 15 \text{ A}; V_{IS} = 0 \text{ V}; t_p = 300 \mu\text{s}$	-	1.0	1.5	V
$t_{rr}$	Reverse recovery time	not applicable <sup>1</sup>	-	-	-	-

### ENVELOPE CHARACTERISTICS

SYMBOL	PARAMETER	CONDITIONS	MIN.	TYP.	MAX.	UNIT
$L_d$	Internal drain inductance	Measured from upper edge of tab to centre of die	-	2.5	-	nH
$L_s$	Internal source inductance	Measured from source lead soldering point to source bond pad	-	7.5	-	nH




Fig.2. Normalised limiting power dissipation.  
 $P_D\% = 100 \cdot P_D/P_D(25^\circ\text{C}) = f(T_{mb})$




Fig.4. Safe operating area.  $T_{mb} = 25^\circ\text{C}$   
 $I_D \& I_{DM} = f(V_{DS})$ ;  $I_{DM}$  single pulse; parameter  $t_p$




Fig.3. Normalised continuous drain current.  
 $I_D\% = 100 \cdot I_D/I_D(25^\circ\text{C}) = f(T_{mb})$ ; conditions:  $V_{IS} = 5 \text{ V}$






Fig.5. Transient thermal impedance.  
 $Z_{th j-mb} = f(t)$ ; parameter  $D = t_p/T$

<sup>1</sup> The reverse diode of this type is not intended for applications requiring fast reverse recovery.


# PowerMOS transistor TOPFET

**BUK108-50GS**



*Fig.6. Typical output characteristics,  $T_j = 25^\circ\text{C}$ .  
 $ID = f(V_{DS})$ ; parameter  $V_{IS}$ ;  $t_p = 250 \mu\text{s}$  &  $t_p < t_{dsc}$*




*Fig.9. Typical transfer characteristics,  $T_j = 25^\circ\text{C}$ .  
 $ID = f(V_{IS})$ ; conditions:  $V_{DS} = 10 \text{ V}$ ;  $t_p = 250 \mu\text{s}$*




*Fig.7. Typical on-state characteristics,  $T_j = 25^\circ\text{C}$ .  
 $ID = f(V_{DS})$ ; parameter  $V_{IS}$ ;  $t_p = 250 \mu\text{s}$*



*Fig.10. Typical transconductance,  $T_j = 25^\circ\text{C}$ .  
 $g_{fs} = f(I_D)$ ; conditions:  $V_{DS} = 10 \text{ V}$ ;  $t_p = 250 \mu\text{s}$*



*Fig.8. Typical on-state resistance,  $T_j = 25^\circ\text{C}$ .  
 $R_{DS(ON)} = f(I_D)$ ; parameter  $V_{IS}$ ;  $t_p = 250 \mu\text{s}$*



*Fig.11. Normalised drain-source on-state resistance.  
 $a = R_{DS(ON)}/R_{DS(ON)25^\circ\text{C}} = f(T_j)$ ;  $I_D = 7.5 \text{ A}$ ;  $V_{IS} = 5 \text{ V}$*

# PowerMOS transistor TOPFET


**BUK108-50GS**


Fig.12. Typical overload protection characteristics.  
 $t_{dsc} = f(P_{DS})$ ; conditions:  $V_{IS} \geq 5$  V;  $T_j = 25$  °C.




Fig.15. Typical clamping characteristics, 25 °C.  
 $I_D = f(V_{DS})$ ; conditions:  $V_{IS} = 0$  V;  $t_p \leq 50$  µs




Fig.13. Normalised limiting overload dissipation.  
 $P_{DSM}\% = 100 P_{DSM}/P_{DSM}(25\text{ }^{\circ}\text{C}) = f(T_{mb})$




Fig.16. Input threshold voltage.  
 $V_{IS(TO)} = f(T_j)$ ; conditions:  $I_D = 1$  mA;  $V_{DS} = 5$  V




Fig.14. Typical overload protection characteristics.  
Conditions:  $V_{DD} = 13$  V;  $V_{IS} = 10$  V; SC load = 30 mΩ




Fig.17. Typical DC input characteristics,  $T_j = 25$  °C.  
 $I_{IS} = f(V_{IS})$ ; normal operation

## PowerMOS transistor TOPFET

**BUK108-50GS**




Fig. 18. Typical DC input characteristics,  $T_j = 25^\circ\text{C}$ .  
 $I_{ISL} = f(V_{IS})$ ; overload protection operated  $\Rightarrow I_D = 0\text{ A}$




Fig. 21. Typical switching waveforms, resistive load.  
 $V_{DD} = 13\text{ V}$ ;  $R_L = 4\Omega$ ;  $R_I = 50\Omega$ ,  $T_j = 25^\circ\text{C}$ .




Fig. 19. Typical reverse diode current,  $T_j = 25^\circ\text{C}$ .  
 $I_S = f(V_{SDS})$ ; conditions:  $V_{IS} = 0\text{ V}$ ;  $t_p = 250\mu\text{s}$




Fig. 22. Typical switching waveforms, resistive load.  
 $V_{DD} = 13\text{ V}$ ;  $R_L = 4\Omega$ ;  $R_I = 50\Omega$ ,  $T_j = 25^\circ\text{C}$ .




Fig. 20. Test circuit for resistive load switching times.




Fig. 23. Test circuit for inductive load switching times.

## PowerMOS transistor TOPFET

**BUK108-50GS**




Fig.24. Typical switching waveforms, inductive load.  
 $V_{DD} = 13 \text{ V}$ ;  $I_D = 3 \text{ A}$ ;  $R_L = 50 \Omega$ ,  $T_j = 25^\circ\text{C}$ .




Fig.27. Clamping energy test circuit,  $R_{IS} = 50 \Omega$ .  
 $E_{DSM} = 0.5 \cdot L I_D^2 \cdot V_{(CL)DSS} / (V_{(CL)DSS} - V_{DD})$




Fig.25. Typical switching waveforms, inductive load.  
 $V_{DD} = 13 \text{ V}$ ;  $I_D = 3 \text{ A}$ ;  $R_L = 50 \Omega$ ,  $T_j = 25^\circ\text{C}$ .




Fig.28. Typical off-state leakage current.  
 $I_{DSS} = f(T_j)$ ; Conditions:  $V_{DS} = 40 \text{ V}$ ;  $I_{IS} = 0 \text{ V}$ .




Fig.26. Normalised limiting clamping energy.  
 $E_{DSM}\% = f(T_{mb})$ ; conditions:  $I_D = 15 \text{ A}$ ;  $V_{IS} = 10 \text{ V}$




Fig.29. Normalised input current (normal operation).  
 $I_{IS}/I_{IS,25^\circ\text{C}} = f(T_j)$ ;  $V_{IS} = 10 \text{ V}$


**PowerMOS transistor  
TOPFET****BUK108-50GS**

Fig.30. Normalised input current (protection latched).  
 $I_{ISL}/I_{ISL}25\text{ }^{\circ}\text{C} = f(T_j)$ ;  $V_{IS} = 10\text{ V}$




Fig.31. Maximum drain source supply voltage for SC load protection.  $V_{DDP(P)} = f(V_{IS})$ ;  $T_{mb} \leq 150\text{ }^{\circ}\text{C}$

**PowerMOS transistor  
TOPFET**

**BUK108-50GS**

### MECHANICAL DATA

Dimensions in mm

Net Mass: 1.4 g




Fig.32. SOT404 : centre pin connected to mounting base.

#### Notes

1. Epoxy meets UL94 V0 at 1/8".

### MOUNTING INSTRUCTIONS

Dimensions in mm




Fig.33. SOT404 : minimum pad sizes for surface mounting.

#### Notes

1. Plastic meets UL94 V0 at 1/8".

**PowerMOS transistor  
TOPFET****BUK108-50GS****DEFINITIONS**

<b>Data sheet status</b>	
Objective specification	This data sheet contains target or goal specifications for product development.
Preliminary specification	This data sheet contains preliminary data; supplementary data may be published later.
Product specification	This data sheet contains final product specifications.
<b>Limiting values</b>	
Limiting values are given in accordance with the Absolute Maximum Rating System (IEC 134). Stress above one or more of the limiting values may cause permanent damage to the device. These are stress ratings only and operation of the device at these or at any other conditions above those given in the Characteristics sections of this specification is not implied. Exposure to limiting values for extended periods may affect device reliability.	
<b>Application information</b>	
Where application information is given, it is advisory and does not form part of the specification.	
<b>© Philips Electronics N.V. 1996</b>	
All rights are reserved. Reproduction in whole or in part is prohibited without the prior written consent of the copyright owner.	
The information presented in this document does not form part of any quotation or contract, it is believed to be accurate and reliable and may be changed without notice. No liability will be accepted by the publisher for any consequence of its use. Publication thereof does not convey nor imply any license under patent or other industrial or intellectual property rights.	

**LIFE SUPPORT APPLICATIONS**

These products are not designed for use in life support appliances, devices or systems where malfunction of these products can be reasonably expected to result in personal injury. Philips customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify Philips for any damages resulting from such improper use or sale.

**This datasheet has been downloaded from:**

**[www.EEworld.com.cn](http://www.EEworld.com.cn)**

**Free Download**

**Daily Updated Database**

**100% Free Datasheet Search Site**

**100% Free IC Replacement Search Site**

**Convenient Electronic Dictionary**

**Fast Search System**

**[www.EEworld.com.cn](http://www.EEworld.com.cn)**