



Silicon PNP Epitaxial Planar Transistor

BTA1797M3

BV_{CEO}	-50V
I_C	-2A
$V_{CESAT(Max)}$	-0.2V

Description

- Low saturation voltage, $V_{CE(SAT)} = -0.2V(max.)$ at $I_C/I_B = -1A/-50mA$.
- High current capability.
- Excellent DC current gain characteristics.
- Pb-free lead plating and halogen-free package.

Symbol

Outline

Absolute Maximum Ratings ($T_a = 25^\circ C$)

Parameter	Symbol	Limits	Unit
Collector-Base Voltage	V_{CBO}	-50	V
Collector-Emitter Voltage	V_{CEO}	-50	V
Emitter-Base Voltage	V_{EBO}	-7	V
Collector Current (DC)	I_C	-2	A
Collector Current (Pulse)	I_{CP}	-5 (Note 1)	A
Power Dissipation	P_D	0.5	W
		1 (Note 2)	W
		2 (Note 3)	W
Thermal Resistance, Junction to Ambient	$R_{\theta JA}$	250	$^\circ C/W$
		125 (Note 2)	$^\circ C/W$
		62.5 (Note 3)	$^\circ C/W$
Operating Junction Temperature Range	T_j	-55~+150	$^\circ C$
Storage Temperature Range	T_{stg}	-55~+150	$^\circ C$

 Note : 1. Single Pulse $P_w \leq 300\mu s$, Duty $\leq 2\%$.

 2. When mounted on FR-4 PCB with area measuring $10 \times 10 \times 1$ mm.

 3. When mounted on ceramic with area measuring $40 \times 40 \times 1$ mm


Characteristics (Ta=25°C)

Symbol	Min.	Typ.	Max.	Unit	Test Conditions
BV_{CBO}	-50	-	-	V	$I_C=-50\mu A, I_E=0$
BV_{CEO}	-50	-	-	V	$I_C=-1mA, I_B=0$
BV_{EBO}	-7	-	-	V	$I_E=-50\mu A, I_C=0$
I_{CBO}	-	-	-100	nA	$V_{CB}=-50V, I_E=0$
I_{EBO}	-	-	-100	nA	$V_{EB}=-7V, I_C=0$
* $V_{CE(sat)}$	-	-0.1	-0.2	V	$I_C=-1A, I_B=-50mA$
* $V_{CE(sat)}$	-	-0.19	-0.5	V	$I_C=-2A, I_B=-100mA$
* $V_{BE(sat)}$	-	-0.85	-1.2	V	$I_C=-1A, I_B=-50mA$
* $V_{BE(on)}$	-	-0.78	-1	V	$V_{CE}=-2V, I_C=-1A$
h_{FE1}	180	-	-	-	$V_{CE}=-2V, I_C=-20mA$
h_{FE2}	200	-	400	-	$V_{CE}=-2V, I_C=-500mA$
h_{FE3}	120	-	-	-	$V_{CE}=-2V, I_C=-1A$
f_T	-	180	-	MHz	$V_{CE}=-2V, I_C=-300mA$
Cob	-	24	-	pF	$V_{CB}=-10V, I_E=0, f=1MHz$

*Pulse Test: Pulse Width $\leq 380\mu s$, Duty Cycle $\leq 2\%$

Ordering Information


Device	Package	Shipping
BTA1797M3-0-T2-G	SOT-89 (Pb-free lead plating and halogen-free package)	1000 pcs / Tape & Reel

Recommended soldering footprint



unit : mm

Typical Characteristics


Emitter Grounded Output Characteristics




Emitter Grounded Output Characteristics




Emitter Grounded Output Characteristics




Emitter Grounded Output Characteristics



Current Gain vs Collector Current




Current Gain vs Collector Current




Typical Characteristics(Cont.)


Current Gain vs Collector Current




Saturation Voltage vs Collector Current




Saturation Voltage vs Collector Current




Saturation Voltage vs Collector Current



Saturation Voltage vs Collector Current




On Voltage vs Collector Current




Typical Characteristics(Cont.)


Cutoff Frequency vs Collector Current




Capacitance vs Reverse-biased Voltage




Power Derating Curves



Reel Dimension



Carrier Tape Dimension




Notes:

1. 10 sprocket hole pitch cumulative tolerance ± 0.2 .
2. Camber not to exceed 1mm in 100mm.
3. Material: Conductive Black Advantek Polystyrene.
4. A_0 & B_0 measured on a plane 0.3mm above the bottom of the pocket.
5. K_0 measured from a plane on the inside bottom of the pocket to the top surface of the carrier.
6. Pocket position relative to sprocket hole measured as true position of pocket, not pocket hole.

Recommended wave soldering condition


Product	Peak Temperature	Soldering Time
Pb-free devices	260 +0/-5 °C	5 +1/-1 seconds

Recommended temperature profile for IR reflow



Profile feature	Sn-Pb eutectic Assembly	Pb-free Assembly
Average ramp-up rate (T _{smax} to T _p)	3°C/second max.	3°C/second max.
Preheat		
-Temperature Min(T _{s min})	100°C	150°C
-Temperature Max(T _{s max})	150°C	200°C
-Time(t _{s min} to t _{s max})	60-120 seconds	60-180 seconds
Time maintained above:		
-Temperature (T _L)	183°C	217°C
- Time (t _L)	60-150 seconds	60-150 seconds
Peak Temperature(T _P)	240 +0/-5 °C	260 +0/-5 °C
Time within 5°C of actual peak temperature(tp)	10-30 seconds	20-40 seconds
Ramp down rate	6°C/second max.	6°C/second max.
Time 25 °C to peak temperature	6 minutes max.	8 minutes max.

Note : All temperatures refer to topside of the package, measured on the package body surface.

SOT-89 Dimension



Marking:



Device Code → AG
 Date Code → □□

Style: Pin 1. Base 2. Collector 3. Emitter

3-Lead SOT-89 Plastic
 Surface Mounted Package
 CYStek Package Code: M3

*: Typical

DIM	Inches		Millimeters		DIM	Inches		Millimeters	
	Min.	Max.	Min.	Max.		Min.	Max.	Min.	Max.
A	0.1732	0.1811	4.40	4.60	F	0.0591	TYP	1.50	TYP
B	0.1551	0.1673	3.94	4.25	G	0.1181	TYP	3.00	TYP
C	0.0610	REF	1.55	REF	H	0.0551	0.0630	1.40	1.60
D	0.0906	0.1024	2.30	2.60	I	0.0138	0.0173	0.35	0.44
E	0.0126	0.0205	0.32	0.52					

Notes: 1. Controlling dimension: millimeters.
 2. Maximum lead thickness includes lead finish thickness, and minimum lead thickness is the minimum thickness of base material.
 3. If there is any question with packing specification or packing method, please contact your local CYStek sales office.

Material:

- Lead: Pure tin plated.
- Mold Compound: Epoxy resin family, flammability solid burning class: UL94V-0.

Important Notice:

- All rights are reserved. Reproduction in whole or in part is prohibited without the prior written approval of CYStek.
- CYStek reserves the right to make changes to its products without notice.
- CYStek **semiconductor products are not warranted to be suitable for use in Life-Support Applications, or systems.**
- CYStek assumes no liability for any consequence of customer product design, infringement of patents, or application assistance.