


# TFH2411


## Features

- Two TFS2411 chips in a SOT-363 package.
- Mounting possible with SOT-323 automatic mounting machines.
- Transistor elements are independent, eliminating interference.
- Mounting cost and area can be cut in half.
- High  $I_{C(Max)}$  .  $I_{C(Max)} = 0.6A$
- Low  $V_{CE(sat)}$  , TYP.  $V_{CE(sat)} = 0.2V$  at  $I_C/I_B = 500mA/50mA$   
Optimal for low Voltage operation
- Complementary to TFH1036

## Equivalent Circuit



## Outline



The following characteristics apply to both Tr1 and Tr2

### Absolute Maximum Ratings ( $T_a=25^{\circ}C$ )

Parameter	Symbol	Limits	Unit
Collector-Base Voltage	$V_{CBO}$	60	V
Collector-Emitter Voltage	$V_{CEO}$	40	V
Emitter-Base Voltage	$V_{EBO}$	6	V
Collector Current	$I_C$	0.6	A
Power Dissipation	$P_d$	200(total) (Note)	mW
Junction Temperature	$T_j$	150	$^{\circ}C$
Storage Temperature	$T_{stg}$	-55~+150	$^{\circ}C$

Note : 150mW per element must not be exceeded.



**Characteristics** (Ta=25°C)


Symbol	Min.	Typ.	Max.	Unit	Test Conditions
BV <sub>CBO</sub>	60	-	-	V	I <sub>C</sub> =100μA
BV <sub>CEO</sub>	40	-	-	V	I <sub>C</sub> =1mA
BV <sub>EBO</sub>	6	-	-	V	I <sub>E</sub> =10μA
I <sub>CEX</sub>	-	-	100	nA	V <sub>CE</sub> =35V, V <sub>EB</sub> =0.4V
*V <sub>CE(sat)</sub> 1	-	-	0.4	V	I <sub>C</sub> =150mA, I <sub>B</sub> =15mA
*V <sub>CE(sat)</sub> 2	-	0.2	0.75	V	I <sub>C</sub> =500mA, I <sub>B</sub> =50mA
*V <sub>BE(sat)</sub> 1	-	-	0.95	V	I <sub>C</sub> =150mA, I <sub>B</sub> =15mA
*V <sub>BE(sat)</sub> 2	-	-	1.2	V	I <sub>C</sub> =500mA, I <sub>B</sub> =50mA
h <sub>FE</sub> 1	20	-	-		V <sub>CE</sub> =1V, I <sub>C</sub> =100μA
h <sub>FE</sub> 2	40	-	-		V <sub>CE</sub> =1V, I <sub>C</sub> =1mA
*h <sub>FE</sub> 3	80	-	-		V <sub>CE</sub> =1V, I <sub>C</sub> =10mA
*h <sub>FE</sub> 4	82	-	390		V <sub>CE</sub> =1V, I <sub>C</sub> =150mA
*h <sub>FE</sub> 5	40	-	-		V <sub>CE</sub> =2V, I <sub>C</sub> =500mA
f <sub>T</sub>	-	250	-	MHz	V <sub>CE</sub> =5V, I <sub>C</sub> =20mA, f=100MHz
Cob	-	6	-	pF	V <sub>CB</sub> =5V, f=1MHz

\*Pulse Test: Pulse Width ≤380μs, Duty Cycle≤2%




### Characteristic Curves


Current Gain vs Collector Current




Saturation Voltage vs Collector Current




Saturation Voltage vs Collector Current




Cutoff Frequency vs Collector Current




Power Derating Curves




### Reel Dimension



### Carrier Tape Dimension



## SOT-363R Dimension



\*:Typical

DIM	Inches		Millimeters		DIM	Inches		Millimeters	
	Min.	Max.	Min.	Max.		Min.	Max.	Min.	Max.
A	0.071	0.087	1.8	2.2	J	0.004	0.010	0.1	0.25
B	0.045	0.053	1.15	1.35	K	0.004	0.012	0.1	0.30
C	0.031	0.043	0.8	1.1	N	0.008 REF		0.20 REF	
D	0.004	0.012	0.1	0.3	S	0.079	0.087	2.00	2.40
G	0.026BSC		0.65BSC		Y	0.012	0.016	0.30	0.40
H	-	0.004	-	0.1					

Notes : 1.Controlling dimension : millimeters.

2.Maximum lead thickness includes lead finish thickness, and minimum lead thickness is the minimum thickness of base material.

3.If there is any question with packing specification or packing method, please contact your local Tin Far sales office.

Material :

- Lead : 42 Alloy ; solder plating
- Mold Compound : Epoxy resin family, flammability solid burning class:UL94V-0

### Important Notice:

- All rights are reserved. Reproduction in whole or in part is prohibited without the prior written approval of Tin Far.
- Tin Far reserves the right to make changes to its products without notice.
- Tin Far **semiconductor products are not warranted to be suitable for use in Life-Support Applications, or systems.**
- Tin Far assumes no liability for any consequence of customer product design, infringement of patents, or application assistance.