

# Digital transistors (built-in resistors)

## PNP Silicon Surface Mount Transistor with Monolithic Bias Resistor Network

- **Applications**


Inverter, Interface, Driver

- **Features**

- 1) Built-in bias resistors enable the configuration of an inverter circuit without connecting external input resistors (see equivalent circuit).
  - 2) The bias resistors consist of thin-film resistors with complete isolation to allow positive biasing of the input. They also have the advantage of almost completely eliminating parasitic effects.
  - 3) Only the on/off conditions need to be set for operation, making the device design easy.
- We declare that the material of product compliance with RoHS requirements.

● **Absolute maximum ratings (Ta=25°C)**

Parameter	Symbol	Limits		Unit
Supply voltage	V <sub>cc</sub>	-50		V
Input voltage	V <sub>i</sub>	-30 to +5		V
Output current	I <sub>o</sub>	-100		mA
	I <sub>C(Max.)</sub>	-100		
Power dissipation	P <sub>d</sub>	200		mW
Junction temperature	T <sub>j</sub>	150		°C
Storage temperature	T <sub>stg</sub>	-55 to +150		°C



### DEVICE MARKING AND RESISTOR VALUES

Device	Marking	R1 (K)	R2 (K)	Shipping
DTA606	6K	4.7	47	3000/Tape & Reel

● **Electrical characteristics (Ta=25°C)**

Parameter	Symbol	Min.	Typ.	Max.	Unit	Condi ions
Input voltage	V <sub>i(off)</sub>	—	—	-0.5	V	V <sub>cc</sub> =-5V, I <sub>o</sub> =-100µA
	V <sub>i(on)</sub>	-1.3	—	—		V <sub>o</sub> =-0.3V, I <sub>o</sub> =-5mA
Output voltage	V <sub>O(on)</sub>	—	-0.1	-0.3	V	I <sub>o</sub> /I <sub>i</sub> =-5mA/-0.25mA
Input current	I <sub>i</sub>	—	—	-1.8	mA	V <sub>i</sub> =-5V
Output current	I <sub>O(off)</sub>	—	—	-0.5	µA	V <sub>cc</sub> =-50V, V <sub>i</sub> =0V
DC current gain	G <sub>f</sub>	80	—	—	—	V <sub>o</sub> =-5V, I <sub>o</sub> =-10mA
Input resistance	R <sub>i</sub>	3.29	4.7	6.11	kΩ	—
Resistance ratio	R <sub>2</sub> /R <sub>1</sub>	8	10	12	—	—
Transition frequency	f <sub>r</sub> □	—	250	—	MHz	V <sub>CE</sub> =-10V, I <sub>e</sub> =5mA, f=100MHz

□ Characteristics of built-in transistor

### ●Electrical characteristic curves




Fig.1 Input voltage vs. output current  
(ON characteristics)




Fig.2 Output current vs. input voltage  
(OFF characteristics)




Fig.3 DC current gain vs. output current







Fig.4 Output voltage vs. output current

**SC-89 (SOT-523)**

**NOTES:**

- 1 DIMENSIONING AND TOLERANCING PER ANSI Y14.5M, 1982
- 2 CONTROLLING DIMENSION: MILLIMETERS
- 3 MAXIMUM LEAD THICKNESS INCLUDES LEAD FINISH THICKNESS MINIMUM LEAD THICKNESS IS THE MINIMUM THICKNESS OF BASE MATERIAL
- 4 463C-01 OBSOLETE, NEW STANDARD 463C-02

DIM	MILLIMETERS			INCHES		
	MIN	NOM	MAX	MIN	NOM	MAX
A	1.50	1.60	1.70	0.059	0.063	0.067
B	0.75	0.85	0.95	0.030	0.034	0.040
C	0.60	0.70	0.80	0.024	0.028	0.031
D	0.23	0.28	0.33	0.009	0.011	0.013
G	0.50BSC			0.020BSC		
H	0.53RBF			0.021RBF		
J	0.10	0.15	0.20	0.004	0.006	0.008
K	0.30	0.40	0.50	0.012	0.016	0.020
L	1.00RBF			0.043RBF		
M	-	-	10°	-	-	10°
N	-	-	10°	-	-	10°
S	1.50	1.60	1.70	0.059	0.063	0.067


**RECOMMENDED PATTERN  
OF SOLDER PADS**