


用途:用于电视末级图象放大。/Purpose: TV final picture IF amplifier applications.

特点:增益高, h_{FE} 线性好。/Features: High gain, good linearity of h_{FE} .

极限参数/Absolute maximum ratings($T_a=25^\circ\text{C}$)

参数符号 Symbol	数值 Rating	单位 Unit
V_{CB0}	30	V
V_{CE0}	25	V
V_{EB0}	4.0	V
I_C	50	mA
I_E	-50	mA
P_C	300	mW
T_j	150	$^\circ\text{C}$
T_{stg}	-55~150	$^\circ\text{C}$



引脚: 1. B 2. E 3. C

电性能参数/Electrical characteristics($T_a=25^\circ\text{C}$)

参数符号 Symbol	测试条件 Test condition		数值 Rating			单位 Unit
			最小值 Min	典型值 Typ	最大值 Max	
V_{CE0}	$I_C=10\text{mA}$	$I_B=0$	25			V
I_{CB0}	$V_{CB}=30\text{V}$	$I_E=0$			0.1	μA
I_{EB0}	$V_{EB}=3.0\text{V}$	$I_C=0$			0.1	μA
h_{FE}	$V_{CE}=12.5\text{V}$	$I_C=12.5\text{mA}$	40		240	
$V_{CE(sat)}$	$I_C=15\text{mA}$	$I_B=1.5\text{mA}$			0.2	V
$V_{BE(sat)}$	$I_C=15\text{mA}$	$I_B=1.5\text{mA}$			1.5	V
f_T	$V_{CE}=12.5\text{V}$	$I_C=12.5\text{mA}$	300			MHz
C_{ob}	$V_{CB}=10\text{V}$	$I_E=0$ $f=30\text{MHz}$	0.8		2.0	pF
G_{pe}	$V_{CC}=12.5\text{V}$	$I_E=-12.5\text{mA}$ $f=45\text{MHz}$	28		36	dB
C_c, r_{bb}'	$V_{CB}=10\text{V}$	$I_E=-1.0\text{mA}$ $f=30\text{MHz}$			25	ps

