

MJE13003H1 (3DD13003H1)

硅 NPN 半导体三极管/SILICON NPN TRANSISTOR


用途：主要用于节能灯、日光灯电子镇流器及其它开关、振荡电路。

Purpose: High frequency electronic lighting ballast applications, converters, inverters, switching regulators, etc.

极限参数/Absolute maximum ratings(Ta=25°C)

参数符号 Symbol	数值 Rating	单位 Unit
V _{CB0}	600	V
V _{CE0}	400	V
V _{EBO}	9.0	V
I _C	1.2	A
P _C (Ta=25°C)	1.0	W
T _j	150	°C
T _{stg}	-55~150	°C

T0-92 单位:mm



引脚: 1. E 2. C 3. B

电性能参数/Electrical characteristics(Ta=25°C)

参数符号 Symbol	测试条件 Test condition	数值 Rating			单位 Unit
		最小值 Min	典型值 Typ	最大值 Max	
V _{CB0}	I _C =1mA I _E =0	600			V
V _{CE0}	I _C =10mA I _B =0	400			V
V _{EBO}	I _E =1mA I _C =0	9.0			V
I _{CB0}	V _{CB} =600V I _E =0			0.1	mA
I _{CE0}	V _{CE} =400V I _B =0			0.1	mA
I _{EBO}	V _{EB} =9.0V I _C =0			0.1	mA
h _{FE}	V _{CE} =5.0V I _C =200mA	10		40	
V _{CE(sat)}	I _C =500mA I _B =100mA			0.8	V
V _{BE(sat)}	I _C =500mA I _B =100mA			1.2	V
f _T	V _{CE} =10V I _C =100mA f=1.0MHz	5.0			MHz
t _f	V _{CE} =5V I _C =250mA			0.6	μs
t _S	(UI9600)			3.5	μs

MJE13003H1 (3DD13003H1)

