




Dual Enhancement Mode Field Effect Transistor (N and P Channel)

PRODUCT SUMMARY (N-Channel)		
VDSS	ID	RDS(ON) (mΩ) Max
30V	5.3A	46 @ VGS=10V
		65 @ VGS=4.5V

PRODUCT SUMMARY (P-Channel)		
VDSS	ID	RDS(ON) (mΩ) Max
-30V	-4.7A	56 @ VGS=-10V
		90 @ VGS=-4.5V



ABSOLUTE MAXIMUM RATINGS (TA=25°C unless otherwise noted)

Symbol	Parameter	N-Channel	P-Channel	Units	
V _{DS}	Drain-Source Voltage	30	-30	V	
V _{GS}	Gate-Source Voltage	±20	±20	V	
I _D	Drain Current-Continuous ^a	TA=25°C	5.3	-4.7	A
		TA=70°C	4.2	-3.8	A
I _{DM}	-Pulsed ^b	19	-17	A	
P _D	Maximum Power Dissipation ^a	TA=25°C	2.0	W	
		TA=70°C	1.28	W	
T _J , T _{STG}	Operating Junction and Storage Temperature Range	-55 to 150		°C	

THERMAL CHARACTERISTICS

R _{θJA}	Thermal Resistance, Junction-to-Ambient ^a	62.5	°C/W
------------------	--	------	------

STM8300

Ver 1.0

N-Channel ELECTRICAL CHARACTERISTICS (TA=25°C unless otherwise noted)

Symbol	Parameter	Conditions	Min	Typ	Max	Units
OFF CHARACTERISTICS						
BV _{DSS}	Drain-Source Breakdown Voltage	V _{GS} =0V , I _D =250uA	30			V
I _{DSS}	Zero Gate Voltage Drain Current	V _{DS} =24V , V _{GS} =0V			1	uA
I _{GSS}	Gate-Body Leakage Current	V _{GS} = ±20V , V _{DS} =0V			±100	nA
ON CHARACTERISTICS						
V _{GS(th)}	Gate Threshold Voltage	V _{DS} =V _{GS} , I _D =250uA	1	1.6	3	V
R _{DS(ON)}	Drain-Source On-State Resistance	V _{GS} =10V , I _D =5.3A		38	46	m ohm
		V _{GS} =4.5V , I _D =4.5A		48	65	m ohm
g _{FS}	Forward Transconductance	V _{DS} =5V , I _D =5.3A		10		S
DYNAMIC CHARACTERISTICS ^c						
C _{ISS}	Input Capacitance	V _{DS} =15V, V _{GS} =0V f=1.0MHz		310		pF
C _{OSS}	Output Capacitance			73		pF
C _{RSS}	Reverse Transfer Capacitance			44		pF
SWITCHING CHARACTERISTICS ^c						
t _{D(ON)}	Turn-On Delay Time	V _{DD} =15V I _D =1A V _{GS} =10V R _{GEN} =6 ohm		7.5		ns
t _r	Rise Time			9.5		ns
t _{D(OFF)}	Turn-Off Delay Time			16		ns
t _f	Fall Time			13		ns
Q _g	Total Gate Charge	V _{DS} =15V, I _D =5.3A, V _{GS} =10V		5.3		nC
		V _{DS} =15V, I _D =5.3A, V _{GS} =4.5V		2.8		nC
Q _{gs}	Gate-Source Charge	V _{DS} =15V, I _D =5.3A,		0.9		nC
Q _{gd}	Gate-Drain Charge	V _{GS} =10V		1.2		nC
DRAIN-SOURCE DIODE CHARACTERISTICS						
I _S	Maximum Continuous Drain-Source Diode Forward Current				1	A
V _{SD}	Diode Forward Voltage ^b	V _{GS} =0V, I _S =1A		0.79	1.2	V

Jul,31,2008

STM8300

Ver 1.0

P-Channel ELECTRICAL CHARACTERISTICS (TA=25°C unless otherwise noted)

Symbol	Parameter	Conditions	Min	Typ	Max	Units
OFF CHARACTERISTICS						
BV _{DSS}	Drain-Source Breakdown Voltage	V _{GS} =0V , I _D =-250uA	-30			V
I _{DSS}	Zero Gate Voltage Drain Current	V _{DS} =-24V , V _{GS} =0V			-1	uA
I _{GSS}	Gate-Body Leakage Current	V _{GS} = ±20V , V _{DS} =0V			±100	nA
ON CHARACTERISTICS						
V _{GS(th)}	Gate Threshold Voltage	V _{DS} =V _{GS} , I _D =-250uA	-1.0	-1.8	-3.0	V
R _{DS(ON)}	Drain-Source On-State Resistance	V _{GS} =-10V , I _D =-4.7A		46	56	m ohm
		V _{GS} =-4.5V , I _D =-3.7A		68	90	m ohm
g _{FS}	Forward Transconductance	V _{DS} =-5V , I _D =-4.7A		7.5		S
DYNAMIC CHARACTERISTICS °						
C _{ISS}	Input Capacitance	V _{DS} =-15V, V _{GS} =0V f=1.0MHz		520		pF
C _{OSS}	Output Capacitance			125		pF
C _{RSS}	Reverse Transfer Capacitance			78		pF
SWITCHING CHARACTERISTICS °						
t _{D(ON)}	Turn-On Delay Time	V _{DD} =-15V I _D =-1A		7.5		ns
t _r	Rise Time			12.4		ns
t _{D(OFF)}	Turn-Off Delay Time	V _{GS} =-10V R _{GEN} =6 ohm		62		ns
t _f	Fall Time			37		ns
Q _g	Total Gate Charge	V _{DS} =-15V, I _D =-4.7A, V _{GS} =-10V		10.3		nC
		V _{DS} =-15V, I _D =-4.7A, V _{GS} =-4.5V		5.2		nC
Q _{gs}	Gate-Source Charge	V _{DS} =-15V, I _D =-4.7A, V _{GS} =-10V		1.1		nC
Q _{gd}	Gate-Drain Charge			2.8		nC
DRAIN-SOURCE DIODE CHARACTERISTICS						
I _S	Maximum Continuous Drain-Source Diode Forward Current				-1	A
V _{SD}	Diode Forward Voltage ^b	V _{GS} =0V, I _S =-1A		-0.77	-1.2	V

Notes

- a. Surface Mounted on FR4 Board, t ≤ 10sec.
b. Pulse Test: Pulse Width ≤ 300us, Duty Cycle ≤ 2%.
c. Guaranteed by design, not subject to production testing.

Jul,31,2008

N-Channel




Figure 1. Output Characteristics




Figure 2. Transfer Characteristics




Figure 3. On-Resistance vs. Drain Current and Gate Voltage




Figure 4. On-Resistance Variation with Drain Current and Temperature




Figure 5. Gate Threshold Variation with Temperature




Figure 6. Breakdown Voltage Variation with Temperature




Figure 7. On-Resistance vs. Gate-Source Voltage




Figure 8. Body Diode Forward Voltage Variation with Source Current




Figure 9. Capacitance




Figure 10. Gate Charge




Figure 11. switching characteristics






Figure 12. Maximum Safe Operating Area




Unclamped Inductive Test Circuit

Figure 13a.



Unclamped Inductive Waveforms

Figure 13b.



P-Channel




Figure 1. Output Characteristics




Figure 2. Transfer Characteristics




Figure 3. On-Resistance vs. Drain Current and Gate Voltage




Figure 4. On-Resistance Variation with Drain Current and Temperature




Figure 5. Gate Threshold Variation with Temperature




Figure 6. Breakdown Voltage Variation with Temperature




Figure 7. On-Resistance vs. Gate-Source Voltage




Figure 8. Body Diode Forward Voltage Variation with Source Current




Figure 9. Capacitance




Figure 10. Gate Charge




Figure 11. switching characteristics






Figure 12. Maximum Safe Operating Area




Unclamped Inductive Test Circuit

Figure 13a.




Unclamped Inductive Waveforms

Figure 13b.



PACKAGE OUTLINE DIMENSIONS


SO-8



SYMBOLS	MILLIMETERS		INCHES	
	MIN	MAX	MIN	MAX
A	1.35	1.75	0.053	0.069
A1	0.10	0.25	0.004	0.010
D	4.80	4.98	0.189	0.196
E	3.81	3.99	0.150	0.157
H	5.79	6.20	0.228	0.244
L	0.41	1.27	0.016	0.050
θ	0°	8°	0°	8°

SO-8 Tape and Reel Data


SO-8 Carrier Tape



unit:mm

PACKAGE	A0	B0	K0	D0	D1	E	E1	E2	P0	P1	P2	T
SOP 8N 150mil	6.50 ±0.15	5.25 ±0.10	2.10 ±0.10	φ 1.5 (MIN)	φ 1.55 ±0.10	12.0 +0.3 - 0.1	1.75 ±0.10	5.5 ±0.10	8.0 ±0.10	4.0 ±0.10	2.0 ±0.10	0.30 ±0.013

SO-8 Reel



UNIT:mm

TAPE SIZE	REEL SIZE	M	N	W	W1	H	K	S	G	R	V
12 mm	φ 330	330 ± 1	62 ±1.5	12.4 + 0.2	16.8 - 0.4	φ 12.75 + 0.15	---	2.0 ±0.15	---	---	---