

■ Features


- Low forward voltage drop.
- Excellent high temperature stability.
- Fast switching capability.
- Suffix "G" indicates Halogen-free part, ex. CF20L120CTG.
- Lead-free parts meet environmental standards of MIL-STD-19500 /228

■ Mechanical data

- Epoxy : UL94-V0 rated flame retardant.
- Case : JEDEC ITO-220AB molded plastic body.
- Terminals : Solder plated, solderable per MIL-STD-750, Method 2026.
- Polarity: As marked.
- Mounting Position : Any.
- Weight : Approximated 2.25 gram.

■ Outline

ITO-220AB



■ Maximum ratings and electrical characteristics

Rating at 25°C ambient temperature unless otherwise specified. Single phase, half wave, 60Hz, resistive or inductive load. For capacitive load, derate current by 20%.

| Parameter | Conditions | Symbol | CF20L120CT | | | UNIT |
|--|--|----------------|------------|-------|------|------|
| Marking code | | | CF20L120CT | | | |
| Peak repetitive reverse voltage | | V_{RRM} | 120 | | | V |
| Working peak reverse voltage | | V_{RWM} | | | | |
| DC blocking voltage | | V_{RM} | | | | |
| Forward rectified current (total device) | | I_O | 20 | | | A |
| Forward surge current (per diode) | 8.3ms single half sine-wave superimposed on rate load (JEDEC method) | I_{FSM} | 120 | | | A |
| Operating and Storage temperature | | T_J, T_{STG} | -40 ~ +150 | | | °C |
| Parameter | Conditions | Symbol | MIN. | TYP. | MAX. | UNIT |
| Breakdown voltage (per diode) | $I_R = 1mA, T_J = 25^\circ C$ | V_{BR} | 120 | | | V |
| Forward voltage drop (per diode) | $I_F = 5A, T_J = 25^\circ C$ | V_F | | 620 | | mV |
| | $I_F = 10A, T_J = 25^\circ C$ | | | 810 | 900 | |
| | $I_F = 5A, T_J = 125^\circ C$ | | | 540 | | |
| | $I_F = 10A, T_J = 125^\circ C$ | | | 640 | 720 | |
| Reverse current (per diode) | $V_R = 90V, T_J = 25^\circ C$ | I_R | | 0.008 | | mA |
| | $V_R = 90V, T_J = 125^\circ C$ | | | 6 | | |
| | $V_R = 120V, T_J = 25^\circ C$ | | | | 0.7 | |
| | $V_R = 120V, T_J = 125^\circ C$ | | | 14 | 45 | |

Note : 1. Thermal resistance from junction to case per leg, with heatsink size(1.35" x 0.95" x 0.18") Al-plate.

■ Rating and characteristic curves

Fig. 1 - Forward Current Derating Curve (per diode)




Fig. 2 - Instantaneous Forward Characteristics (per diode)




Fig. 3 - Reverse Characteristics (per diode)





Fig. 4 - Typical Junction Capacitance (per diode)



- CITC reserves the right to make changes to this document and its products and specifications at any time without notice.
- Customers should obtain and confirm the latest product information and specifications before final design, purchase or use.
- CITC makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does CITC assume any liability for application assistance or customer product design.
- CITC does not warrant or accept any liability with products which are purchased or used for any unintended or unauthorized application.
- No license is granted by implication or otherwise under any intellectual property rights of CITC.
- CITC products are not authorized for use as critical components in life support devices or systems without express written approval of CITC.