

■ Features


- Fast switching speed.
- Electrically identical to standard JEDEC.
- Surface mount package ideally suited for automatic insertion.
- Tiny plastic SMD package.
- Silicon epitaxial planar chip.
- Suffix "G" indicates Halogen-free part, ex. 1SS355G.
- Lead-free parts meet environmental standards of MIL-STD-19500 /228

■ Mechanical data

- Epoxy: UL94-V0 rated flame retardant
- Case : Molded plastic, SOD-323
- Terminals : Solder plated, solderable per MIL-STD-750, Method 2026
- Polarity : Indicated by cathode band
- Weight : 0.0002 ounce, 0.005 gram

■ Outline

SOD-323



Dimensions in inches and (millimeters)

■ Maximum ratings and electrical characteristics

Rating at 25°C ambient temperature unless otherwise specified. Single phase, half wave, 60Hz, resistive or inductive load. For capacitive load, derate current by 20%.

Parameter	Symbol	1SS355	UNIT
Marking code		5D	
Repetitive peak reverse voltage	V_{RM}	90	V
DC reverse voltage ($I_R = 100\mu A$)	V_R	80	
Peak Forward current	I_{FM}	225	mA
Forward current	I_O	100	mA
Power dissipation	P_D	225	mW
Peak forward surge current $t = 1s$	I_{FSM}	500	mA
Junction temperature	T_J	125	°C
Storage temperature	T_{STG}	-55 ~ +125	

Parameter	Conditions	Symbol	MIN.	TYP.	MAX.	UNIT
Forward voltage	$I_F = 100mA$	V_F			1.2	V
Reverse current	$V_R = 80V$	I_R			0.1	μA
Diode capacitance	$V_R = 0.5V, f = 1MHz$	C_D			3.5	pF
Reverse recovery time	$V_R = 6V, I_F = 10mA, R_L = 100\Omega$	T_{rr}			4.0	ns

■ Rating and characteristic curves

FIG.1-TYPICAL FORWARD CHARACTERISTICS




FIG.3 - TYPICAL REVERSE CHARACTERISTICS






FIG.2 - TYPICAL DIODE CAPACITANCE



■ SOD-323 foot print



A	B	C
0.059 (1.50)	0.039 (1.00)	0.051 (1.30)

Dimensions in inches and (millimeters)

- CITC reserves the right to make changes to this document and its products and specifications at any time without notice.
- Customers should obtain and confirm the latest product information and specifications before final design, purchase or use.
- CITC makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does CITC assume any liability for application assistance or customer product design.
- CITC does not warrant or accept any liability with products which are purchased or used for any unintended or unauthorized application.
- No license is granted by implication or otherwise under any intellectual property rights of CITC.
- CITC products are not authorized for use as critical components in life support devices or systems without express written approval of CITC.