

### ■ Features


- Fast switching.
- ESD improved capability.
- Low gate charge.
- Low reverse transfer capacitances.
- 100% single pulse avalanche energy test.

### ■ Mechanical data

- Epoxy : UL94-V0 rated flame retardant.
- Case : JEDEC TO-220F molded plastic body.
- Terminals : Solder plated, solderable per MIL-STD-750, Method 2026.
- Polarity: As marked.
- Mounting Position : Any.
- Weight : Approximated 2.25 gram.

### ■ Outline

TO-220F



Dimensions in inches and (millimeters)

### ■ Absolute( $T_c = 25^\circ\text{C}$ unless otherwise specified)

PARAMETER	CONDITIONS	Symbol	CS8N60FA9H	UNIT
Drain-Source Voltage		$V_{DSS}$	600	V
Continuous Drain Current		$I_D$	8	A
Continuous Drain Current	$T_c = 100^\circ\text{C}$		5.5	
Pulsed Drain Current(1)		$I_{DM}$	32	
Gate-Source Voltage		$V_{GS}$	$\pm 30$	
Single Pulse Avalanche Energy(2)		$E_{AS}$	600	mJ
Avalanche Current(1)		$I_{AR}$	3.5	A
Repetitive Avalanche Energy(1)		$E_{AR}$	60	mJ
Power Dissipation		$P_D$	45	W
	Derating factor above $25^\circ\text{C}$		0.36	$\text{W}/^\circ\text{C}$
Peak Diode Recovery $dv/dt$ (3)		$dV/dt$	5.0	V/ns
Operating and Storage Temperature Range		$T_J, T_{STG}$	-55 ~ +150	$^\circ\text{C}$
Maximum temperature for soldering		$T_L$	300	$^\circ\text{C}$

NOTE : 1.Repetitive rating; pulse width limited by maximum junction temperature.

2. $L=10.0\text{mH}$ ,  $I_0 = 10.9\text{A}$ , Start  $T_j = 25^\circ\text{C}$ .3. $I_{SD} = 8\text{A}, di/dt \leq 100\text{A/us}$ ,  $V_{DD} \leq BV_{DS}$ , Start  $T_j = 25^\circ\text{C}$ .

■ Electrical characteristics( $T_c = 25^\circ\text{C}$  unless otherwise specified)

PARAMETER	CONDITIONS	Symbol	MIN.	TYP.	MAX.	UNIT
Drain-Source Breakdown Voltage	$V_{GS} = 0\text{V}, I_D = 250\mu\text{A}$	$V_{DSS}$	600			V
Bvdss Temperature Coefficient	$I_D = 250\mu\text{A}$ , Reference $25^\circ\text{C}$	$\text{BV}_{DSS}/T_J$		0.74		$^\circ\text{C}$
Drain-Source Leakage Current	$V_{DS} = 600\text{V}, V_{GS} = 0\text{V}, T_a = 25^\circ\text{C}$	$I_{DSS}$			1	uA
	$V_{DS} = 480\text{V}, V_{GS} = 0\text{V}, T_a = 125^\circ\text{C}$				100	
Gate-Source Leakage Current, Forward	$V_{GS} = 30\text{V}$	$I_{GSS(F)}$			100	nA
Gate-Source Leakage Current, Reverse	$V_{GS} = -30\text{V}$	$I_{GSS(R)}$			-100	

## ■ ON Characteristics

PARAMETER	CONDITIONS	Symbol	MIN.	TYP.	MAX.	UNIT
Gate Threshold Voltage	$V_{DS} = V_{GS}, I_D = 250\mu\text{A}$	$V_{GS(\text{th})}$	2.0		4.0	V
Static Drain-Source On-Resistance	$V_{GS} = 10\text{V}, I_D = 4\text{A}$	$R_{DS(on)}$		0.8	1.2	$\Omega$

## ■ Dynamic Characteristics

PARAMETER	CONDITIONS	Symbol	MIN.	TYP.	MAX.	UNIT
Forward Transconductance	$V_{DS} = 15\text{V}, I_D = 4\text{A}$	$g_{fs}$		7		s
Input Capacitance		$C_{iss}$		1253		pF
Output Capacitance	$V_{DS} = 25\text{V}, V_{GS} = 0\text{V}, f = 1.0\text{MHz}$	$C_{oss}$		115		
Reverse Transfer Capacitance		$C_{rss}$		15		

## ■ Resistive Switching Characteristics

PARAMETER	CONDITIONS	Symbol	MIN.	TYP.	MAX.	UNIT
Turn-on Delay Time	$I_D = 8\text{A}, V_{DD} = 300\text{V}, V_{GS} = 10\text{V}, R_G = 9.1\Omega$	$t_{d(\text{ON})}$		13		ns
Rise Time		$tr$		15		
Turn-off Delay Time		$t_{d(\text{OFF})}$		41		
Fail Time		$tf$		21		
Total Gate Charge	$I_D = 8\text{A}, V_{DD} = 300\text{V}, V_{GS} = 10\text{V}$	$Q_g$		29		nC
Gate-Source Charge		$Q_{gs}$		7		
Gate-Drain Charge		$Q_{gd}$		12		

## ■ Source-Drain Diode Characteristics

PARAMETER	CONDITIONS	Symbol	MIN.	TYP.	MAX.	UNIT
Continuous Source-Drain Diode Current	Body Diode	$I_s$			8	A
Pulse Diode Forward Current	Body Diode	$I_{sm}$			32	
Body Diode Voltage	$I_s = 8.0\text{A}, V_{GS} = 0\text{V}$	$V_{SD}$			1.5	V
Reverse recovery time	$I_s = 8\text{A}, T_J = 25^\circ\text{C}, dI_f/dt = 100\text{A}/\mu\text{s}, V_{GS} = 0\text{V}$	$t_{rr}$		406		ns
Reverse recovery charge		$Q_{rr}$		1895		$\mu\text{C}$

## ■ Thermal characteristics

PARAMETER	CONDITIONS	Symbol	MIN.	TYP.	MAX.	UNIT
Thermal Resistance	Junction to Case	$R_{\theta JC}$		2.78		$^\circ\text{C}/\text{W}$
	Junction to Ambient	$R_{\theta JA}$		100		

■ Rating and characteristic curves




Figure 1 Maximum Forward Bias Safe Operating Area




Figure 2 Maximum Power Dissipation vs Case Temperature




Figure 3 Maximum Continuous Drain Current vs Case Temperature




Figure 4 Typical Output Characteristics




Figure 5 Maximum Effective Thermal Impedance, Junction to Case

■ Rating and characteristic curves




Figure 6 Maximum Peak Current Capability




Figure 7 Typical Transfer Characteristics




Figure 8 Typical Drain to Source ON Resistance vs Gate Voltage and Drain Current




Figure 9 Typical Drain to Source ON Resistance vs Drain Current




Figure 10 Typical Drian to Source on Resistance vs Junction Temperature

■ Rating and characteristic curves




Figure 11 Typical Threshold Voltage vs Junction Temperature




Figure 12 Typical Breakdown Voltage vs Junction Temperature




Figure 13 Typical Capacitance vs Drain to Source Voltage




Figure 14 Typical Gate Charge vs Gate to Source Voltage




Figure 15 Typical Body Diode Transfer Characteristics




Figure 16 Unclamped Inductive Switching Capability

■ Test circuit and waveform




Figure 17. Gate Charge Test Circuit




Figure 18. Gate Charge Waveform




Figure 19. Resistive Switching Test Circuit




Figure 20. Resistive Switching Waveforms

■ Test circuit and waveform




Figure 21. Diode Reverse Recovery Test Circuit




Figure 22. Diode Reverse Recovery Waveform




Figure 23. Unclamped Inductive Switching Test Circuit




Figure 24. Unclamped Inductive Switching Waveforms

- CITC reserves the right to make changes to this document and its products and specifications at any time without notice.
- Customers should obtain and confirm the latest product information and specifications before final design, purchase or use.
- CITC makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does CITC assume any liability for application assistance or customer product design.
- CITC does not warrant or accept any liability with products which are purchased or used for any unintended or unauthorized application.
- No license is granted by implication or otherwise under any intellectual property rights of CITC.
- CITC products are not authorized for use as critical components in life support devices or systems without express written approval of CITC.