

RGP20A THRU RGP20M

**SINTERED GLASS JUNCTION
FAST SWITCHING PLASTIC RECTIFIER**
VOLTAGE:50 TO 1000V CURRENT: 2.0A




FEATURE

High temperature metallurgically bonded construction
Sintered glass cavity free junction
Capability of meeting environmental standard of MIL-S-19500
High temperature soldering guaranteed
350°C /10sec/0.375"lead length at 5 lbs tension
Operate at Ta =55°C with no thermal run away
Typical Ir<0.1µA

MECHANICAL DATA

Terminal: Plated axial leads solderable per MIL-STD 202E, method 208C
Case: Molded with UL-94 Class V-0 recognized Flame Retardant Epoxy
Polarity: color band denotes cathode
Mounting position: any

DO-15/DO-204C



Dimensions in inches and (millimeters)

MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

(single-phase, half-wave, 60HZ, resistive or inductive load rating at 25°C, unless otherwise stated)

	SYMBOL	RGP 20A	RGP 20B	RGP 20D	RGP 20G	RGP 20J	RGP 20K	RGP 20M	units	
Maximum Recurrent Peak Reverse Voltage	Vrrm	50	100	200	400	600	800	1000	V	
Maximum RMS Voltage	Vrms	35	70	140	280	420	560	700	V	
Maximum DC blocking Voltage	Vdc	50	100	200	400	600	800	1000	V	
Maximum Average Forward Rectified Current 3/8"lead length at Ta =55°C	If(av)	2.0								A
Peak Forward Surge Current 8.3ms single half sine-wave superimposed on rated load	Ifsm	80.0								A
Maximum Forward Voltage at rated Forward Current and 25°C	Vf	1.3								V
Maximum full load reverse current full cycle average at 55°C Ambient	Ir(av)	100.0								µA
Maximum DC Reverse Current Ta =25°C at rated DC blocking voltage Ta =150°C	Ir	5.0 200.0								µA µA
Maximum Reverse Recovery Time (Note 1)	Trr	150				250	500			nS
Typical Junction Capacitance (Note 2)	Cj	35.0								pF
Typical Thermal Resistance (Note 3)	R(ja)	22.0								°C /W
Storage and Operating Junction Temperature	Tstg, Tj	-65 to +175								°C

Note:

1. Reverse Recovery Condition If =0.5A, Ir =1.0A, Irr =0.25A
2. Measured at 1.0 MHz and applied reverse voltage of 4.0Vdc
3. Thermal Resistance from Junction to Ambient at 3/8"lead length, P.C. Board Mounted

RATINGS AND CHARACTERISTIC CURVES RGP20A THRU RGP20M

