



# 3CG6

## PNP Silicon High Frequency Low Power Transistor



### Features:

1. Using epitaxy planar technology structure. High working frequency. Metallic packaging.
2. Small volume, light weight, easy installation.
3. Use for high frequency oscillation, high frequency small signal amplification, low power source adjustment circuit. Make up push pull amplifying circuit with NPN.
4. Quality Class: GS, G. Implementation of standards: QZJ840611

### TECHNICAL DATA:

( $T_a = 25^\circ\text{C}$ )

Parameter name	Symbols	Unit	Specifications						Test Condition
			A	B	C	D	E	F	
Total Dissipation	$P_{tot}$	mW	600						$T_a=25^\circ\text{C}$
Max. Collector Current	$I_{CM}$	mA	60						
Junction Temperature	$T_{jm}$	$^\circ\text{C}$	175						
Storage Temperature	$T_{stg}$	$^\circ\text{C}$	-55~+175						
C-E Breakdown Voltage	$V_{(BR)CEO}$	V	15	15	20	30	30	40	$I_c=0.1\text{mA}$
E-B Breakdown Voltage	$V_{(BR)EBO}$	V	4						$I_E=0.1\text{mA}$
Collector- Emitter Saturation Voltage Drop	$V_{CE(sat)}$	V	0.5						$I_c=50\text{mA}$ , $I_B=5\text{mA}$
C-E Leakage Current	$I_{CEO}$	$\mu\text{A}$	1.0						$V_{CE}=10\text{V}$
DC Current Gain	$h_{FE}$		25~270						$V_{CE}=10\text{V}$ , $I_c=30\text{mA}$
Transition frequency	$f_T$	MHz	80	100	120	150	$V_{CE}=10\text{V}$ , $I_c=5\text{mA}$ $f=30\text{MHz}$		

### $h_{FE}$ Colored:

Color	Orange	Yellow	Green	Blue	Purple	Gray
$h_{FE}$	25~40	40~55	55~80	80~120	120~180	180~270

### Outline and Dimensions: