

2N2904, 2N2904A JAN, JTX, JTXV
2N2904AL JAN, JTX, JTXV
2N2905, 2N2905A JAN, JTX, JTXV
2N2905AL JAN, JTX, JTXV




Processed per MIL-PRF-19500/290

PNP SWITCHING SILICON TRANSISTOR

MAXIMUM RATINGS

Ratings	Symbol	2N2904 2N2905	2N2904A, L 2N2905A, L	Units
Collector-Emitter Voltage	V_{CEO}	40	60	Vdc
Collector-Base Voltage	V_{CBO}		60	Vdc
Emitter-Base Voltage	V_{EBO}		5.0	Vdc
Collector Current	I_C		600	mAdc
Total Power Dissipation @ $T_A = 25^{\circ}C$ ⁽¹⁾	P_T		0.6	W
@ $T_C = 25^{\circ}C$ ⁽²⁾			3.0	W
Operating & Storage Junction Temperature Range	T_J, T_{stg}		-65 to +200	$^{\circ}C$



THERMAL CHARACTERISTICS

Characteristics	Symbol	Max.	Unit
Thermal Resistance, Junction-to-Case	$R_{\theta JC}$	0.29	$^{\circ}C/mW$

1) Derate linearly 3.43 W/ $^{\circ}C$ for $T_A > 25^{\circ}C$

2) Derate linearly 17.2 W/ $^{\circ}C$ for $T_C > 25^{\circ}C$

ELECTRICAL CHARACTERISTICS ($T_A = 25^{\circ}C$ unless otherwise noted)

Characteristics	Symbol	Min.	Max.	Unit
-----------------	--------	------	------	------

OFF CHARACTERISTICS

Collector-Emitter Breakdown Voltage $I_C = 10$ mAdc	2N2904, 2N2905 2N2904A, L, 2N2905A, L	$V_{(BR)CEO}$	40 60	Vdc
Collector-Emitter Cutoff Voltage $V_{CE} = 40$ Vdc $V_{CE} = 60$ Vdc	2N2904, 2N2905 2N2904A, L, 2N2905A, L	I_{CES}	1.0 1.0	μ Adc
Collector-Base Cutoff Current $V_{CB} = 60$ Vdc $V_{CB} = 50$ Vdc	2N2904, 2N2905 2N2904A, L, 2N2905A, L	I_{CBO}	10 20 10	μ Adc η Adc
Emitter-Base Cutoff Current $V_{EB} = 5.0$ Vdc $V_{EB} = 3.5$ Vdc		I_{EBO}	10 50	μ Adc η Adc

2N2904, 2N2904A, 2N2904AL, 2N2905, 2N2905A, 2N2905AL JAN SERIES

ELECTRICAL CHARACTERISTICS (con't)

Characteristics	Symbol	Min.	Max.	Unit
ON CHARACTERISTICS ⁽³⁾				
Forward-Current Transfer Ratio $I_C = 0.1 \text{ mAdc}, V_{CE} = 10 \text{ Vdc}$ 2N2904 2N2905 2N2904A, 2N2904AL 2N2905A, 2N2905AL	h_{FE}	20		
$I_C = 1.0 \text{ mAdc}, V_{CE} = 10 \text{ Vdc}$ 2N2904 2N2905 2N2904A, 2N2904AL 2N2905A, 2N2905AL		35		
$I_C = 10 \text{ mAdc}, V_{CE} = 10 \text{ Vdc}$ 2N2904 2N2905 2N2904A, 2N2904AL 2N2905A, 2N2905AL		40		
$I_C = 150 \text{ mAdc}, V_{CE} = 10 \text{ Vdc}$ 2N2904, 2N2904A, L 2N2905, 2N2905A, L		75		
$I_C = 500 \text{ mAdc}, V_{CE} = 10 \text{ Vdc}$ 2N2904 2N2905 2N2904A, 2N2904AL 2N2905A, 2N2905AL		25	175	
		50	450	
		40	175	
		100	450	
		35		
		75		
		40		
		100		
	40	120		
	100	300		
	20			
	30			
	40			
	50			
Collector-Emitter Saturation Voltage $I_C = 150 \text{ mAdc}, I_B = 15 \text{ mAdc}$ $I_C = 500 \text{ mAdc}, I_B = 50 \text{ mAdc}$	$V_{CE(sat)}$		0.4 1.6	Vdc
Base-Emitter Voltage $I_C = 150 \text{ mAdc}, I_B = 15 \text{ mAdc}$ $I_C = 500 \text{ mAdc}, I_B = 50 \text{ mAdc}$	$V_{BE(sat)}$		1.3 2.6	Vdc
DYNAMIC CHARACTERISTICS				
Small-Signal Cutoff Frequency $I_C = 1.0 \text{ mAdc}, V_{CE} = 10 \text{ Vdc}, f = 1.0 \text{ kHz}$ 2N2904 2N2905 2N2904A, 2N2905A 2N2904AL, 2N2905AL	h_{fe}	25		
		50		
		40		
		100		
Small-Signal Cutoff Frequency, Magnitude $I_C = 50 \text{ mAdc}, V_{CE} = 20 \text{ Vdc}, f = 100 \text{ MHz}$	$ h_{fe} $	2.0		
Output Capacitance $V_{CB} = 10 \text{ Vdc}, I_E = 0, 100 \text{ kHz} \leq f \leq 1.0 \text{ MHz}$	C_{obo}		8.0	pF
Input Capacitance $V_{EB} = 2.0 \text{ Vdc}, I_C = 0, 100 \text{ kHz} \leq f \leq 1.0 \text{ MHz}$	C_{ibo}		30	pF
SWITCHING CHARACTERISTICS				
Turn-On Time $V_{CC} = 30 \text{ Vdc}; I_C = 150 \text{ mAdc}; I_{B1} = 15 \text{ mAdc}$	t_{on}		45	ns
Turn-Off Time $V_{CC} = 30 \text{ Vdc}; I_C = 150 \text{ mAdc}; I_{B1} = I_{B2} = 15 \text{ mAdc}$	t_{off}		300	ns

(3) Pulse Test: Pulse Width = 300µs, Duty Cycle ≤ 2.0%.