

BAS81-83

SMALL SIGNAL SCHOTTKY DIODE

FEATURES :


- * Integrated protection ring against static discharge.
- * Low capacitance
- * Low leakage current
- * Low forward voltage drop
- * Low low switching time
- * Pb / RoHS Free

MECHANICAL DATA :


Case: MiniMELF Glass Case (SOD-80C)

Weight: approx. 0.05g

MiniMELF (SOD-80C)



Mounting Pad Layout



Dimensions in inches and (millimeters)

Maximum Ratings and Thermal Characteristics (Rating at 25 °C ambient temperature unless otherwise specified)

Parameter	Symbol	Value	Unit
Continuous Reverse Voltage	V _R	40	V
BAS81		50	
BAS82		60	
Continuous Forward Current	I _F	30	mA
Repetitive Peak Forward Current	I _{FRM}	150	mA
Forward Surge Current at t _p = 1 s	I _{FSM}	500	mA
Thermal Resistance Junction to Ambient Air	R _{0JA}	320 ⁽¹⁾	°C/W
Junction Temperature	T _J	125	°C
Storage temperature range	T _{STG}	-65 to + 150	°C

Note: (1) on PC board 50 mm x 50mm x 1.6mm.

Electrical Characteristics (Ta = 25 °C unless otherwise noted)

Parameter	Symbol	Test Condition	Min	Typ	Max	Unit
Forward Voltage	V _F	I _F = 0.1mA	-	-	0.33	V
		I _F = 1.0mA	-	-	0.41	
		I _F = 15mA	-	-	1.0	
Reverse Current	I _R	V _R = V _{Rmax}	-	-	200	nA
Diode Capacitance	C _d	V _R = 1V, f = 1MHz	-	-	1.6	pF