



ELECTRONICS, INC.
44 FARRAND STREET
BLOOMFIELD, NJ 07003
(973) 748-5089
<http://www.nteinc.com>

NTE2956
MOSFET
N-Channel, Enhancement Mode
High Speed Switch

Applications:

- SMPS
- AC Adapter
- Power Supply for Printer, Copies, TV, VCR, etc.

Absolute Maximum Ratings: ($T_C = +25^\circ\text{C}$ unless otherwise specified)

Drain-Source Voltage ($V_{GS} = 0\text{V}$), V_{DSS}	500V
Gate-Source Voltage ($V_{DS} = 0\text{V}$), V_{GS}	$\pm 30\text{V}$
Drain Current, I_D	
Continuous	14A
Pulsed	42A
Avalanche Current (Pulsed, $L = 200\mu\text{H}$), I_{DA}	14A
Maximum Power Dissipation, P_D	35W
Channel Temperature Range, T_{ch}	-55° to +150°C
Storage Temperature Range, T_{stg}	-55° to +150°C
Maximum Thermal Resistance, Channel-to-Case, $R_{th(ch-c)}$	3.57°C/W
Isolation Voltage (AC for 1 Minute, Terminal-to-Case), V_{ISO}	2000V

Electrical Characteristics: ($T_{ch} = +25^\circ\text{C}$ unless otherwise specified)

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
Drain-Source Breakdown Voltage	$V_{(BR)DSS}$	$V_{DS} = 0\text{V}$, $I_D = 1\text{mA}$	500	-	-	V
Gate-Source Breakdown Voltage	$V_{(BR)GSS}$	$V_{DS} = 0\text{V}$, $I_G = \pm 100\mu\text{A}$	± 30	-	-	V
Gate-Source Leakage	I_{GSS}	$V_{GS} = \pm 25\text{V}$, $V_{DS} = 0\text{V}$	-	-	± 10	μA
Zero Gate Voltage Drain Current	I_{DSS}	$V_{DS} = 500\text{V}$, $V_{GS} = 0$	-	-	1.0	mA
Gate Threshold Voltage	$V_{GS(th)}$	$V_{DS} = 10\text{V}$, $I_D = 1\text{mA}$	2.5	3.0	3.5	V
Static Drain-Source ON Resistance	$R_{DS(on)}$	$V_{GS} = 10\text{V}$, $I_D = 7\text{A}$	-	0.50	0.64	Ω
Drain-Source On-State Voltage	$V_{DS(on)}$	$V_{GS} = 10\text{V}$, $I_D = 7\text{A}$	-	3.50	4.48	V
Forward Transfer Admittance	$ Y_{fs} $	$V_{GS} = 10\text{V}$, $I_D = 7\text{A}$	6.6	11.0	-	S

Electrical Characteristics (Cont'd): ($T_{ch} = +25^\circ\text{C}$ unless otherwise specified)

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
Input Capacitance	C_{iss}	$V_{GS} = 0\text{V}$, $V_{DS} = 25\text{V}$, $f = 1\text{MHz}$	-	1500	-	pF
Output Capacitance	C_{oss}		-	150	-	pF
Reverse Transfer Capacitance	C_{rss}		-	35	-	pF
Turn-On Delay Time	$t_{d(on)}$	$V_{DD} = 200\text{V}$, $I_D = 7\text{A}$, $V_{GS} = 10\text{V}$, $R_{GEN} = R_{GS} = 50\Omega$	-	25	-	ns
Rise Time	t_r		-	40	-	ns
Turn-Off Delay Time	$t_{d(off)}$		-	190	-	ns
Fall Time	t_f		-	50	-	ns
Diode Forward Voltage	V_{SD}	$I_S = 7\text{A}$, $V_{GS} = 0\text{V}$	-	1.5	2.0	V

