



Micro Commercial Components



Micro Commercial Components
 20736 Marilla Street Chatsworth
 CA 91311
 Phone: (818) 701-4933
 Fax: (818) 701-4939

SI2304


Features

- Lead Free Finish/RoHS Compliant ("P" Suffix designates RoHS Compliant. See ordering information)
- Epoxy meets UL 94 V-0 flammability rating
- Moisture Sensitivity Level 1
- 30V,2.5A, $R_{DS(ON)}=65m\Omega @V_{GS}=10V$
 30V,2.0A, $R_{DS(ON)}=90m\Omega @V_{GS}=4.5V$
- High dense cell design for extremely low $R_{DS(ON)}$
- Rugged and reliable
- Lead free product is acquired
- SOT-23 Package
- Marking Code: S4

N-Channel Enhancement Mode Field Effect Transistor


Maximum Ratings @ 25°C Unless Otherwise Specified

Symbol	Parameter	Rating	Unit
V_{DS}	Drain-source Voltage	30	V
I_D	Drain Current-Continuous	2.5	A
I_{DM}	Drain Current-Pulsed	10	A
V_{GS}	Gate-source Voltage	± 20	V
P_D	Total Power Dissipation	0.25	W
$R_{\theta JA}$	Thermal Resistance Junction to Ambient	500	$^{\circ}C/W$
T_J	Operating Junction Temperature	-55 to +150	$^{\circ}C$
T_{STG}	Storage Temperature	-55 to +150	$^{\circ}C$




DIM	INCHES		MM		NOTE
	MIN	MAX	MIN	MAX	
A	.110	.120	2.80	3.04	
B	.083	.104	2.10	2.64	
C	.047	.055	1.20	1.40	
D	.035	.041	.89	1.03	
E	.070	.081	1.78	2.05	
F	.018	.024	.45	.60	
G	.0005	.0039	.013	.100	
H	.035	.044	.89	1.12	
J	.003	.007	.085	.180	
K	.015	.020	.37	.51	

Internal Block Diagram




Suggested Solder Pad Layout




Electrical Characteristics T_A = 25°C unless otherwise noted

Parameter	Symbol	Test Condition	Min	Typ	Max	Units
Off Characteristics						
Drain-Source Breakdown Voltage	BV _{DSS}	V _{GS} = 0V, I _D = 250μA	30			V
Zero Gate Voltage Drain Current	I _{DSS}	V _{DS} = 30V, V _{GS} = 1V			1	μA
Gate Body Leakage Current, Forward	I _{GSSF}	V _{GS} = 20V, V _{DS} = 0V			100	nA
Gate Body Leakage Current, Reverse	I _{GSSR}	V _{GS} = -20V, V _{DS} = 0V			-100	nA
On Characteristics						
Gate Threshold Voltage	V _{GS(th)}	V _{GS} = V _{DS} , I _D = 250μA	1		3	V
Static Drain-Source On-Resistance	R _{DS(on)}	V _{GS} = 10V, I _D = 2.5A			65	mΩ
		V _{GS} = 4.5V, I _D = 2A			90	mΩ
Forward Transconductance	g _{FS}	V _{DS} = 4.5V, I _D = 2.5A		4.6		S
Dynamic Characteristics						
Input Capacitance	C _{iss}	V _{DS} = 15V, V _{GS} = 0V, f = 1.0 MHz		240		pF
Output Capacitance	C _{oss}			110		pF
Reverse Transfer Capacitance	C _{rss}			17		pF
Switching Characteristics						
Turn-On Delay Time	t _{d(on)}	V _{DD} = 15V, I _D = 1A, V _{GEN} = 10V, R _G = 6Ω, R _L = 15Ω		8	20	ns
Turn-On Rise Time	t _r			12	30	ns
Turn-Off Delay Time	t _{d(off)}			17	35	ns
Turn-Off Fall Time	t _f			8	20	ns
Total Gate Charge	Q _g	V _{DS} = 15V, I _D = 2.5A, V _{GS} = 10V		4.5	10	nC
Gate-Source Charge	Q _{gs}			0.8		nC
Gate-Drain Charge	Q _{gd}			1.0		nC
Drain-Source Diode Characteristics and Maximum Ratings						
Drain-Source Diode Forward Voltage	V _{SD}	V _{GS} = 0V, I _S = 1.25A			1.2	V


Output Characteristics




Transfer Characteristics




On-Resistance vs. Drain Current




Capacitance








Gate Charge



On-Resistance vs. Junction Temperature







Micro Commercial Components

Ordering Information :

Device	Packing
Part Number-TP	Tape&Reel: 3Kpcs/Reel

*****IMPORTANT NOTICE*****

Micro Commercial Components Corp. reserves the right to make changes without further notice to any product herein to make corrections, modifications , enhancements , improvements , or other changes . **Micro Commercial Components Corp .** does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights ,nor the rights of others . The user of products in such applications shall assume all risks of such use and will agree to hold **Micro Commercial Components Corp .** and all the companies whose products are represented on our website, harmless against all damages.

*****LIFE SUPPORT*****

MCC's products are not authorized for use as critical components in life support devices or systems without the express written approval of Micro Commercial Components Corporation.

*****CUSTOMER AWARENESS*****

Counterfeiting of semiconductor parts is a growing problem in the industry. Micro Commercial Components (MCC) is taking strong measures to protect ourselves and our customers from the proliferation of counterfeit parts. MCC strongly encourages customers to purchase MCC parts either directly from MCC or from Authorized MCC Distributors who are listed by country on our web page cited below. Products customers buy either from MCC directly or from Authorized MCC Distributors are genuine parts, have full traceability, meet MCC's quality standards for handling and storage. **MCC will not provide any warranty coverage or other assistance for parts bought from Unauthorized Sources.** MCC is committed to combat this global problem and encourage our customers to do their part in stopping this practice by buying direct or from authorized distributors.