



Micro Commercial Components



Micro Commercial Components  
 20736 Marilla Street Chatsworth  
 CA 91311  
 Phone: (818) 701-4933  
 Fax: (818) 701-4939

# BDX33 THRU BDX33D

## Features

- Lead Free Finish/RoHS Compliant(Note 1) ("P" Suffix designates RoHS Compliant. See ordering information)
- Designed For Complementary Use with BDX34, BDX34A, BDX34B, BDX34C and BDX34D
- 70W at 25°C Cass Temperature
- 10A Continuous Collector Current
- Minimum  $h_{FE}$  of 750 at 3.0V, 3.0A
- Epoxy meets UL 94 V-0 flammability rating
- Moisture Sensitivity Level 1
- Mounting Torque: 5 in-lbs Maximum

### Absolute Maximum Ratings @ 25°C Unless Otherwise Noted

Symbol	Rating	Value	Unit
$V_{CBO}$	Collector-Base Voltage ( $I_E=0$ )		
	BDX33	45	V
	BDX33A	60	
	BDX33B	80	
	BDX33C	100	
$V_{CEO}$	Collector-Emitter Voltage ( $I_B=0$ )		
	BDX33	45	V
	BDX33A	60	
	BDX33B	80	
	BDX33C	100	
$V_{EBO}$	Emitter-Base Voltage	5.0	V
$I_C$	Continuous Collector Current	10	A
$I_B$	Continuous Base Current	0.3	A
$P_{TOT}$	Continuous Device Dissipation at (or below) 25°C Case Temperature (see Note2)	70	W
$P_{TOT}$	Continuous Device Dissipation at (or below) 25°C Free Air Temperature (see Note 3)	2.0	W
$T_J$	Operating Free Air Temperature Range	-55~+150	°C
$T_{STG}$	Storage Temperature Range	-55~+150	°C
$T_A$	Operating Free-Air Temperature Range	-55~+150	°C


- Notes: 1. High Temperature Solder Exemption Applied, see EU Directive Annex 7.  
 2. Derate Linearly to 150°C Case Temperature at the Rate of 0.56 W/°C  
 3. Derate Linearly to 150°C Free Air Temperature at the Rate of 16m W/°C

### Electrical Characteristics @ 25°C Unless Otherwise Specified

Symbol	Parameter	Min	Typ	Max	Unit
$V_{(BR)CEO}$	Collector-Emitter Breakdown Voltage				
	( $I_C=100mA$ , $I_B=0$ , see note 3)				
	BDX33	45			V
	BDX33A	60			
	BDX33B	80			
	BDX33C	100			
	BDX33D	100			

## NPN Silicon Power Darlington

### TO-220



DIM	DIMENSIONS				NOTE
	INCHES		MM		
	MIN	MAX	MIN	MAX	
A	.560	.625	14.22	15.88	
B	.380	.420	9.65	10.67	
C	.140	.190	3.56	4.82	
D	.020	.045	0.51	1.14	
F	.139	.161	3.53	4.09	Ø
G	.190	.110	2.29	2.79	
H	---	.250	---	6.35	
J	.012	.025	0.30	0.64	
K	.500	.580	12.70	14.73	
L	.045	.060	1.14	1.52	
N	.190	.210	4.83	5.33	
Q	.100	.135	2.54	3.43	
R	.080	.115	2.04	2.92	
S	.045	.055	1.14	1.39	
T	.230	.270	5.84	6.86	
U	-----	.050	-----	1.27	
V	.045	-----	1.15	-----	

## BDX33 thru BDX33D

Symbol	Parameter	Min	Typ	Max	Unit
$I_{CEO}$	Collector-Emitter Cut-Off Current ( $V_{CE}=30V, I_B=0$ )	BDX33		0.5	mA
	( $V_{CE}=30V, I_B=0$ )	BDX33A		0.5	
	( $V_{CE}=40V, I_B=0$ )	BDX33B		0.5	
	( $V_{CE}=50V, I_B=0$ )	BDX33C		0.5	
	( $V_{CE}=60V, I_B=0$ )	BDX33D		0.5	
	( $V_{CE}=30V, I_B=0, T_C=100^\circ C$ )	BDX33		10	
	( $V_{CE}=30V, I_B=0, T_C=100^\circ C$ )	BDX33A		10	
	( $V_{CE}=40V, I_B=0, T_C=100^\circ C$ )	BDX33B		10	
	( $V_{CE}=50V, I_B=0, T_C=100^\circ C$ )	BDX33C		10	
( $V_{CE}=60V, I_B=0, T_C=100^\circ C$ )	BDX33D		10		
$I_{CBO}$	Collector Cut-Off Current ( $V_{CB}=45V, I_E=0$ )	BDX33		1.0	mA
	( $V_{CB}=60V, I_E=0$ )	BDX33A		1.0	
	( $V_{CB}=80V, I_E=0$ )	BDX33B		1.0	
	( $V_{CB}=100V, I_E=0$ )	BDX33C		1.0	
	( $V_{CB}=100V, I_E=0$ )	BDX33D		1.0	
	( $V_{CB}=45V, I_E=0, T_C=100^\circ C$ )	BDX33		5.0	
	( $V_{CB}=60V, I_E=0, T_C=100^\circ C$ )	BDX33A		5.0	
	( $V_{CB}=80V, I_E=0, T_C=100^\circ C$ )	BDX33B		5.0	
	( $V_{CB}=100V, I_E=0, T_C=100^\circ C$ )	BDX33C		5.0	
( $V_{CB}=120V, I_E=0, T_C=100^\circ C$ )	BDX33D		5.0		
$I_{EBO}$	Emitter Cut-Off Current ( $V_{EB}=5.0V, I_C=0$ )			10	mA
$h_{FE}$	Forward Current Transfer Ratio ( $V_{CE}=3.0V, I_C=4.0A$ )	BDX33	750		
	( $V_{CE}=3.0V, I_C=4.0A$ )	BDX33A	750		
	( $V_{CE}=3.0V, I_C=3.0A$ ) (see notes 4 and 5)	BDX33B	750		
	( $V_{CE}=3.0V, I_C=3.0A$ )	BDX33C	750		
	( $V_{CE}=3.0V, I_C=3.0A$ )	BDX33D	750		
$V_{BE(ON)}$	Base-Emitter Voltage ( $V_{CE}=3.0V, I_C=4.0A$ )	BDX33		2.5	V
	( $V_{CE}=3.0V, I_C=4.0A$ )	BDX33A		2.5	
	( $V_{CE}=3.0V, I_C=3.0A$ ) (see notes 4 and 5)	BDX33B		2.5	
	( $V_{CE}=3.0V, I_C=3.0A$ )	BDX33C		2.5	
	( $V_{CE}=3.0V, I_C=3.0A$ )	BDX33D		2.5	
$V_{CE(SAT)}$	Collector-Emitter Saturation Voltage ( $I_B=8.0mA, I_C=4.0A$ )	BDX33		2.5	V
	( $I_B=8.0mA, I_C=4.0A$ )	BDX33A		2.5	
	( $I_B=6.0mA, I_C=3.0A$ ) (see notes 4 and 5)	BDX33B		2.5	
	( $I_B=6.0mA, I_C=3.0A$ )	BDX33C		2.5	
	( $I_B=6.0mA, I_C=3.0A$ )	BDX33D		2.5	
$V_{EC}$	Parallel Diode Forward Voltage ( $I_E=8.0A, I_B=0$ )			4.0	V

 NOTES: 4. These parameters must be measured using pulse techniques,  $t_p=300\mu s$ , duty cycle  $\leq 2\%$ .

5. These parameters must be measured using voltage-sensing contacts, separate from the current carrying contacts.

**Thermal Characteristics**

Symbol	Parameter	Min	Typ	Max	Unit
$R_{\theta JC}$	Junction to Case Thermal Resistance			1.78	$^\circ C/W$
$R_{\theta JA}$	Junction to Free Air Thermal Resistance			62.5	$^\circ C/W$

**Resistive-Load-Switching Characteristics at 25 °C Case Temperature**

Symbol	Parameter	Test Conditions <sup>†</sup>	Min	Typ	Max	Unit
$t_{on}$	Turn-On Time	$I_C=3.0A, I_{B(on)}=12mA, I_{B(off)}=-12mA$		1.0		$\mu s$
$t_{off}$	Turn-Off Time	$V_{BE(off)}=-3.5V, R_L=10\Omega, t_p=20\mu s, dc \leq 2\%$		5.0		$\mu s$

<sup>†</sup> Voltage and current values shown are nominal; exact values vary slightly with transistor parameters.

# BDX33 thru BDX33D

**TYPICAL DC CURRENT GAIN**  
**VS**  
**COLLECTOR CURRENT**




Figure 1.

**COLLECTOR-EMITTER SATURATION VOLTAGE**  
**VS**  
**COLLECTOR CURRENT**




Figure 2.

**BASE-EMITTER SATURATION VOLTAGE**  
**VS**  
**COLLECTOR CURRENT**




Figure 3.

## THERMAL INFORMATION

**MAXIMUM POWER DISSIPATION**  
**VS**  
**CASE TEMPERATURE**




Figure 4.



Micro Commercial Components

### Ordering Information :

Device	Packing
Part Number-BP	Bulk; 1Kpcs/Box

**\*\*\*IMPORTANT NOTICE\*\*\***

**Micro Commercial Components Corp.** reserves the right to make changes without further notice to any product herein to make corrections, modifications, enhancements, improvements, or other changes. **Micro Commercial Components Corp.** does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights, nor the rights of others. The user of products in such applications shall assume all risks of such use and will agree to hold **Micro Commercial Components Corp.** and all the companies whose products are represented on our website, harmless against all damages.

**\*\*\*LIFE SUPPORT\*\*\***

MCC's products are not authorized for use as critical components in life support devices or systems without the express written approval of Micro Commercial Components Corporation.

**\*\*\*CUSTOMER AWARENESS\*\*\***

Counterfeiting of semiconductor parts is a growing problem in the industry. Micro Commercial Components (MCC) is taking strong measures to protect ourselves and our customers from the proliferation of counterfeit parts. MCC strongly encourages customers to purchase MCC parts either directly from MCC or from Authorized MCC Distributors who are listed by country on our web page cited below. Products customers buy either from MCC directly or from Authorized MCC Distributors are genuine parts, have full traceability, meet MCC's quality standards for handling and storage. **MCC will not provide any warranty coverage or other assistance for parts bought from Unauthorized Sources.** MCC is committed to combat this global problem and encourage our customers to do their part in stopping this practice by buying direct or from authorized distributors.