

# 2SK2207

External dimensions 1 ..... FM20

## Absolute Maximum Ratings (Ta = 25°C)

Symbol	Rated	Unit
V <sub>DSS</sub>	900	V
V <sub>GSS</sub>	±30	V
I <sub>D</sub>	±3	A
I <sub>D</sub> (pulse) *1	±12	A
P <sub>D</sub>	35 (T <sub>c</sub> = 25°C)	W
E <sub>AS</sub> *2	280	mJ
I <sub>AS</sub>	3	A
T <sub>ch</sub>	150	°C
T <sub>stg</sub>	-55 to +150	°C

\*1: P<sub>w</sub> ≤ 100μs, duty cycle ≤ 1%

\*2: V<sub>DD</sub> = 50V, L = 60mH, I<sub>L</sub> = 3A, unclamped, R<sub>G</sub> = 50Ω, See Figure 1 on Page 5.

## Electrical Characteristics (Ta = 25°C)

Symbol	Rated			Unit	Conditions
	min	typ	max		
V <sub>(BR)</sub> DSS	900			V	I <sub>D</sub> = 100μA, V <sub>GS</sub> = 0V
I <sub>GSS</sub>			±100	nA	V <sub>GS</sub> = ±30V
I <sub>DSS</sub>			100	μA	V <sub>D</sub> = 900V, V <sub>GS</sub> = 0V
V <sub>TH</sub>	2.0	3.0	4.0	V	V <sub>D</sub> = 10V, I <sub>D</sub> = 1mA
Re (yfs)	1.0	2.0		S	V <sub>D</sub> = 20V, I <sub>D</sub> = 1.5A
R <sub>DS</sub> (on)		3.8	5.0	Ω	V <sub>GS</sub> = 10V, I <sub>D</sub> = 1.5A
C <sub>iss</sub>		630		pF	V <sub>D</sub> = 10V, f = 1.0MHz, V <sub>GS</sub> = 0V
C <sub>oss</sub>		120		pF	
C <sub>rss</sub>		52		pF	
t <sub>on</sub>		55		ns	I <sub>D</sub> = 1.5A, V <sub>DD</sub> ≈ 250V, R <sub>L</sub> = 167Ω, V <sub>GS</sub> = 10V, See Figure 2 on Page 5.
t <sub>off</sub>		165		ns	

