

SWITCHING REGURATOR APPLICATIONS

Features


- High Voltage: $BV_{DSS}=60V(\text{Min.})$
- Low C_{rSS} : $C_{rSS}=84pF(\text{Typ.})$
- Low gate charge : $Qg=26.7nC(\text{Typ.})$
- Low $R_{DS(on)}$: $R_{DS(on)}=16m\Omega(\text{Max.})$

Ordering Information

Type NO.	Marking	Package Code
STK7006P	STK7006	TO-220AB-3L

Outline Dimensions

unit : mm



Absolute maximum ratings (Tc=25°C)

Characteristic	Symbol	Rating	Unit
Drain-Source voltage	V_{DSS}	60	V
Gate-Source voltage	V_{GSS}	±20	V
Continuous Drain current (Tc=25°C)	I_D	70	A
Continuous Drain current (Tc=100°C)	I_D	48	A
Drain Current-Pulsed ①	I_{DM}	280	A
Power Dissipation (Tc=25°C)	P_D	147	W
Single Pulsed Avalanche Energy ②	E_{AS}	754	mJ
Avalanche current ①	I_{AR}	70	A
Repetitive Avalanche Energy ①	E_{AR}	14.7	mJ
Junction temperature	T_J	175	°C
Storage temperature range	T_{stg}	-55~175	

Thermal Resistance

Characteristic	Symbol	Typ.	Max	Units
Junction to Case	$R_{th(J-C)}$	-	1.02	°C/W
Junction to Ambient	$R_{th(J-a)}$	-	62.5	

Electrical Characteristics (Tc=25°C)

Characteristic	Symbol	Test Condition	Min.	Typ.	Max.	Unit	
Drain-Source breakdown voltage	BV_{DSS}	$I_D=250\mu A, V_{GS}=0$	60	-	-	V	
Gate-Threshold voltage	$V_{GS(th)}$	$I_D=250\mu A, V_{DS}=V_{GS}$	2.0	-	4.0	V	
Drain-source leakage current	I_{DSS}	$V_{DS}=60V, V_{GS}=0V$	-	-	1	μA	
Gate-source leakage	I_{GSS}	$V_{DS}=0V, V_{GS}=\pm 20V$	-	-	± 100	nA	
Drain-Source on-resistance ④	$R_{DS(ON)}$	$V_{GS}=10V, I_D=35A$	-	13	16	m Ω	
Forward transfer admittance ④	g_{fs}	$V_{DS}=20V, I_D=35A$	-	22	-	S	
Input capacitance	C_{iss}	$V_{GS}=0V, V_{DS}=25V, f=1MHz$	-	2273	2935	pF	
Output capacitance	C_{oss}		-	722	940		
Reverse transfer capacitance	C_{rss}		-	83	108		
Turn-on delay time	$t_{d(on)}$	$V_{DD}=30V, I_D=35A$ $R_G=25\Omega$	-	20	50	ns	
Rise time	t_r		-	200	420		
Turn-off delay time	$t_{d(off)}$		④ ⑤	-	55		120
Fall time	t_f		-	75	160		
Total gate charge	Q_g	$V_{DS}=48V, V_{GS}=10V,$ $I_D=70A$	-	43	56	nC	
Gate-source charge	Q_{gs}		-	7.9	-		
Gate-drain("Miller")charge	Q_{gd}		④ ⑤	-	15.0		-

Source-Drain Diode Ratings and Characteristics (Tc=25°C)

Characteristic	Symbol	Test Condition	Min	Typ	Max	Units
Continuous source current	I_S	Integral reverse diode in the MOSFET	-	-	70	A
Pulsed-source current ①	I_{SM}		-	-	280	
Diode forward voltage ④	V_{SD}	$V_{GS}=0V, I_S=70A$	-	-	1.5	V
Reverse recovery time	t_{rr}	$I_S=70A$ $di_F/dt=100A/us$	-	95	-	ns
Reverse recovery charge	Q_{rr}		④	-	150	-

Note ;

- ① Repetitive Rating : Pulse Width Limited by Maximum Junction Temperature
- ② $L=180\mu H, I_{AS}=70A, V_{DD}=25V, R_G=25\Omega$, starting $T_J=25^\circ C$
- ③ $I_S \leq 50A, di/dt \leq 300A/us, V_{DD} \leq BV_{DSS}$, starting $T_J=25^\circ C$
- ④ Pulse Test : Pulse Width < 300us, Duty cycle $\leq 2\%$
- ⑤ Essentially independent of operating temperature

Electrical Characteristic Curves

Fig. 1 $I_D - V_{DS}$




Fig. 2 $I_D - V_{GS}$




Fig. 3 $R_{DS(on)} - I_D$




Fig. 4 $I_S - V_{SD}$




Fig. 5 Capacitance - V_{DS}




Fig. 6 $V_{GS} - Q_G$




Fig. 7 $V_{DSS} - T_J$




Fig. 8 $R_{DS(on)} - T_J$




Fig. 9 $I_D - T_C$




Fig. 10 Safe Operating Area




Fig. 10 Gate Charge Test Circuit & Waveform




Fig. 11 Resistive Switching Test Circuit & Waveform




Fig. 12 E_{AS} Test Circuit & Waveform





Fig. 13 Diode Reverse Recovery Time Test Circuit & Waveform



The AUK Corp. products are intended for the use as components in general electronic equipment (Office and communication equipment, measuring equipment, home appliance, etc.).

Please make sure that you consult with us before you use these AUK Corp. products in equipments which require high quality and / or reliability, and in equipments which could have major impact to the welfare of human life(atomic energy control, airplane, spaceship, transportation, combustion control, all types of safety device, etc.). AUK Corp. cannot accept liability to any damage which may occur in case these AUK Corp. products were used in the mentioned equipments without prior consultation with AUK Corp..

Specifications mentioned in this publication are subject to change without notice.