


Turbo 2 ultrafast High Voltage Rectifier STTH12R06FP

TO-220FPAC

■ Features

- Ultrafast switching
- Low reverse recovery current
- Low thermal resistance
- Reduces switching losses



■ Absolute Maximum Ratings $T_a = 25^\circ\text{C}$

Parameter	Symbol	Rating	Unit
Repetitive Peak reverse voltage	V_{RRM}	600	V
RMS forward voltage	$I_{F(RMS)}$	30	A
Average forward current $T_c=50^\circ\text{C}$	$I_{F(AV)}$	12	A
Surge non repetitive forward current *	I_{FSM}	100	A
Junction temperature	T_j	175	$^\circ\text{C}$
Storage temperature	T_{stg}	-65 to +175	$^\circ\text{C}$

* $t_p=10\text{ms}$ sinusoidal

■ Electrical Characteristics $T_a = 25^\circ\text{C}$

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
Forward voltage	V_F	$I_F=12\text{A}, T_J=25^\circ\text{C}$			2.9	V
		$I_F=12\text{A}, T_J=125^\circ\text{C}$		1.4	1.8	V
Reverse current	I_R	$V_R=V_{RRM}, T_J=25^\circ\text{C}$			45	μA
		$V_R=V_{RRM}, T_J=125^\circ\text{C}$		50	600	μA
Reverse recovery time	t_{rr}	$I_F=0.5\text{A}, I_{RR}=0.25\text{A}, I_R=1\text{A}$			25	ns
		$I_F=1\text{A}, di/dt=-50\text{A}/\mu\text{s}, V_R=30\text{V}$			45	ns
Reverse recovery current	I_{RM}	$I_F = 12\text{A}, V_R = 400\text{V}, di/dt = -200\text{A}/\mu\text{s}, T_J=125^\circ\text{C}$		7.0	8.4	A
Softness factor	S_{factor}			0.2		
Reverse recovery charges	Q_{rr}			180		nC
Forward recovery time	t_{fr}		$I_F = 12\text{A}, di/dt = 96\text{A}/\mu\text{s}, T_J=25^\circ\text{C}, V_{FR}=1.1 \times V_F \text{ max}$			200
Forward recovery voltage	V_{FP}				5.5	V