



P-Channel Enhancement Mode Field Effect Transistor

PRELIMINARY

FEATURES

- -30V, -15A, $R_{DS(ON)} = 7m\Omega$ @ $V_{GS} = -10V$.
 $R_{DS(ON)} = 15m\Omega$ @ $V_{GS} = -4.5V$.
- Super high dense cell design for extremely low $R_{DS(ON)}$.
- High power and current handing capability.
- Lead-free plating ; RoHS compliant.
- Surface mount Package.
- ESD Protected: 4000 V

ABSOLUTE MAXIMUM RATINGS $T_A = 25^\circ C$ unless otherwise noted

Parameter	Symbol	Limit	Units
Drain-Source Voltage	V_{DS}	-30	V
Gate-Source Voltage	V_{GS}	± 20	V
Drain Current-Continuous	I_D	-15	A
Drain Current-Pulsed ^a	I_{DM}	-60	A
Maximum Power Dissipation	P_D	2.5	W
Operating and Store Temperature Range	T_J, T_{stg}	-55 to 150	$^\circ C$

Parameter	Symbol	Limit	Units
Thermal Resistance, Junction-to-Ambient ^b	$R_{\theta JA}$	50	$^\circ C/W$

**Electrical Characteristics** $T_A = 25^\circ\text{C}$ unless otherwise noted

Parameter	Symbol	Test Condition	Min	Typ	Max	Units
Off Characteristics						
Drain-Source Breakdown Voltage	BV_{DSS}	$V_{\text{GS}} = 0\text{V}, I_D = -250\mu\text{A}$	-30			V
Zero Gate Voltage Drain Current	I_{DSS}	$V_{\text{DS}} = -30\text{V}, V_{\text{GS}} = 0\text{V}$			-1	μA
Gate Body Leakage Current, Forward	I_{GSSF}	$V_{\text{GS}} = 20\text{V}, V_{\text{DS}} = 0\text{V}$			100	nA
Gate Body Leakage Current, Reverse	I_{GSSR}	$V_{\text{GS}} = -20\text{V}, V_{\text{DS}} = 0\text{V}$			-100	nA
On Characteristics^c						
Gate Threshold Voltage	$V_{\text{GS(th)}}$	$V_{\text{GS}} = V_{\text{DS}}, I_D = -250\mu\text{A}$	-0.8		-2.0	V
Static Drain-Source On-Resistance	$R_{\text{DS(on)}}$	$V_{\text{GS}} = -10\text{V}, I_D = -6.5\text{A}$		5.5	7.0	$\text{m}\Omega$
		$V_{\text{GS}} = -4.5\text{V}, I_D = -6.5\text{A}$		10	15	$\text{m}\Omega$
Dynamic Characteristics^d						
Input Capacitance	C_{iss}	$V_{\text{DS}} = -10\text{V}, V_{\text{GS}} = 0\text{V}, f = 1\text{MHz}$		5190		pF
Output Capacitance	C_{oss}			1145		pF
Reverse Transfer Capacitance	C_{rss}			730		pF
Switching Characteristics^d						
Turn-On Delay Time	$t_{\text{d(on)}}$	$V_{\text{DD}} = -15\text{V}, I_D = -6.5\text{A}, V_{\text{GS}} = -10\text{V}, R_{\text{GEN}} = 4.7\Omega$		26	52	ns
Turn-On Rise Time	t_r			17	34	ns
Turn-Off Delay Time	$t_{\text{d(off)}}$			145	290	ns
Turn-Off Fall Time	t_f			69	138	ns
Total Gate Charge	Q_g	$V_{\text{DS}} = -24\text{V}, I_D = -13\text{A}, V_{\text{GS}} = -10\text{V}$		128	166	nC
Gate-Source Charge	Q_{gs}			16		nC
Gate-Drain Charge	Q_{gd}			35		nC
Drain-Source Diode Characteristics and Maximum Ratings						
Drain-Source Diode Forward Current ^b	I_S				-1	A
Drain-Source Diode Forward Voltage ^c	V_{SD}	$V_{\text{GS}} = 0\text{V}, I_S = -1\text{A}$			-1.2	V

Notes :

- a.Repetitive Rating : Pulse width limited by maximum junction temperature.
- b.Surface Mounted on FR4 Board, t ≤ 10 sec.
- c.Pulse Test : Pulse Width ≤ 300μs, Duty Cycle ≤ 2%.
- d.Guaranteed by design, not subject to production testing.




Figure 1. Output Characteristics




Figure 2. Transfer Characteristics




Figure 3. Capacitance




Figure 4. On-Resistance Variation with Temperature




Figure 5. Gate Threshold Variation with Temperature




Figure 6. Body Diode Forward Voltage Variation with Source Current




Figure 7. Gate Charge




Figure 8. Maximum Safe Operating Area




Figure 9. Switching Test Circuit




Figure 10. Switching Waveforms




Figure 11. Normalized Thermal Transient Impedance Curve