

## 20V, 3A SCHOTTKY BARRIER RECTIFIER

### Features

- Low forward voltage drop
- Low power loss and High efficiency
- Low leakage current
- High surge capability
- Full lead (Pb)-free and RoHS compliant device


### Applications

- High efficiency SMPS
- Output rectification
- High frequency switching
- Freewheeling
- DC-DC converter systems

### Description

The SDB320 is suited for Switch Mode Power Supply and high frequency DC to DC converters.

This device is especially intended for use in low voltage, high frequency inverters, freewheeling and polarity protection applications.



### Product Characteristics

$I_{F(AV)}$	<b>3A</b>
$V_{RRM}$	<b>20V</b>
$V_{FM}$ at 125 °C	<b>0.40V (Typ.)</b>
$I_{FSM}$	<b>30A</b>

### Ordering Information

Device	Marking Code	Package	Packaging
SDB320	32C	SOD-106	Tape & Reel

### Marking Information



32C = Specific Device Code

YWW = Year & Week Code Marking

-. Y = Year Code

-. WW = Week Code

■ = Color band denote cathode

## Absolute Maximum Ratings (Rating at 25°C ambient temperature unless otherwise specified.)

Characteristic	Symbol	Value	Unit
Maximum repetitive reverse voltage Maximum working peak reverse voltage Maximum DC blocking voltage	$V_{RRM}$ $V_{RWM}$ $V_R$	20	V
Maximum average forward rectified current	$I_{F(AV)}$	3	A
Peak forward surge current 8.3ms single half sine-wave superimposed on rated load per diode	$I_{FSM}$	30	A
Storage temperature range	$T_{stg}$	-55°C to +150°C	°C
Maximum operating junction temperature	$T_J$	150	°C

## Thermal Characteristics

Characteristic	Symbol	Value	Unit
Maximum thermal resistance junction to ambient	$R_{th(j-a)}$ <sup>1)</sup>	100	°C/W


\* 1) Device mounted on FR-4 board with recommended pad layout.

## Electrical Characteristics (Rating at 25°C ambient temperature unless otherwise specified.)

Characteristic	Symbol	Test Condition	Min.	Typ.	Max.	Unit	
Peak forward voltage drop	$V_{FM}$ <sup>2)</sup>	$I_{FM} = 3A$	$T_J = 25^\circ C$	-	0.46	0.50	V
			$T_J = 125^\circ C$	-	0.40	0.43	V
Reverse leakage current	$I_{RM}$ <sup>2)</sup>	$V_R = V_{RRM}$	$T_J = 25^\circ C$	-	-	2	mA
			$T_J = 125^\circ C$	-	-	50	mA
Typical junction capacitance	$C_J$	$V_R = 1V, f = 1MHz$	-	650	-	pF	

\* 2) Pulse test:  $t_p \leq 380 \mu s$ , Duty cycle  $\leq 2\%$

To evaluate the conduction losses use the following equation :  $P_F = 0.37 I_{F(AV)} + 0.0276 I_F^2 (RMS)$




$$\text{Forward Voltage : } V_{FM} = V_{to} + rd I_{FM}$$


$$\text{Conduction Loss : } P_F = V_{to} I_{F(AV)} + rd I_F^2 (RMS)$$

## Rating and Characteristic Curves


**Fig. 1) Typical Forward Characteristics**




**Fig. 2) Typical Reverse Characteristics**




**Fig. 3) Maximum Forward Derating Curve**




**Fig. 4) Forward Power Dissipation**



**Fig. 5) Typical Junction Capacitance**




Package Outline Dimension



SYMBOL	MILLIMETERS			NOTE
	MINIMUM	NOMINAL	MAXIMUM	
A	1.25	1.30	1.35	
A1	0.00	—	0.10	
A2	1.05	1.10	1.15	
b	1.35	1.42	1.49	
c	0.17	0.22	0.27	
D	2.50	2.60	2.70	
E	4.60	4.80	5.00	
E1	3.90	4.00	4.10	
L	0.79	0.94	1.09	
L1	0.30	0.40	0.50	
Θ	4°	—	10°	

Recommend PCB Solder Land Dimension (Unit: mm)



**The AUK Corp. products are intended for the use as components in general electronic equipment (Office and communication equipment, measuring equipment, home appliance, etc.).**

**Please make sure that you consult with us before you use these AUK Corp. products in equipments which require high quality and / or reliability, and in equipments which could have major impact to the welfare of human life(atomic energy control, airplane, spaceship, transportation, combustion control, all types of safety device, etc.). AUK Corp. cannot accept liability to any damage which may occur in case these AUK Corp. products were used in the mentioned equipments without prior consultation with AUK Corp..**

**Specifications mentioned in this publication are subject to change without notice.**