

Single N-channel MOSFET

ELM14420AA-N

■ General description

ELM14420AA-N uses advanced trench technology to provide excellent $R_{ds(on)}$, low gate charge and low gate resistance.

■ Features

- $V_{ds}=30V$
- $I_d=13.7A$ ($V_{gs}=10V$)
- $R_{ds(on)} < 10.5m\Omega$ ($V_{gs}=10V$)
- $R_{ds(on)} < 12m\Omega$ ($V_{gs}=4.5V$)

■ Maximum absolute ratings


Parameter	Symbol	Limit	Unit	Note	
Drain-source voltage	V_{ds}	30	V		
Gate-source voltage	V_{gs}	± 12	V		
Continuous drain current	I_d	Ta=25°C	13.7	A	1
		Ta=70°C	9.7		
Pulsed drain current	I_{dm}	60	A	2	
Power dissipation	P_d	Ta=25°C	3.1	W	
		Ta=70°C	2.0		
Junction and storage temperature range	T_j, T_{stg}	-55 to 150	°C		

■ Thermal characteristics

Parameter		Symbol	Typ.	Max.	Unit	Note
Maximum junction-to-ambient	$t \leq 10s$	$R_{\theta ja}$	28	40	°C/W	1
Maximum junction-to-ambient	Steady-state		54	75	°C/W	
Maximum junction-to-lead	Steady-state	$R_{\theta jl}$	21	30	°C/W	3


■ Pin configuration

SOP-8(TOP VIEW)



Pin No.	Pin name
1	SOURCE
2	SOURCE
3	SOURCE
4	GATE
5	DRAIN
6	DRAIN
7	DRAIN
8	DRAIN

■ Circuit



Single N-channel MOSFET

ELM14420AA-N

■Electrical characteristics

Ta=25°C

Parameter	Symbol	Condition	Min.	Typ.	Max.	Unit
STATIC PARAMETERS						
Drain-source breakdown voltage	BVdss	Id=250μA, Vgs=0V	30			V
Zero gate voltage drain current	Idss	Vds=24V, Vgs=0V		0.004	1.000	μA
		Tj=55°C			5.000	
Gate-body leakage current	Igss	Vds=0V, Vgs=±12V			100	nA
Gate threshold voltage	Vgs(th)	Vds=Vgs, Id=250μA	0.6	1.1	2.0	V
On state drain current	Id(on)	Vgs=4.5V, Vds=5V	40			A
Static drain-source on-resistance	Rds(on)	Vgs=10V		8.3	10.5	mΩ
		Id=13.7A	Tj=125°C	12.5	15.0	
		Vgs=4.5V, Id=12.7A		9.7	12.0	mΩ
Forward transconductance	Gfs	Vds=5V, Id=13.7A	30	37		S
Diode forward voltage	Vsd	Is=1A, Vgs=0V		0.76	1.00	V
Max. body-diode continuous current	Is				5	A
DYNAMIC PARAMETERS						
Input capacitance	Ciss			3656	4050	pF
Output capacitance	Coss	Vgs=0V, Vds=15V, f=1MHz		256		pF
Reverse transfer capacitance	Crss			168		pF
Gate resistance	Rg	Vgs=0V, Vds=0V, f=1MHz		0.86	1.10	Ω
SWITCHING PARAMETERS						
Total gate charge (4.5V)	Qg			30.5	36.0	nC
Gate-source charge	Qgs	Vgs=10V, Vds=15V, Id=13.7A		4.6		nC
Gate-drain charge	Qgd			8.6		nC
Turn-on delay time	td(on)			5.5	9.0	ns
Turn-on rise time	tr	Vgs=10V, Vds=15V		3.4	7.0	ns
Turn-off delay time	td(off)	RI=1.1Ω, Rgen=0Ω		49.8	75.0	ns
Turn-off fall time	tf			5.9	11.0	ns
Body diode reverse recovery time	trr	If=13.7A, dl/dt=100A/μs		22.5	28.0	ns
Body diode reverse recovery charge	Qrr	If=13.7A, dl/dt=100A/μs		12.5	16.0	nC

NOTE :

1. The value of Rθja is measured with the device mounted on 1in² FR-4 board of 2oz. Copper, in still air environment with Ta=25°C. The value in any given applications depends on the user's specific board design, The current rating is based on the t ≤ 10s thermal resistance rating.
2. Repetitive rating, pulse width limited by junction temperature.
3. The Rθja is the sum of the thermal impedance from junction to lead Rθjl and lead to ambient.
4. The static characteristics in Figures 1 to 6 are obtained using 80μs pulses, duty cycle 0.5%max.
5. These tests are performed with the device mounted on 1in² FR-4 board with 2oz. Copper, in a still air environment with Ta=25°C. The SOA curve provides a single pulse rating.

Single N-channel MOSFET

ELM14420AA-N

■ Typical electrical and thermal characteristics




Figure 1: On-Regions Characteristics




Figure 2: Transfer Characteristics




Figure 3: On-Resistance vs. Drain Current and Gate Voltage




Figure 4: On-Resistance vs. Junction Temperature




Figure 5: On-Resistance vs. Gate-Source Voltage




Figure 6: Body-Diode Characteristics

Single N-channel MOSFET

ELM14420AA-N




Figure 7: Gate-Charge Characteristics




Figure 8: Capacitance Characteristics




Figure 9: Maximum Forward Biased Safe Operating Area (Note E)




Figure 10: Single Pulse Power Rating Junction-to-Ambient (Note E)




Figure 11: Normalized Maximum Transient Thermal Impedance