

DATA SHEET

PIN Diode Chips Supplied on Film Frame

Applications

- Switches
- Attenuators

Features

- Preferred device for module applications
- PIN diodes supplied are 100% tested, saw cut, and mounted on film frame
- Low cost

NEW



Skyworks Green™ products are RoHS (Restriction of Hazardous Substances)-compliant, conform to the EIA/EICTA/JEITA Joint Industry Guide (JIG) Level A guidelines, are halogen free according to IEC-61249-2-21, and contain <1,000 ppm antimony trioxide in polymeric materials.



Description

The PIN diodes that comprise this family of diodes supplied on film frames are designed for high volume applications from 10 MHz to over 3 GHz. This family contains two groups of PIN diodes:

1. Low-capacitance, low-resistance PIN diodes designed primarily for RF switching applications:

SMP1320-099
 SMP1321-099
 SMP1322-099
 SMP1340-099
 SMP1353-099

2. PIN diodes with thick I-layers designed for low-distortion RF variable attenuator applications:

SMP1302-099
 SMP1304-099
 SMP1307-099

These PIN diodes are provided as 100 percent tested, diced wafers mounted on film frames for optimal compatibility with high-volume pick-and-place assembly techniques.

Absolute maximum ratings are provided in Table 1. Electrical specifications are provided in Table 2. Chip dimensions are shown in Table 3. Typical performance characteristics are illustrated in Figures 1 through 6. Figure 7 describes the wafer film frame.

Table 1. PIN Diode Chips Absolute Maximum Ratings

Parameter	Symbol	Minimum	Maximum	Units
Reverse voltage	V _R		Voltage rating	V
Power dissipation @ 25 °C at the base of the chip	P _d		250	mW
Operating temperature	T _{OP}	-65	+150	°C
Storage temperature	T _{STG}	-65	+150	°C

Note: Exposure to maximum rating conditions for extended periods may reduce device reliability. There is no damage to device with only one parameter set at the limit and all other parameters set at or below their nominal value.

CAUTION: Although these devices are designed to be as robust as possible, Electrostatic Discharge (ESD) can damage them. These devices must be protected at all times from ESD. Static charges may easily produce potentials of several kilovolts on the human body or equipment, which can discharge without detection. Industry-standard ESD precautions should be used at all times. PIN diode chips supplied on film frames are Class 1C ESD devices.

Table 2. PIN Diode Chips Electrical Specifications (Note 1)

(T_{OP} = 25 °C)

Part Number	Voltage Rating (V)	Max C _J (pF) V _R = 30 V, f = 1 MHz	Typ V _F (mV) @ I _F = 10 mA	Max R _s (Ω) I _F = 1 mA, f = 100 MHz	Max R _s (Ω) I _F = 10 mA, f = 100 MHz	Typ T _L (ns) I _F = 10 mA
Switching Applications						
SMP1320-099	50	0.175	850	2 typ	0.9	400
SMP1321-099	100	0.150	860	3 typ	2.0	400
SMP1322-099	50	0.850	825	1.5	0.45 typ	400
SMP1340-099	50	0.15 @ 10 V	880	1.7 typ	1.2	100
SMP1353-099	200	0.13 @ 20 V	825	15	2.8	1000
Attenuator Applications						
SMP1302-099	200	0.15	800	20	3	700
SMP1304-099	200	0.15	800	50	7	1000
SMP1307-099	200	0.20	850	75 typ	1.5	1500

Note 1: Performance is guaranteed only under the conditions listed in this Table.

Reverse current is specified @ 10 μA maximum at the voltage rating. This voltage should not be exceeded.

The PIN diodes listed here are processed on 100 mm silicon wafers, 100% DC tested, saw cut, and shipped on 6-inch film frame hoops.

Electrical rejects are identified with black ink on the film frame.

Attenuators are 100% series resistance tested @ 1 mA/100 MHz.

Table 3. PIN Diode Chip Dimensions

Part Number	Quantity of Good Diodes Per Wafer		Chip Size (In)	Chip Height (In)	Anode Contact (In)
	Minimum	Nominal			
SMP1320-099	40000	46000	0.0135 ± 0.001	0.005 ± 0.001	0.0030 ± 0.0003
SMP1321-099	40000	46000	0.0135 ± 0.001	0.005 ± 0.001	0.0030 ± 0.0003
SMP1322-099	40000	46000	0.0135 ± 0.001	0.005 ± 0.001	0.0075 ± 0.0005
SMP1340-099	65000	72000	0.0105 ± 0.001	0.005 ± 0.001	0.0029 ± 0.0003
SMP1353-099	65000	72000	0.0105 ± 0.001	0.005 ± 0.001	0.0070 ± 0.0005
SMP1302-099	40000	46000	0.0135 ± 0.001	0.005 ± 0.001	0.0085 ± 0.0005
SMP1304-099	40000	46000	0.0135 ± 0.001	0.009 ± 0.001	0.0085 ± 0.0005
SMP1307-099	20000	25000	0.0185 ± 0.001	0.009 ± 0.001	0.0110 ± 0.0005

Typical Performance Characteristics

(Top = 25 °C)




Figure 1. Series Resistance vs Forward Current @ 100 MHz




Figure 2. Capacitance vs Reverse Voltage




Figure 3. Series Resistance vs Forward Current @ 100 MHz




Figure 4. Capacitance vs Reverse Voltage




Figure 5. Capacitance vs Reverse Voltage (SMP1307-099)




Figure 6. Series Resistance vs Forward Current (SMP1307-099)




Figure 7. Wafer Film Frame Description

Copyright © 2002-2008, 2011-2013 Skyworks Solutions, Inc. All Rights Reserved.

Information in this document is provided in connection with Skyworks Solutions, Inc. ("Skyworks") products or services. These materials, including the information contained herein, are provided by Skyworks as a service to its customers and may be used for informational purposes only by the customer. Skyworks assumes no responsibility for errors or omissions in these materials or the information contained herein. Skyworks may change its documentation, products, services, specifications or product descriptions at any time, without notice. Skyworks makes no commitment to update the materials or information and shall have no responsibility whatsoever for conflicts, incompatibilities, or other difficulties arising from any future changes.

No license, whether express, implied, by estoppel or otherwise, is granted to any intellectual property rights by this document. Skyworks assumes no liability for any materials, products or information provided hereunder, including the sale, distribution, reproduction or use of Skyworks products, information or materials, except as may be provided in Skyworks Terms and Conditions of Sale.

THE MATERIALS, PRODUCTS AND INFORMATION ARE PROVIDED "AS IS" WITHOUT WARRANTY OF ANY KIND, WHETHER EXPRESS, IMPLIED, STATUTORY, OR OTHERWISE, INCLUDING FITNESS FOR A PARTICULAR PURPOSE OR USE, MERCHANTABILITY, PERFORMANCE, QUALITY OR NON-INFRINGEMENT OF ANY INTELLECTUAL PROPERTY RIGHT; ALL SUCH WARRANTIES ARE HEREBY EXPRESSLY DISCLAIMED. SKYWORKS DOES NOT WARRANT THE ACCURACY OR COMPLETENESS OF THE INFORMATION, TEXT, GRAPHICS OR OTHER ITEMS CONTAINED WITHIN THESE MATERIALS. SKYWORKS SHALL NOT BE LIABLE FOR ANY DAMAGES, INCLUDING BUT NOT LIMITED TO ANY SPECIAL, INDIRECT, INCIDENTAL, STATUTORY, OR CONSEQUENTIAL DAMAGES, INCLUDING WITHOUT LIMITATION, LOST REVENUES OR LOST PROFITS THAT MAY RESULT FROM THE USE OF THE MATERIALS OR INFORMATION, WHETHER OR NOT THE RECIPIENT OF MATERIALS HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

Skyworks products are not intended for use in medical, lifesaving or life-sustaining applications, or other equipment in which the failure of the Skyworks products could lead to personal injury, death, physical or environmental damage. Skyworks customers using or selling Skyworks products for use in such applications do so at their own risk and agree to fully indemnify Skyworks for any damages resulting from such improper use or sale.

Customers are responsible for their products and applications using Skyworks products, which may deviate from published specifications as a result of design defects, errors, or operation of products outside of published parameters or design specifications. Customers should include design and operating safeguards to minimize these and other risks. Skyworks assumes no liability for applications assistance, customer product design, or damage to any equipment resulting from the use of Skyworks products outside of stated published specifications or parameters.

Skyworks, the Skyworks symbol, and "Breakthrough Simplicity" are trademarks or registered trademarks of Skyworks Solutions, Inc., in the United States and other countries. Third-party brands and names are for identification purposes only, and are the property of their respective owners. Additional information, including relevant terms and conditions, posted at www.skyworksinc.com, are incorporated by reference.