

PMV170UN

20 V, single N-channel Trench MOSFET

3 August 2012

Product data sheet

1. Product profile

1.1 General description

N-channel enhancement mode Field-Effect Transistor (FET) in a small SOT23 (TO-236AB) Surface-Mounted Device (SMD) plastic package using Trench MOSFET technology.

1.2 Features and benefits

- Low threshold voltage
- Very fast switching
- Trench MOSFET technology

1.3 Applications

- Relay driver
- High-speed line driver
- Low-side loadswitch
- Switching circuits

1.4 Quick reference data

Table 1. Quick reference data

Symbol	Parameter	Conditions	Min	Typ	Max	Unit
V_{DS}	drain-source voltage	$T_{amb} = 25\text{ °C}$	-	-	20	V
V_{GS}	gate-source voltage		-8	-	8	V
I_D	drain current	$V_{GS} = 4.5\text{ V}; T_{amb} = 25\text{ °C}; t \leq 5\text{ s}$	[1]	-	1.5	A
Static characteristics						
$R_{DS(on)}$	drain-source on-state resistance	$V_{GS} = 4.5\text{ V}; I_D = 1\text{ A}; T_J = 25\text{ °C}$	-	140	165	mΩ



[1] Device mounted on an FR4 Printed-Circuit Board (PCB), single-sided copper, tin-plated, mounting pad for drain 6 cm².

PMV170UN

20 V, single N-channel Trench MOSFET

2. Pinning information

Table 2. Pinning information

Pin	Symbol	Description	Simplified outline	Graphic symbol
1	G	gate	 <p>TO-236AB (SOT23)</p>	 <p>017aaa253</p>
2	S	source		
3	D	drain		

3. Ordering information

Table 3. Ordering information

Type number	Package		
	Name	Description	Version
PMV170UN	TO-236AB	plastic surface-mounted package; 3 leads	SOT23

4. Marking

Table 4. Marking codes

Type number	Marking code
PMV170UN	EG%

[1] % = placeholder for manufacturing site code

5. Limiting values

Table 5. Limiting values

In accordance with the Absolute Maximum Rating System (IEC 60134).

Symbol	Parameter	Conditions		Min	Max	Unit
V_{DS}	drain-source voltage	$T_{amb} = 25\text{ °C}$		-	20	V
V_{GS}	gate-source voltage			-8	8	V
I_D	drain current	$V_{GS} = 4.5\text{ V}; T_{amb} = 25\text{ °C}; t \leq 5\text{ s}$	[1]	-	1.5	A
		$V_{GS} = 4.5\text{ V}; T_{amb} = 25\text{ °C}$	[1]	-	1	A
		$V_{GS} = 4.5\text{ V}; T_{amb} = 100\text{ °C}$	[1]	-	0.9	A
I_{DM}	peak drain current	$T_{amb} = 25\text{ °C};$ single pulse; $t_p \leq 10\text{ }\mu\text{s}$		-	4	A
P_{tot}	total power dissipation	$T_{amb} = 25\text{ °C}$	[2]	-	325	mW
			[1]	-	455	mW
		$T_{sp} = 25\text{ °C}$		-	1140	mW

PMV170UN

20 V, single N-channel Trench MOSFET

Symbol	Parameter	Conditions		Min	Max	Unit
T_j	junction temperature			-55	150	°C
T_{amb}	ambient temperature			-55	150	°C
T_{stg}	storage temperature			-65	150	°C
Source-drain diode						
I_s	source current	$T_{amb} = 25\text{ °C}$	[1]	-	0.7	A

[1] Device mounted on an FR4 Printed-Circuit Board (PCB), single-sided copper, tin-plated, mounting pad for drain 6 cm^2 .

[2] Device mounted on an FR4 Printed-Circuit Board (PCB), single-sided copper, tin-plated and standard footprint.

6. Thermal characteristics

Table 6. Thermal characteristics

Symbol	Parameter	Conditions		Min	Typ	Max	Unit
$R_{th(j-a)}$	thermal resistance from junction to ambient	in free air	[1]	-	333	385	K/W
			[2]	-	240	275	K/W
		in free air; $t \leq 5\text{ s}$	[2]	-	203	235	K/W
$R_{th(j-sp)}$	thermal resistance from junction to solder point			-	85	100	K/W

[1] Device mounted on an FR4 PCB, single-sided copper, tin-plated and standard footprint.

[2] Device mounted on an FR4 PCB, single-sided copper, tin-plated, mounting pad for drain 6 cm^2 .

PMV170UN

20 V, single N-channel Trench MOSFET

Symbol	Parameter	Conditions	Min	Typ	Max	Unit
I _{GSS}	gate leakage current	V _{GS} = 8 V; V _{DS} = 0 V; T _j = 25 °C	-	-	100	nA
		V _{GS} = -8 V; V _{DS} = 0 V; T _j = 25 °C	-	-	100	nA
R _{DS(on)}	drain-source on-state resistance	V _{GS} = 4.5 V; I _D = 1 A; T _j = 25 °C	-	140	165	mΩ
		V _{GS} = 4.5 V; I _D = 1 A; T _j = 150 °C	-	208	248	mΩ
		V _{GS} = 2.5 V; I _D = 1 A; T _j = 25 °C	-	175	220	mΩ
		V _{GS} = 1.8 V; I _D = 0.25 A; T _j = 25 °C	-	237	337	mΩ
g _{fs}	forward transconductance	V _{DS} = 10 V; I _D = 1 A; T _j = 25 °C	-	3.4	-	S
Dynamic characteristics						
Q _{G(tot)}	total gate charge	V _{DS} = 10 V; I _D = 1 A; V _{GS} = 4.5 V; T _j = 25 °C	-	1.1	1.65	nC
Q _{GS}	gate-source charge		-	0.15	-	nC
Q _{GD}	gate-drain charge		-	0.3	-	nC
C _{iss}	input capacitance	V _{DS} = 10 V; f = 1 MHz; V _{GS} = 0 V; T _j = 25 °C	-	83	-	pF
C _{oss}	output capacitance		-	37	-	pF
C _{rss}	reverse transfer capacitance		-	26	-	pF
t _{d(on)}	turn-on delay time		-	6	-	ns
t _r	rise time	V _{DS} = 10 V; I _D = 1 A; V _{GS} = 4.5 V; R _{G(ext)} = 6 Ω; T _j = 25 °C	-	12	-	ns
t _{d(off)}	turn-off delay time		-	16	-	ns
t _f	fall time		-	8	-	ns
Source-drain diode						
V _{SD}	source-drain voltage	I _S = 0.7 A; V _{GS} = 0 V; T _j = 25 °C	-	0.8	1.2	V