

**Silicon NPN Power Transistors**

**2SC1185**

**DESCRIPTION**


- With TO-3 package
- Wide area of safe operation
- High breakdown voltage  
:V<sub>CEO</sub>=250V(min)

**APPLICATIONS**

- For voltage regulator, inverter, switching mode power supply applications.

**PINNING(see Fig.2)**

PIN	DESCRIPTION
1	Base
2	Emitter
3	Collector



**Absolute maximum ratings(Ta=?)**

SYMBOL	PARAMETER	CONDITIONS	VALUE	UNIT
V <sub>CBO</sub>	Collector-base voltage	Open emitter	300	V
V <sub>CEO</sub>	Collector-emitter voltage	Open base	250	V
V <sub>EBO</sub>	Emitter-base voltage	Open collector	5	V
I <sub>C</sub>	Collector current		0.7	A
P <sub>D</sub>	Total power dissipation	T <sub>C</sub> =25?	50	W
T <sub>j</sub>	Junction temperature		150	?
T <sub>stg</sub>	Storage temperature		-55~150	?

## Silicon NPN Power Transistors

## 2SC1185

## CHARACTERISTICS

T<sub>j</sub>=25° unless otherwise specified

SYMBOL	PARAMETER	CONDITIONS	MIN	TYP.	MAX	UNIT
V <sub>(BR)CEO</sub>	Collector-emitter breakdown voltage	I <sub>C</sub> =30mA; I <sub>B</sub> =0	250			V
V <sub>(BR)CBO</sub>	Collector-base breakdown voltage	I <sub>C</sub> =1mA; I <sub>E</sub> =0	300			V
V <sub>(BR)EBO</sub>	Emitter-base breakdown voltage	I <sub>E</sub> =1mA; I <sub>C</sub> =0	5			V
V <sub>CEsat</sub>	Collector-emitter saturation voltage	I <sub>C</sub> =500mA; I <sub>B</sub> =100mA			1.0	V
V <sub>BEsat</sub>	Base-emitter saturation voltage	I <sub>C</sub> =500mA; I <sub>B</sub> =100mA			1.5	V
I <sub>CBO</sub>	Collector cut-off current	V <sub>CB</sub> =200V; I <sub>E</sub> =0			10	μA
I <sub>EBO</sub>	Emitter cut-off current	V <sub>EB</sub> =5V; I <sub>C</sub> =0			10	μA
h <sub>FE</sub>	DC current gain	I <sub>C</sub> =0.4A; V <sub>CE</sub> =10V	40		200	

PACKAGE OUTLINE




Fig.2 outline dimensions