

Silicon NPN Power Transistors

MJE13004

DESCRIPTION


- With TO-220C package
- High voltage ,high speed

APPLICATIONS

- Particularly suited for 115V and 220V switchmode applications such as switching regulators,inverters ,motor controls,solenoid/ relay drivers and deflection circuits

PINNING

PIN	DESCRIPTION
1	Base
2	Collector;connected to mounting base
3	Emitter



ABSOLUTE MAXIMUM RATINGS(T_c=25°C)

SYMBOL	PARAMETER	CONDITIONS	VALUE	UNIT
V _{CBO}	Collector-base voltage	Open emitter	600	V
V _{CEO}	Collector-emitter voltage	Open base	300	V
V _{EBO}	Emitter-base voltage	Open collector	9	V
I _C	Collector current (DC)		4	A
I _{CM}	Collector current-Peak		8	A
I _B	Base current		2	A
I _{BM}	Base current-Peak		4	A
P _D	Total power dissipation	T _a =25°C	2	W
		T _c =25°C	75	
T _j	Junction temperature		150	°C
T _{stg}	Storage temperature		-65~150	°C

THERMAL CHARACTERISTICS

SYMBOL	PARAMETER	MAX	UNIT
R _{th j-C}	Thermal resistance from junction to case	1.67	°C/W

Silicon NPN Power Transistors

MJE13004

CHARACTERISTICS

T_j=25 °C unless otherwise specified

SYMBOL	PARAMETER	CONDITIONS	MIN	TYP.	MAX	UNIT
V _{CEQ(SUS)}	Collector-emitter sustaining voltage	I _C =10mA ; I _B =0	300			V
V _{CE(sat)-1}	Collector-emitter saturation voltage	I _C =1A; I _B =0.2A			0.5	V
V _{CE(sat)-2}	Collector-emitter saturation voltage	I _C =2A; I _B =0.5A			0.6	V
V _{CE(sat)-3}	Collector-emitter saturation voltage	I _C =4A; I _B =1A			1.0	V
V _{BE(sat)-1}	Base-emitter saturation voltage	I _C =1A; I _B =0.2A			1.2	V
V _{BE(sat)-2}	Base-emitter saturation voltage	I _C =2A ; I _B =0.5A			1.6	V
I _{CEV}	Collector cut-off current	V _{CEV} =600V; V _{BE} =1.5V T _C =100 °C			1.0 5.0	mA
I _{EBO}	Emitter cut-off current	V _{EB} =9V; I _C =0			1.0	mA
h _{FE-1}	DC current gain	I _C =1A ; V _{CE} =5V	10		60	
h _{FE-2}	DC current gain	I _C =2A ; V _{CE} =5V	8		40	
f _T	Transition frequency	I _C =0.5A ; V _{CE} =10V; f=1MHz	4			MHz
C _{OB}	Collector outoutput capacitance	I _E =0; f=1MHz ; V _{CB} =10V		65		pF

Switching times

t _d	Delay time	V _{CC} =125V , I _C =2A I _{B1} =-I _{B2} =0.4A t _p =25µs; duty cycle≤1%			0.1	µs
t _r	Rise time				0.7	µs
t _s	Storage time				4.0	µs
t _f	Fall time				0.9	µs

Silicon NPN Power Transistors

MJE13004

PACKAGE OUTLINE




Fig.2 Outline dimensions (unindicated tolerance: $\pm 0.10\text{mm}$)