


2SA1052

■ Features

- Low frequency amplifier



■ Absolute Maximum Ratings Ta = 25°C

Parameter	Symbol	Rating	Unit
Collector to base voltage	V _{CB0}	-30	V
Collector to emitter voltage	V _{CEO}	-30	V
Emitter to base voltage	V _{EBO}	-5	V
Collector current	I _C	-100	mA
Emitter current	I _E	100	mA
Collector power dissipation	P _C	150	mW
Junction temperature	T _j	150	°C
Storage temperature	T _{stg}	-55 to +150	°C

■ Electrical Characteristics Ta = 25°C

Parameter	Symbol	Testconditons	Min	Typ	Max	Unit
Collector to base breakdown voltage	V _{(BR)CB0}	I _C = -10 μA, I _E = 0	-30			V
Collector to emitter breakdown voltage	V _{(BR)CEO}	I _C = -1 mA, R _{BE} = ∞	-30			V
Emitter to base breakdown voltage	V _{(BR)EBO}	I _E = -10 μA, I _C = 0	-5			V
Collector cutoff current	I _{CBO}	V _{CB} = -20 V, I _E = 0			-0.5	mA
Emitter cutoff current	I _{EBO}	V _{EB} = -2 V, I _C = 0			-0.5	mA
DC current transfer ratio	h _{FE}	V _{CE} = -12 V, I _C = -2 mA	100		500	
Collector to emitter saturation voltage	V _{CE(sat)}	I _C = -10 mA, I _B = -1 mA			-0.2	V
Base to emitter voltage	V _{BE}	V _{CE} = -12 V, I _C = -2 mA			-0.75	V

■ hFE Classification

Marking	MB	MC	MD
hFE	100~200	160~320	250~500