


KB160M-20

■ Features

- Low Power Loss, High Efficiency
- High Surge Capability
- High Current Capability and Low Forward Voltage Drop



■ Absolute Maximum Ratings Ta = 25°C

Parameter	Symbol	Rating	Unit
Peak repetitive Peak reverse voltage	V _{RRM}		
Working Peak Reverse Voltage	V _{RWM}	20	V
DC Blocking Voltage	V _R		
RMS Reverse Voltage	V _{R(RMS)}	14	V
Average Rectified Output Current (Note 1) @T _L = 90°C	I _O	1	A
Non-Repetitive Peak Forward Surge Current 8.3ms Single half sine-wave superimposed on rated load (JEDEC Method)	I _{FSM}	25	A
Forward Voltage @I _F = 1.0A @I _F = 3.0A	V _F	0.45 0.75	V
Peak Reverse Current @T _A = 25°C	I _R	1	
At Rated DC Blocking Voltage @T _A = 100°C		10	mA
Thermal Resistance Junction to Ambient	R _{θ JA}	500	°C/W
Operating and Storage Temperature Range	T _j , T _{STG}	-65 to 150	°C

Note: 1. Valid provided that leads are kept at ambient temperature at a distance of 9.5mm from the case.

■ Marking

Marking	SJ
---------	----

KB160M-20

Typical Characteristics

Fig. 1 - Forward Current Derating Curve




Fig. 2 - Maximum Non-Repetitive Peak Forward Surge Current




Fig. 3 - Typical Instantaneous Forward Characteristics




Fig. 4 - Typical Reverse Characteristics




Fig. 5 - Typical Junction Capacitance




Fig. 6 - Typical Transient Thermal Impedance

