





●Applications

General rectification

●Features

- 1) Small power mold type.
(SOD-723)
- 2) Low V_f
- 3) High reliability



●Construction

Silicon epitaxial planar

We declare that the material of product compliance with RoHS requirements.

Pb-Free package is available

RoHS product for packing code suffix "G"

Halogen free product for packing code suffix "H"

Moisture Sensitivity Level 1

Polarity: Color band denotes cathode end

●Absolute maximum ratings ($T_a=25^\circ\text{C}$)

Parameter	Symbol	Limits	Unit
Reverse voltage (repetitive peak)	V_{RM}	40	V
Reverse voltage (DC)	V_R	30	V
Average rectified forward current	I_o	30	mA
Forward current surge peak (60Hz·1cyc)	I_{FSM}	200	mA
Junction temperature	T_j	125	$^\circ\text{C}$
Operating/Storage temperature	T_{stg}	-40 to +125	$^\circ\text{C}$

●Electrical characteristic ($T_a=25^\circ\text{C}$)

Parameter	Symbol	Min.	Typ.	Max.	Unit	Conditions
Forward voltage	V_F	-	-	0.37	V	$I_F=1\text{mA}$
Reverse current	I_R	-	-	0.5	μA	$V_R=30\text{V}$
Capacitance between terminals	C_t	-	2	-	pF	$V_R=1\text{V}$, $f=1\text{MHz}$










●DEVICE MARKING

Device	Marking
SCS751G	5

30mA Surface Mount Schottky Barrier Rectifiers-40V SOD-723 Package

SCS751G

Electrical characteristic curves (Ta=25°C)











30mA Surface Mount Schottky Barrier Rectifiers-40V SOD-723 Package

SCS751G

Electrical characteristic curves (Ta=25°C)








WILLAS



30mA Surface Mount Schottky Barrier Rectifiers-40V
SOD-723 Package

SCS751G

SOD-723





Ordering Information:

Device PN	Packing
SCS751G -T ⁽¹⁾ G ⁽²⁾ -WS	Tape&Reel: 8 Kpcs/Reel

Note: (1) Packing code, Tape & Reel Packing

(2) RoHS product for packing code suffix "G" ; Halogen free product for packing code suffix "H"

Disclaimer

WILLAS reserves the right to make changes without notice to any product specification herein, to make corrections, modifications, enhancements or other changes. WILLAS or anyone on its behalf assumes no responsibility or liability for any errors or inaccuracies. Data sheet specifications and its information contained are intended to provide a product description only. "Typical" parameters which may be included on WILLAS data sheets and/ or specifications can and do vary in different applications and actual performance may vary over time. WILLAS does not assume any liability arising out of the application or use of any product or circuit.

WILLAS products are not designed, intended or authorized for use in medical, life-saving implant or other applications intended for life-sustaining or other related applications where a failure or malfunction of component or circuitry may directly or indirectly cause injury or threaten a life without expressed written approval of WILLAS. Customers using or selling WILLAS components for use in such applications do so at their own risk and shall agree to fully indemnify WILLAS Inc and its subsidiaries harmless against all claims, damages and expenditures.