

Dual Enhancement Mode MOSFET (N- and P-Channel)

Features• **N-Channel**


20V/5A,

 $R_{DS(ON)} = 38m\Omega$ (max.) @ $V_{GS} = 4.5V$ $R_{DS(ON)} = 54m\Omega$ (max.) @ $V_{GS} = 2.5V$ $R_{DS(ON)} = 85m\Omega$ (max.) @ $V_{GS} = 1.8V$ • **P-Channel**


-20V/-3.3A,

 $R_{DS(ON)} = 85m\Omega$ (max.) @ $V_{GS} = -4.5V$ $R_{DS(ON)} = 120m\Omega$ (max.) @ $V_{GS} = -2.5V$ $R_{DS(ON)} = 210m\Omega$ (max.) @ $V_{GS} = -1.8V$

• Reliable and Rugged

• Lead Free and Green Devices Available
(RoHS Compliant)**Pin Description**

Top View of SOT-23-6




N-Channel

P-Channel

Applications

- Power Management in Notebook Computer, Portable Equipment and Battery Powered Systems.
- Load Switch

Ordering and Marking Information

SM2607CS □□-□□ □  Assembly Material Handling Code Temperature Range Package Code	Package Code C : SOT-23-6 Operating Junction Temperature Range C : -55 to 150 °C Handling Code TR : Tape & Reel (3000ea/reel) Assembly Material G : Halogen and Lead Free Device
SM2607CS C : K07XX	XX - Lot Code

Note : SINOPOWER lead-free products contain molding compounds/die attach materials and 100% matte tin plate termination finish; which are fully compliant with RoHS. SINOPOWER lead-free products meet or exceed the lead-free requirements of IPC/JEDEC J-STD-020D for MSL classification at lead-free peak reflow temperature. SINOPOWER defines "Green" to mean lead-free (RoHS compliant) and halogen free (Br or Cl does not exceed 900ppm by weight in homogeneous material and total of Br and Cl does not exceed 1500ppm by weight).

SINOPOWER reserves the right to make changes to improve reliability or manufacturability without notice, and advise customers to obtain the latest version of relevant information to verify before placing orders.

Absolute Maximum Ratings ($T_A = 25^\circ\text{C}$ unless otherwise noted)

Symbol	Parameter	N Channel	P Channel	Unit
Common Ratings				
V_{DSS}	Drain-Source Voltage	20	-20	V
V_{GSS}	Gate-Source Voltage	± 12	± 12	V
I_D	Continuous Drain Current	$T_A=25^\circ\text{C}$	5	-3.3
		$T_A=70^\circ\text{C}$	4	-2.6
I_{DM}	300 μs Pulsed Drain Current	$V_{GS}=10\text{V}$	20	-13
I_S	Diode Continuous Forward Current		1	
T_J	Maximum Junction Temperature		150	$^\circ\text{C}$
T_{STG}	Storage Temperature Range		-55 to 150	
P_D	Maximum Power Dissipation	$T_A=25^\circ\text{C}$	1.4	W
		$T_A=70^\circ\text{C}$	0.9	
$R_{\theta JA}^*$	Thermal Resistance-Junction to Ambient	$t \leq 10\text{s}$	90	$^\circ\text{C}/\text{W}$
		Steady State	125	

Note: * Surface Mounted on 1in² pad area.

N Channel Electrical Characteristics ($T_A = 25^\circ\text{C}$ unless otherwise noted)

Symbol	Parameter	Test Conditions	N Channel			Unit
			Min.	Typ.	Max.	
Static Characteristics						
BV_{DSS}	Drain-Source Breakdown Voltage	$\text{V}_{\text{GS}}=0\text{V}, \text{I}_{\text{DS}}=250\mu\text{A}$	20	-	-	V
I_{DSS}	Zero Gate Voltage Drain Current	$\text{V}_{\text{DS}}=16\text{V}, \text{V}_{\text{GS}}=0\text{V}$ $\text{T}_J=85^\circ\text{C}$	-	-	1	μA
			-	-	30	
$\text{V}_{\text{GS(th)}}$	Gate Threshold Voltage	$\text{V}_{\text{DS}}=\text{V}_{\text{GS}}, \text{I}_{\text{DS}}=250\mu\text{A}$	0.5	0.7	1	V
I_{GSS}	Gate Leakage Current	$\text{V}_{\text{GS}}=\pm 12\text{V}, \text{V}_{\text{DS}}=0\text{V}$	-	-	± 10	μA
$\text{R}_{\text{DS(ON)}}^{\text{a}}$	Drain-Source On-State Resistance	$\text{V}_{\text{GS}}=4.5\text{V}, \text{I}_{\text{DS}}=5\text{A}$	-	30	38	$\text{m}\Omega$
		$\text{V}_{\text{GS}}=2.5\text{V}, \text{I}_{\text{DS}}=4\text{A}$	-	40	54	
		$\text{V}_{\text{GS}}=1.8\text{V}, \text{I}_{\text{DS}}=1\text{A}$	-	60	85	
Diode Characteristics						
$\text{V}_{\text{SD}}^{\text{a}}$	Diode Forward Voltage	$\text{I}_{\text{SD}}=1\text{A}, \text{V}_{\text{GS}}=0\text{V}$	-	0.75	1.1	V
t_{rr}	Reverse Recovery Time	$\text{I}_{\text{SD}}=5\text{A}, \frac{d\text{I}_{\text{SD}}}{dt}=100\text{A}/\mu\text{s}$	-	10.5	-	ns
Q_{rr}	Reverse Recovery Charge		-	3.2	-	nC
Dynamic Characteristics ^b						
R_g	Gate Resistance	$\text{V}_{\text{GS}}=0\text{V}, \text{V}_{\text{DS}}=0\text{V}, \text{F}=1\text{MHz}$	-	2.2	-	Ω
C_{iss}	Input Capacitance	$\text{V}_{\text{GS}}=0\text{V}, \text{V}_{\text{DS}}=10\text{V}, \text{Frequency}=1.0\text{MHz}$	-	275	-	pF
C_{oss}	Output Capacitance		-	70	-	
C_{rss}	Reverse Transfer Capacitance		-	60	-	
$\text{t}_{\text{d(ON)}}$	Turn-on Delay Time	$\text{V}_{\text{DD}}=10\text{V}, \text{R}_L=10\Omega, \text{I}_{\text{DS}}=1\text{A}, \text{V}_{\text{GEN}}=10\text{V}, \text{R}_G=6\Omega$	-	2.4	4.3	ns
T_r	Turn-on Rise Time		-	13	23	
$\text{t}_{\text{d(OFF)}}$	Turn-off Delay Time		-	15.5	28	
T_f	Turn-off Fall Time		-	3	5.5	
Gate Charge Characteristics ^b						
Q_g	Total Gate Charge	$\text{V}_{\text{DS}}=10\text{V}, \text{I}_{\text{DS}}=5\text{A}$	$\text{V}_{\text{GS}}=4.5\text{V},$	-	4.5	nC
			$\text{V}_{\text{GS}}=10\text{V}$	-	9	
Q_{gs}	Gate-Source Charge	$\text{V}_{\text{DS}}=10\text{V}, \text{V}_{\text{GS}}=10\text{V}, \text{I}_{\text{DS}}=5\text{A}$	-	0.3	-	nC
Q_{gd}	Gate-Drain Charge		-	2	-	
Q_{gth}	Threshold Gate Charge		-	0.8	-	

Note a : Pulse test; pulse width $\leq 300\mu\text{s}$, duty cycle $\leq 2\%$.

Note b : Guaranteed by design, not subject to production testing.





P Channel Electrical Characteristics ($T_A = 25^\circ\text{C}$ unless otherwise noted)

Symbol	Parameter	Test Conditions	P Channel			Unit	
			Min.	Typ.	Max.		
Static Characteristics							
BV_{DSS}	Drain-Source Breakdown Voltage	$V_{\text{GS}}=0\text{V}, I_{\text{DS}}=-250\mu\text{A}$	-20	-	-	V	
I_{DSS}	Zero Gate Voltage Drain Current	$V_{\text{DS}}=-16\text{V}, V_{\text{GS}}=0\text{V}$ $T_J=85^\circ\text{C}$	-	-	-1	μA	
			-	-	-30		
$V_{\text{GS}(\text{th})}$	Gate Threshold Voltage	$V_{\text{DS}}=V_{\text{GS}}, I_{\text{DS}}=-250\mu\text{A}$	-0.5	-0.7	-1	V	
I_{GSS}	Gate Leakage Current	$V_{\text{GS}}=\pm 10\text{V}, V_{\text{DS}}=0\text{V}$	-	-	± 10	μA	
$R_{\text{DS}(\text{ON})}^{\text{a}}$	Drain-Source On-State Resistance	$V_{\text{GS}}=-4.5\text{V}, I_{\text{DS}}=-3.3\text{A}$	-	65	85	$\text{m}\Omega$	
		$V_{\text{GS}}=-2.5\text{V}, I_{\text{DS}}=-2.1\text{A}$	-	90	120		
		$V_{\text{GS}}=-1.8\text{V}, I_{\text{DS}}=-1\text{A}$	-	130	210		
Diode Characteristics							
V_{SD}^{a}	Diode Forward Voltage	$I_{\text{SD}}=-1\text{A}, V_{\text{GS}}=0\text{V}$	-	-0.75	-1.1	V	
t_{rr}	Reverse Recovery Time	$I_{\text{SD}}=-3.3\text{A}, dI_{\text{SD}}/dt=100\text{A}/\mu\text{s}$	-	20	-	ns	
Q_{rr}	Reverse Recovery Charge		-	6	-	nC	
Dynamic Characteristics ^b							
R_g	Gate Resistance	$V_{\text{GS}}=0\text{V}, V_{\text{DS}}=0\text{V}, F=1\text{MHz}$	-	6.8	-	Ω	
C_{iss}	Input Capacitance	$V_{\text{GS}}=0\text{V},$ $V_{\text{DS}}=-10\text{V},$ Frequency=1.0MHz	-	310	-	pF	
C_{oss}	Output Capacitance		-	66	-		
C_{rss}	Reverse Transfer Capacitance		-	54	-		
$t_{\text{d}(\text{ON})}$	Turn-on Delay Time	$V_{\text{DD}}=-10\text{V}, R_L=10\Omega,$ $I_{\text{DS}}=-1\text{A}, V_{\text{GEN}}=-10\text{V},$ $R_G=6\Omega$	-	5.3	-	ns	
T_r	Turn-on Rise Time		-	14.2	-		
$t_{\text{d}(\text{OFF})}$	Turn-off Delay Time		-	22	-		
T_f	Turn-off Fall Time		-	4.6	-		
Gate Charge Characteristics ^b							
Q_g	Total Gate Charge	$V_{\text{DS}}=-10\text{V},$ $I_{\text{DS}}=-3.3\text{A}$	$V_{\text{GS}}=-4.5\text{V},$ $V_{\text{GS}}=-10\text{V}$	-	4.5	-	nC
			-	9.2	-		
Q_{gs}	Gate-Source Charge	$V_{\text{DS}}=-10\text{V}, V_{\text{GS}}=-10\text{V},$ $I_{\text{DS}}=-3.3\text{A}$	-	0.5	-		
Q_{gd}	Gate-Drain Charge		-	1.5	-		
Q_{gth}	Threshold Gate Charge		-	2.2	-		





Note a : Pulse test; pulse width $\leq 300\mu\text{s}$, duty cycle $\leq 2\%$.

Note b : Guaranteed by design, not subject to production testing.

N Channel Typical Operating Characteristics




N Channel Typical Operating Characteristics (Cont.)




N Channel Typical Operating Characteristics (Cont.)


Drain-Source On Resistance




Source-Drain Diode Forward



Capacitance




Gate Charge




P Channel Typical Operating Characteristics


Power Dissipation




Drain Current







Safe Operation Area







Thermal Transient Impedance



P Channel Typical Operating Characteristics (Cont.)





P Channel Typical Operating Characteristics (Cont.)





Avalanche Test Circuit and Waveforms

N Channel





P Channel





Switching Time Test Circuit and Waveforms

N Channel




P Channel



Package Information


SOT-23-6



SYMBOL	SOT-23-6			
	MILLIMETERS		INCHES	
	MIN.	MAX.	MIN.	MAX.
A	-	1.25	-	0.049
A1	0.00	0.15	0.000	0.006
A2	0.90	1.30	0.035	0.051
b	0.30	0.50	0.012	0.020
c	0.08	0.22	0.003	0.009
D	2.70	3.10	0.106	0.122
E	2.60	3.00	0.102	0.118
E1	1.40	1.80	0.055	0.071
e	0.95 BSC		0.037 BSC	
e1	1.90 BSC		0.075 BSC	
L	0.30	0.60	0.012	0.024
θ	0°	8°	0°	8°



Note : 1. Follow JEDEC TO-178 AB.
 2. Dimension D and E1 do not include mold flash, protrusions or gate burrs. Mold flash, protrusion or gate burrs shall not exceed 10 mil per side.

RECOMMENDED LAND PATTERN



UNIT: mm

Carrier Tape & Reel Dimensions




Application	A	H	T1	C	d	D	W	E1	F
SOT-23-6	178.0±2.00	50 MIN.	8.4+2.00 -0.00	13.0+0.50 -0.20	1.5 MIN.	20.2 MIN.	8.0±0.30	1.75±0.10	3.5±0.05
	P0	P1	P2	D0	D1	T	A0	B0	K0
	4.0±0.10	4.0±0.10	2.0±0.05	1.5+0.10 -0.00	1.0 MIN.	0.6+0.00 -0.40	3.20±0.20	3.10±0.20	1.50±0.20


(mm)

Taping Direction Information

SOT-23-6



Classification Profile



Classification Reflow Profiles

Profile Feature	Sn-Pb Eutectic Assembly	Pb-Free Assembly
Preheat & Soak		
Temperature min (T_{smin})	100 °C	150 °C
Temperature max (T_{smax})	150 °C	200 °C
Time (T_{smin} to T_{smax}) (t_s)	60-120 seconds	60-120 seconds
Average ramp-up rate (T_{smax} to T_p)	3 °C/second max.	3°C/second max.
Liquidous temperature (T_L)	183 °C	217 °C
Time at liquidous (t_L)	60-150 seconds	60-150 seconds
Peak package body Temperature (T_p)*	See Classification Temp in table 1	See Classification Temp in table 2
Time (t_p)** within 5°C of the specified classification temperature (T_c)	20** seconds	30** seconds
Average ramp-down rate (T_p to T_{smax})	6 °C/second max.	6 °C/second max.
Time 25°C to peak temperature	6 minutes max.	8 minutes max.

* Tolerance for peak profile Temperature (T_p) is defined as a supplier minimum and a user maximum.
 ** Tolerance for time at peak profile temperature (t_p) is defined as a supplier minimum and a user maximum.

Table 1. SnPb Eutectic Process – Classification Temperatures (Tc)

Package Thickness	Volume mm ³ <350	Volume mm ³ ≥350
<2.5 mm	235 °C	220 °C
≥2.5 mm	220 °C	220 °C

Table 2. Pb-free Process – Classification Temperatures (Tc)

Package Thickness	Volume mm ³ <350	Volume mm ³ 350-2000	Volume mm ³ >2000
<1.6 mm	260 °C	260 °C	260 °C
1.6 mm – 2.5 mm	260 °C	250 °C	245 °C
≥2.5 mm	250 °C	245 °C	245 °C

Reliability Test Program

Test item	Method	Description
SOLDERABILITY	JESD-22, B102	5 Sec, 245°C
HTRB	JESD-22, A108	1000 Hrs, 80% of VDS max @ Tjmax
HTGB	JESD-22, A108	1000 Hrs, 100% of VGS max @ Tjmax
PCT	JESD-22, A102	168 Hrs, 100%RH, 2atm, 121°C
TCT	JESD-22, A104	500 Cycles, -65°C~150°C

Customer Service

Sinopower Semiconductor, Inc.

5F, No. 6, Dusing 1St Rd., Hsinchu Science Park,

Hsinchu, 30078, Taiwan

TEL: 886-3-5635818 Fax: 886-3-5642050