


# 2A Avg. 600 Volts Standard Recovery Diode 20KDA60

## ■最大定格 Maximum Ratings

Item	Symbol	Conditions	Unit
くり返しピーク逆電圧 Repetitive Peak Reverse Voltage	$V_{RRM}$	600	V
平均整流電流 Average Rectified Output Current	$I_O$	50Hz 正弦半波抵抗負荷 50Hz half sine wave Resistance load	1.7 2.0
実効順電流 R.M.S. Forward Current	$I_{F(RMS)}$		3.14
サージ順電流 Surge Forward Current	$I_{FSM}$	75 50Hz 正弦半波, 1 サイクル, 非くり返し 50Hz Half Sine Wave, 1 cycle, Non-repetitive	A
動作接合温度範囲 Operating Junction Temperature Range	$T_{jw}$		-40~+150
保存温度範囲 Storage Temperature Range	$T_{stg}$		-40~+150

## ■OUTLINE DRAWING(mm)



## ■電氣的・熱的特性 Electrical/Thermal Characteristics

Item	Symbol	Conditions	Min.	Typ.	Max.	Unit
ピーク逆電流 Peak Reverse Current	$I_{RM}$	$T_j=25^{\circ}C, V_{RM}=V_{RRM}$	—	—	10	$\mu A$
ピーク順電圧 Peak Forward Voltage	$V_{FM}$	$T_j=25^{\circ}C, I_{FM}=2A$	—	—	1.0	V
熱抵抗 Thermal Resistance	$R_{th(j-a)}$	接合部・周囲間*1 Junction to Ambient	—	—	70	$^{\circ}C/W$
	$R_{th(j-l)}$	接合部・リード間 Junction to Lead	—	—	17	$^{\circ}C/W$

\*1: プリント基板実装 / P.C. Board mounted (L=8mm, Print Lands=15×15 mm, Both Sides)

## ■定格・特性曲線

