

0.5A Avg.

60 Volts


SBD

EP05Q06

最大定格 Maximum Ratings

Item	Symbol	Conditions	Unit
くり返しピーク逆電圧 Repetitive Peak Reverse Voltage	$V_{RRM}$	60	V
平均整流電流 Average Rectified Forward Current	$I_O$	50Hz、正弦半波通電抵抗負荷 50Hz Half Sine Wave Resistive Load	
		$T_a = 25^*$	0.40 A
		$T_l = 96$	0.5 A
実効順電流 R.M.S. Forward Current	$I_{F(RMS)}$	0.785	A
サージ順電流 Surge Forward Current	$I_{FSM}$	8 50Hz正弦半波, 1サイクル, 非くり返し 50Hz Half Sine Wave, 1cycle, Non-repetitive	A
動作接合温度範囲 Operating Junction Temperature Range	$T_{jw}$	-40 ~ +150	
保存温度範囲 Storage Temperature Range	$T_{stg}$	-40 ~ +150	

OUTLINE DRAWING(mm)



電氣的・熱的特性 Electrical/Thermal Characteristics

Item	Symbol	Conditions	Min.	Typ.	Max.	Unit
ピーク逆電流 Peak Reverse Current	$I_{RM}$	$T_j = 25, V_{RM} = V_{RRM}$	-	-	100	$\mu A$
ピーク順電圧 Peak Forward Voltage	$V_{FM}$	$T_j = 25, I_{FM} = 0.5A$	-	-	0.62	V
熱抵抗 Thermal Resistance	$R_{th(j-a)}$	接合部・周囲間* Junction to Ambient*	-	-	300	/W
	$R_{th(j-l)}$	接合部・リード間 Junction to Lead	-	-	70	/W

\*プリント基板実装/Glass-Epoxy Substrate mounted (Soldering Lands= 1 x 1 mm, Both Sides)  
( $T_l$ : Lead Temperature)

定格・特性曲線

