

60A Avg.

30 Volts

SBD


KSQ60A03LB

■最大定格 Maximum Ratings

Item	Symbol	Conditions	Unit
くり返しピーク逆電圧 Repetitive Peak Reverse Voltage	$V_{RRM}$	30	V
平均整流電流* Average Rectified Forward Current	$I_O$	50Hz、正弦半波通電抵抗負荷 50Hz Half Sine Wave Resistive Load	$T_c=106^{\circ}C$ 60
実効順電流* R.M.S. Forward Current	$I_{F(RMS)}$	94.2	A
サージ順電流* Surge Forward Current	$I_{FSM}$	700 50Hz正弦半波、1サイクル、非くり返し 50Hz Half Sine Wave, 1cycle, Non-repetitive	A
動作接合温度範囲 Operating Junction Temperature Range	$T_{jw}$	-40~+150	$^{\circ}C$
保存温度範囲 Storage Temperature Range	$T_{stg}$	-40~+150	$^{\circ}C$
締付トルク Mounting torque	$F_{tor}$	推奨値 Recommended Value	0.5 N·m

\*アノード電極両側通電時 Anode Terminals 1 and 3 Connected

■OUTLINE DRAWING(mm)



■APPROX. NET WEIGHT:5.55g

■電氣的・熱的特性 Electrical/Thermal Characteristics

Item	Symbol	Conditions	Min.	Typ.	Max.	Unit
ピーク逆電流 Peak Reverse Current	$I_{RM}$	$T_j=25^{\circ}C, V_{RM}=V_{RRM}$	—	—	40	mA
ピーク順電圧* Peak Forward Voltage	$V_{FM}$	$T_j=25^{\circ}C, I_{FM}=60A$	—	—	0.54	V
熱抵抗 Thermal Resistance	$R_{th(j-c)}$	接合部・ケース間 Junction to Case	—	—	0.75	$^{\circ}C/W$

\*アノード電極両側通電時 Anode Terminals 1 and 3 Connected

■定格・特性曲線

