

PN4250A  
SILICON  
PNP TRANSISTOR



TO-92 CASE



www.centrasemi.com

**DESCRIPTION:**

The CENTRAL SEMICONDUCTOR PN4250A is a silicon PNP transistor designed for low level, low noise amplifier applications.

**MARKING: FULL PART NUMBER**

**MAXIMUM RATINGS:** ( $T_A=25^\circ\text{C}$ )

Collector-Base Voltage	
Collector-Emitter Voltage	
Collector-Emitter Voltage	
Emitter-Base Voltage	
Continuous Collector Current	
Power Dissipation	
Operating and Storage Junction Temperature	
Thermal Resistance	
Thermal Resistance	

SYMBOL		UNITS
$V_{CBO}$	60	V
$V_{CES}$	60	V
$V_{CEO}$	60	V
$V_{EBO}$	5.0	V
$I_C$	500	mA
$P_D$	625	mW
$T_J, T_{stg}$	-65 to +150	$^\circ\text{C}$
$\theta_{JC}$	83.3	$^\circ\text{C/W}$
$\theta_{JA}$	200	$^\circ\text{C/W}$

**ELECTRICAL CHARACTERISTICS:** ( $T_A=25^\circ\text{C}$  unless otherwise noted)

SYMBOL	TEST CONDITIONS	MIN	MAX	UNITS
$I_{CBO}$	$V_{CB}=50\text{V}$		10	nA
$I_{EBO}$	$V_{EB}=3.0\text{V}$		20	nA
$BV_{CBO}$	$I_C=10\mu\text{A}$	60		V
$BV_{CES}$	$I_C=10\mu\text{A}$	60		V
$BV_{CEO}$	$I_C=5.0\text{mA}$	60		V
$BV_{EBO}$	$I_E=10\mu\text{A}$	5.0		V
$V_{CE(SAT)}$	$I_C=10\text{mA}, I_B=0.5\text{mA}$		0.25	V
$h_{FE}$	$V_{CE}=5.0\text{V}, I_C=100\mu\text{A}$	250	700	
$C_{ob}$	$V_{CB}=5.0\text{V}, f=1.0\text{MHz}$		6.0	pF
$h_{fe}$	$V_{CE}=5.0\text{V}, I_C=1.0\text{mA}, f=1.0\text{kHz}$	250	800	
$h_{ie}$	$V_{CE}=5.0\text{V}, I_C=1.0\text{mA}, f=1.0\text{kHz}$	6.0	20	k $\Omega$
$h_{oe}$	$V_{CE}=5.0\text{V}, I_C=1.0\text{mA}, f=1.0\text{kHz}$	5.0	50	$\mu\text{S}$
$h_{re}$	$V_{CE}=5.0\text{V}, I_C=1.0\text{mA}, f=1.0\text{kHz}$		10	$\times 10^{-4}$
NF	$V_{CE}=5.0\text{V}, I_C=250\mu\text{A}, R_S=1.0\text{k}\Omega$ $f=1.0\text{kHz}, BW=150\text{Hz}$		2.0	dB
NF	$V_{CE}=5.0\text{V}, I_C=20\mu\text{A}, R_S=10\text{k}\Omega$ $f=1.0\text{kHz}, BW=150\text{Hz}$		2.0	dB

R0 (26-July 2013)

PN4250A  
 SILICON  
 PNP TRANSISTOR



TO-92 CASE - MECHANICAL OUTLINE



R1

SYMBOL	INCHES		MILLIMETERS	
	MIN	MAX	MIN	MAX
A (DIA)	0.175	0.205	4.45	5.21
B	0.170	0.210	4.32	5.33
C	0.500	-	12.70	-
D	0.016	0.022	0.41	0.56
E	0.100		2.54	
F	0.050		1.27	
G	0.125	0.165	3.18	4.19
H	0.080	0.105	2.03	2.67
I	0.015		0.38	

TO-92 (REV: R1)

LEAD CODE:

- 1) Emitter
- 2) Base
- 3) Collector

MARKING:






FULL PART NUMBER

R0 (26-July 2013)

PN4250A  
SILICON  
PNP TRANSISTOR



TYPICAL ELECTRICAL CHARACTERISTICS



R0 (26-July 2013)