



Halogens free devices

CHENMKO ENTERPRISE CO.,LTD

SURFACE MOUNT

N-Channel Enhancement Mode Field Effect Transistor

VOLTAGE 600 Volts CURRENT 4 Ampere

CHM04N6NGP

APPLICATION

- * Servo motor control.
- * Power MOSFET gate drivers.
- * Other switching applications.

FEATURE


- * Small flat package. (D2PAK)
- * High density cell design for extremely low $R_{DS(ON)}$.
- * Rugged and reliable.

CONSTRUCTION


- * N-Channel Enhancement



D2PAK



CIRCUIT



Absolute Maximum Ratings $T_A = 25^\circ\text{C}$ unless otherwise noted

Symbol	Parameter	CHM04N6NGP	Units
V_{DSS}	Drain-Source Voltage	600	V
V_{GSS}	Gate-Source Voltage	± 30	V
I_D	Maximum Drain Current - Continuous	4	A
	- Pulsed (Note 3)	16	
P_D	Maximum Power Dissipation	89	W
T_J	Operating Temperature Range	-55 to 150	$^\circ\text{C}$
T_{STG}	Storage Temperature Range	-55 to 150	$^\circ\text{C}$

- Note : 1. Surface Mounted on FR4 Board , $t \leq 10\text{sec}$
 2. Pulse Test , Pulse width $\leq 300\mu\text{s}$, Duty Cycle $\leq 2\%$
 3. Repetitive Rating , Pulse width limited by maximum junction temperature
 4. Guaranteed by design , not subject to production testing

Thermal characteristics

$R_{\theta JA}$	Thermal Resistance, Junction-to-Ambient (Note 1)	62.5	$^\circ\text{C/W}$
-----------------	--	------	--------------------

ELECTRICAL CHARACTERISTIC (CHM04N6NGP)

Electrical Characteristics $T_A = 25^\circ\text{C}$ unless otherwise noted

Symbol	Parameter	Conditions	Min	Typ	Max	Units
--------	-----------	------------	-----	-----	-----	-------

OFF CHARACTERISTICS

BV_{DSS}	Drain-Source Breakdown Voltage	$V_{GS} = 0\text{ V}, I_D = 250\ \mu\text{A}$	600			V
I_{DSS}	Zero Gate Voltage Drain Current	$V_{DS} = 600\text{ V}, V_{GS} = 0\text{ V}$			25	μA
I_{GSSF}	Gate-Body Leakage	$V_{GS} = 30\text{ V}, V_{DS} = 0\text{ V}$			+100	nA
I_{GSSR}	Gate-Body Leakage	$V_{GS} = -30\text{ V}, V_{DS} = 0\text{ V}$			-100	nA

ON CHARACTERISTICS (Note 2)

$V_{GS(th)}$	Gate Threshold Voltage	$V_{DS} = V_{GS}, I_D = 250\ \mu\text{A}$	2		4	V
$R_{DS(on)}$	Static Drain-Source On-Resistance	$V_{GS}=10\text{V}, I_D=2\text{A}$		2.2	2.5	Ω
g_{FS}	Forward Transconductance	$V_{DS}=40\text{V}, I_D = 2\text{A}$		2.8		S

SWITCHING CHARACTERISTICS (Note 4)

Q_g	Total Gate Charge	$V_{DS}=480\text{V}, I_D=4\text{A}$ $V_{GS}=10\text{V}$		24	31	nC
Q_{gs}	Gate-Source Charge			4		
Q_{gd}	Gate-Drain Charge			11		
t_{on}	Turn-On Time	$V_{DD}= 300\text{V}$ $I_D = 4\text{A}, V_{GS} = 10\text{ V}$ $R_{GEN} = 25\Omega$		25	50	nS
t_r	Rise Time			65	120	
t_{off}	Turn-Off Time			75	150	
t_f	Fall Time			65	120	

DRAIN-SOURCE DIODE CHARACTERISTICS AND MAXIMUM RATINGS

I_S	Drain-Source Diode Forward Current	(Note 1)			4	A
V_{SD}	Drain-Source Diode Forward Voltage	$I_S = 2.5\text{A}, V_{GS} = 0\text{ V}$ (Note 2)			1.6	V