



CHENMKO ENTERPRISE CO.,LTD

Halogens free devices

SURFACE MOUNT

N-Channel Enhancement Mode Field Effect Transistor

VOLTAGE 100 Volts CURRENT 17 Ampere

CHM1710PAGP

APPLICATION



- * Servo motor control.
- * Power MOSFET gate drivers.
- * Other switching applications.

FEATURE

- * Small package. (TO-252)
- * Super high dense cell design for extremely low $R_{DS(ON)}$.
- * High power and current handling capability.

CONSTRUCTION

- * N-Channel Enhancement



Absolute Maximum Ratings $T_A = 25^\circ\text{C}$ unless otherwise noted

Symbol	Parameter	CHM1710PAGP	Units
V_{DSS}	Drain-Source Voltage	100	V
V_{GSS}	Gate-Source Voltage	± 20	V
I_D	Maximum Drain Current - Continuous	17	A
	- Pulsed (Note 3)	68	
P_D	Maximum Power Dissipation at $T_c = 25^\circ\text{C}$	50	W
T_J	Operating Temperature Range	-55 to 150	$^\circ\text{C}$
T_{STG}	Storage Temperature Range	-55 to 150	$^\circ\text{C}$

Note : 1. Surface Mounted on FR4 Board , $t \leq 10\text{sec}$
 2. Pulse Test , Pulse width $\leq 300\mu\text{s}$, Duty Cycle $\leq 2\%$
 3. Repetitive Rating , Pulse width limited by maximum junction temperature
 4. Guaranteed by design , not subject to production trsting

Thermal characteristics

$R_{\theta JA}$	Thermal Resistance, Junction-to-Ambient (Note 1)	50	$^\circ\text{C/W}$
-----------------	--	----	--------------------

RATING CHARACTERISTIC CURVES (CHM1710PAGP)

Electrical Characteristics $T_A = 25^\circ\text{C}$ unless otherwise noted

Symbol	Parameter	Conditions	Min	Typ	Max	Units
--------	-----------	------------	-----	-----	-----	-------

OFF CHARACTERISTICS

BV _{DSS}	Drain-Source Breakdown Voltage	V _{GS} = 0 V, I _D = 250 μ A	100			V
I _{DSS}	Zero Gate Voltage Drain Current	V _{DS} = 100 V, V _{GS} = 0 V			1	μ A
I _{GSSF}	Gate-Body Leakage	V _{GS} = 20V, V _{DS} = 0 V			+100	nA
I _{GSSR}	Gate-Body Leakage	V _{GS} = -20V, V _{DS} = 0 V			-100	nA

ON CHARACTERISTICS (Note 2)

V _{GS(th)}	Gate Threshold Voltage	V _{DS} = V _{GS} , I _D = 250 μ A	2		4	V
R _{DS(on)}	Static Drain-Source On-Resistance	V _{GS} =10V, I _D =15A		65	85	m Ω
g _{FS}	Forward Transconductance	V _{DS} =2.5V, I _D = 15A		11		S

SWITCHING CHARACTERISTICS (Note 4)

Q _g	Total Gate Charge	V _{DS} =80V, I _D =19A V _{GS} =10V		26	34	nC
Q _{gs}	Gate-Source Charge			3.3		
Q _{gd}	Gate-Drain Charge			16.2		
t _{on}	Turn-On Time	V _{DD} = 50V I _D =19A, V _{GS} = 10 V R _{GEN} = 25 Ω		17	34	nS
t _r	Rise Time			51	100	
t _{off}	Turn-Off Time			16	32	
t _f	Fall Time			71	140	

DRAIN-SOURCE DIODE CHARACTERISTICS AND MAXIMUM RATINGS

I _S	Drain-Source Diode Forward Current				15	A
V _{SD}	Drain-Source Diode Forward Voltage	I _S = 15A, V _{GS} = 0 V			1.5	V

RATING CHARACTERISTIC CURVES (CHM1710PAGP)

Typical Electrical Characteristics

Figure 1. Output Characteristics




Figure 2. Transfer Characteristics




Figure 3. Gate Charge




Figure 4. On-Resistance Variation with Temperature




Figure 5. Gate Threshold Variation with Temperature

