



Micro Commercial Components 20736 Marilla Street Chatsworth

CA 91311

Phone: (818) 701-4933 Fax: (818) 701-4939

AZ23C2V7W THRU AZ23C39W

Features

- Dual zeners in common anode configuration.
- 200mW power dissipation rating.
- . Ideally suited for automatic insertion.
- \triangle vz for both diodes in one case is \leq 5%.
- Epoxy meets UL 94 V-0 flammability rating
- Moisture Sensitivity Level 1
- Halogen free available upon request by adding suffix "-HF"


Absolute Maximum Ratings

| Symbol | Parameter | Rating | Unit |
|------------------|---|-------------|------|
| P_D | Power dissipation | 200 | mW |
| R_{thJA} | Thermal Resistance, Junction to Ambient Air | 625 | °C/W |
| T _{STG} | Storage Temperature Range | -65 to +150 | °C |


*Pin Configuration - Top View



200 mW Zener Diode 2.7 to 39 Volts



| DIMENSIONS | | | | | |
|------------|--------|------|------|------|------|
| | INCHES | | MM | | |
| DIM | MIN | MAX | MIN | MAX | NOTE |
| Α | .070 | .087 | 1.80 | 2.20 | |
| В | .083 | .096 | 2.10 | 2.45 | |
| C | .045 | .054 | 1.15 | 1.35 | |
| D | .047 | .056 | 1.20 | 1.40 | |
| Е | | .004 | | .10 | |
| F | .006 | .016 | .15 | .40 | |
| G | .035 | .044 | .90 | 1.10 | |
| Н | .002 | .006 | .05 | .15 | |
| | 010 | | 25 | | |





AZ23C2V7W THRU AZ23C39W

Micro Commercial Components

Electrical Characteristics @ T_A= 25°C unless otherwise specified

| | Marking | Zener voltage Range (note1) | Maximum zener Impedance (note 2) | | Typical Temperature | Min reverse Voltage (note1) |
|-----------|---------|--------------------------------|---|---|---------------------|-----------------------------|
| | Code | @ I _{ZT} =5.0mA | Z _{ZT} @I _{ZT} =5.0mA | Z _{Zk} @I _{Zk} =1.0mA | coefficient | @I _R =0.1uA |
| | | V _Z (volts) | Ohms | Ohms | Tc (%/℃) | V _R (volts) |
| AZ23C2V7W | KD1 | 2.5-2.9 | 83 | 500 | -0.065 | _ |
| AZ23C3V0W | KD2 | 2.8-3.2 | 95 | 500 | -0.060 | _ |
| AZ23C3V3W | KD3 | 3.1-3.5 | 95 | 500 | -0.055 | _ |
| AZ23C3V6W | KD4 | 3.4-3.8 | 95 | 500 | -0.055 | _ |
| AZ23C3V9W | KD5 | 3.7-4.1 | 95 | 500 | -0.050 | _ |
| AZ23C4V3W | KD6 | 4.0-4.6 | 95 | 500 | -0.035 | _ |
| AZ23C4V7W | KD7 | 4.4-5.0 | 78 | 500 | -0.015 | _ |
| AZ23C5V1W | KD8 | 4.8-5.4 | 60 | 480 | +0.005 | 0.8 |
| AZ23C5V6W | KD9 | 5.2-6.0 | 40 | 400 | +0.020 | 1.0 |
| AZ23C6V2W | KDA | 5.8-6.6 | 10 | 200 | +0.030 | 2.0 |
| AZ23C6V8W | KDB | 6.4-7.2 | 8.0 | 150 | +0.045 | 3.0 |
| AZ23C7V5W | KDC | 7.0-7.9 | 7.0 | 50 | +0.050 | 5.0 |
| AZ23C8V2W | KDD | 7.7-8.7 | 7.0 | 50 | +0.055 | 6.0 |
| AZ23C9V1W | KDE | 8.5-9.6 | 10 | 50 | +0.065 | 7.0 |
| AZ23C10W | KDF | 9.4-10.6 | 15 | 70 | +0.065 | 7.5 |
| AZ23C11W | KDG | 10.4-11.6 | 20 | 70 | +0.070 | 8.5 |
| AZ23C12W | KDH | 11.4-12.7 | 20 | 90 | +0.075 | 9.0 |
| AZ23C13W | KDI | 12.4-14.1 | 25 | 110 | +0.080 | 10.0 |
| AZ23C15W | KDJ | 13.8-15.6 | 30 | 110 | +0.080 | 11.0 |
| AZ23C16W | KDK | 15.3-17.1 | 40 | 170 | +0.090 | 12.0 |
| AZ23C18W | KDL | 16.8-19.1 | 50 | 170 | +0.090 | 14.0 |
| AZ23C20W | KDM | 18.8-21.2 | 50 | 220 | +0.090 | 15.0 |
| AZ23C22W | KDN | 20.8-23.3 | 55 | 220 | +0.090 | 17.0 |
| AZ23C24W | KDO | 22.8-25.6 | 80 | 220 | +0.090 | 18.0 |
| AZ23C27W | KDP | 25.1-28.9 | 80 | 250 | +0.090 | 20.0 |
| AZ23C30W | KDQ | 28-32 | 80 | 250 | +0.090 | 22.5 |
| AZ23C33W | KDR | 31-35 | 80 | 250 | +0.090 | 25.0 |
| AZ23C36W | KDS | 34-38 | 90 | 250 | +0.090 | 27.0 |
| AZ23C39W | KDT | 37-41 | 90 | 300 | +0.110 | 29.0 |

Notes: 1. Short duration test pulse used to minmize self-heating effect.

2. $f=1KH_Z$



Micro Commercial Components

Ordering Information:

| Device | Packing | | |
|----------------|-----------------------|--|--|
| Part Number-TP | Tape&Reel: 3Kpcs/Reel | | |

Note: Adding "-HF" suffix for halogen free, eg. Part Number-TP-HF

IMPORTANT NOTICE

Micro Commercial Components Corp. reserves the right to make changes without further notice to any product herein to make corrections, modifications, enhancements, improvements, or other changes. **Micro Commercial Components Corp.** does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights, nor the rights of others. The user of products in such applications shall assume all risks of such use and will agree to hold **Micro Commercial Components Corp.** and all the companies whose products are represented on our website, harmless against all damages.

LIFE SUPPORT

MCC's products are not authorized for use as critical components in life support devices or systems without the express written approval of Micro Commercial Components Corporation.

CUSTOMER AWARENESS

Counterfeiting of semiconductor parts is a growing problem in the industry. Micro Commercial Components (MCC) is taking strong measures to protect ourselves and our customers from the proliferation of counterfeit parts. MCC strongly encourages customers to purchase MCC parts either directly from MCC or from Authorized MCC Distributors who are listed by country on our web page cited below. Products customers buy either from MCC directly or from Authorized MCC Distributors are genuine parts, have full traceability, meet MCC's quality standards for handling and storage. MCC will not provide any warranty coverage or other assistance for parts bought from Unauthorized Sources. MCC is committed to combat this global problem and encourage our customers to do their part in stopping this practice by buying direct or from authorized distributors.