

Surface Mount Silicon Zener Diodes

FEATURES

- Low profile package
- Ideal for automated placement
- Glass passivated junction
- Built-in strain relief
- Low inductance
- Moisture sensitivity level: level 1, per J-STD-020
- Compliant to RoHS Directive 2011/65/EU and in accordance to WEEE 2002/96/EC
- Halogen-free according to IEC 61249-2-21 definition



DO-214AA (SMB)

MECHANICAL DATA

Case: DO-214AA (SMB)

Molding compound, UL flammability classification rating 94V-0

Base P/N with suffix "G" on packing code - green compound (halogen-free)

Base P/N with prefix "H" on packing code - AEC-Q101 qualified

Terminal: Matte tin plated leads, solderable per JESD22-B102

Meet JESD 201 class 1A whisker test,

with prefix "H" on packing code meet JESD 201 class 2 whisker test

Polarity: Indicated by cathode band

Weight: 0.1 g (approximately)

| MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS (T _A =25°C unless otherwise noted) | | | |
|--|------------------|--------------|-------|
| PARAMETER | SYMBOL | Value | UNIT |
| DC power dissipation at T _L =75°C, measure at zero lead length (Note 1) derate above 75°C | P _D | 3 | Watts |
| | | 40 | mW/°C |
| DC power dissipation at T _A =25°C Derate above 25°C | P _D | 550 | mW |
| | | 4.4 | mW/°C |
| Thermal Resistance from Junction to Lead | R _{θJL} | 25 | °C /W |
| Thermal Resistance from Junction to Ambient | R _{θJA} | 226 | °C /W |
| Operating junction temperature range | T _J | - 55 to +150 | °C |
| Storage temperature range | T _{STG} | - 55 to +150 | °C |

Note 1: Mounted on Cu-Pad size 5mm x 5mm x 1.6mm on PCB

| ORDERING INFORMATION | | | | | |
|----------------------|--------------------|--------------|---------------------|---------|--------------------------|
| PART NO. | AEC-Q101 QUALIFIED | PACKING CODE | GREEN COMPOUND CODE | PACKAGE | PACKING |
| 1SMBxxxx (Note 1) | Prefix "H" | R5 | Suffix "G" | SMB | 850 / 7" Plastic reel |
| | | R4 | | SMB | 3,000 / 13" Paper reel |
| | | M4 | | SMB | 3,000 / 13" Plastic reel |

Note 1: "xxxx" defines voltage from 11V (1SMB5926) to 200V (1SMB5956)

| EXAMPLE | | | | | |
|---------------|----------|--------------------|--------------|---------------------|--------------------|
| PREFERRED P/N | PART NO. | AEC-Q101 QUALIFIED | PACKING CODE | GREEN COMPOUND CODE | DESCRIPTION |
| 1SMB5926 R5 | 1SMB5926 | | R5 | | |
| 1SMB5926 R5G | 1SMB5926 | | R5 | G | Green compound |
| 1SMB5926HR5 | 1SMB5926 | H | R5 | | AEC-Q101 qualified |

RATINGS AND CHARACTERISTICS CURVES

(TA=25°C unless otherwise noted)

| Device (Note 1) | Device Marking Code | Nominal Zener Voltage | | | Test Current | Zener Impedance (Note 3) | | | Leakage Current | | Maximum DC Zener Current |
|--------------------|---------------------------|-----------------------|------------------|--------|-----------------|-----------------------------|---------|------|-----------------|-------|-----------------------------|
| | | Vz@Iz | | | | ZzT@IzT | ZzK@IzK | | IR@VR | | |
| | | V | | | mA | Ω | Ω | mA | μA | V | mA(DC) |
| | | Min | Nom (Notes 2) | Max | | | | | | | |
| 1SMB5926 | 926B | 10.45 | 11 | 11.55 | 34.1 | 5.5 | 550 | 0.25 | 1 | 8.4 | 136 |
| 1SMB5927 | 927B | 11.40 | 12 | 12.60 | 31.2 | 6.5 | 550 | 0.25 | 1 | 9.1 | 125 |
| 1SMB5928 | 928B | 12.35 | 13 | 13.65 | 28.8 | 7.0 | 550 | 0.25 | 1 | 9.9 | 115 |
| 1SMB5929 | 929B | 14.25 | 15 | 15.75 | 25.0 | 9.0 | 600 | 0.25 | 1 | 11.4 | 100 |
| 1SMB5930 | 930B | 15.20 | 16 | 16.80 | 23.4 | 10.0 | 600 | 0.25 | 1 | 12.2 | 94 |
| 1SMB5931 | 931B | 17.10 | 18 | 18.90 | 20.8 | 12.0 | 650 | 0.25 | 1 | 13.7 | 83 |
| 1SMB5932 | 932B | 19.00 | 20 | 21.00 | 18.7 | 14.0 | 650 | 0.25 | 1 | 15.2 | 75 |
| 1SMB5933 | 933B | 20.90 | 22 | 23.10 | 17.0 | 17.5 | 650 | 0.25 | 1 | 16.7 | 68 |
| 1SMB5934 | 934B | 22.80 | 24 | 25.20 | 15.6 | 19 | 700 | 0.25 | 1 | 18.2 | 63 |
| 1SMB5935 | 935B | 25.65 | 27 | 28.35 | 13.9 | 23 | 700 | 0.25 | 1 | 20.6 | 56 |
| 1SMB5936 | 936B | 28.50 | 30 | 31.50 | 12.5 | 26 | 750 | 0.25 | 1 | 22.8 | 50 |
| 1SMB5937 | 937B | 31.35 | 33 | 34.65 | 11.4 | 33 | 800 | 0.25 | 1 | 25.1 | 45 |
| 1SMB5938 | 938B | 34.20 | 36 | 37.80 | 10.4 | 38 | 850 | 0.25 | 1 | 27.4 | 42 |
| 1SMB5939 | 939B | 37.05 | 39 | 40.95 | 9.6 | 45 | 900 | 0.25 | 1 | 29.7 | 38 |
| 1SMB5940 | 940B | 40.85 | 43 | 45.15 | 8.7 | 53 | 950 | 0.25 | 1 | 32.7 | 35 |
| 1SMB5941 | 941B | 44.65 | 47 | 49.35 | 8.0 | 67 | 1000 | 0.25 | 1 | 35.8 | 32 |
| 1SMB5942 | 942B | 48.45 | 51 | 53.55 | 7.3 | 70 | 1100 | 0.25 | 1 | 38.8 | 29 |
| 1SMB5943 | 943B | 53.20 | 56 | 58.80 | 6.7 | 86 | 1300 | 0.25 | 1 | 42.6 | 27 |
| 1SMB5944 | 944B | 58.90 | 62 | 65.10 | 6.0 | 100 | 1500 | 0.25 | 1 | 47.1 | 24 |
| 1SMB5945 | 945B | 64.60 | 68 | 71.40 | 5.5 | 120 | 1700 | 0.25 | 1 | 51.7 | 22 |
| 1SMB5946 | 946B | 71.25 | 75 | 78.75 | 5.0 | 140 | 2000 | 0.25 | 1 | 56.0 | 20 |
| 1SMB5947 | 947B | 77.90 | 82 | 86.10 | 4.6 | 160 | 2500 | 0.25 | 1 | 62.2 | 18 |
| 1SMB5948 | 948B | 86.45 | 91 | 95.55 | 4.1 | 200 | 3000 | 0.25 | 1 | 69.2 | 16 |
| 1SMB5949 | 949B | 95.00 | 100 | 105.00 | 3.7 | 250 | 3100 | 0.25 | 1 | 76.0 | 15 |
| 1SMB5950 | 950B | 104.50 | 110 | 115.50 | 3.4 | 300 | 4000 | 0.25 | 1 | 83.6 | 13 |
| 1SMB5951 | 951B | 114.00 | 120 | 126.00 | 3.1 | 360 | 4500 | 0.25 | 1 | 91.2 | 12 |
| 1SMB5952 | 952B | 123.50 | 130 | 136.50 | 2.9 | 450 | 5000 | 0.25 | 1 | 98.8 | 11 |
| 1SMB5953 | 953B | 142.50 | 150 | 157.50 | 2.5 | 600 | 6000 | 0.25 | 1 | 114.0 | 10 |
| 1SMB5954 | 954B | 152.00 | 160 | 168.00 | 2.3 | 700 | 6500 | 0.25 | 1 | 121.6 | 9 |
| 1SMB5955 | 955B | 171.00 | 180 | 189.00 | 2.1 | 900 | 7000 | 0.25 | 1 | 136.8 | 8 |
| 1SMB5956 | 956B | 190.00 | 200 | 210.00 | 1.9 | 1200 | 8000 | 0.25 | 1 | 152.0 | 7 |

Notes:

1. Tolerance and type number designation the type numbers listed indicate a tolerance of 5%
2. Zener voltage (Vz) measurement

Nominal Zener voltage is measured with the device junction in thermal equilibrium with ambient temperature 25°C

3. Zener impedance (Zz) derivation : ZzT and ZzK are measured by dividing the AC voltage drop across the device by the AC current applied.

The specified limits are for Iz(AC) = 0.1 Iz(DC) with the AC frequency = 60 Hz

FIG. 1 STEADY STATE POWER DERATING




FIG.2 MAXIMUM SURGE POWER




FIG. 3 ZENER VOLTAGE - TO 12 VOLTAGES




FIG.4 ZENER VOLTAGE 14 TO 200 VOLTAGES




FIG. 5 V_Z = 3.3 THRU 10 VOLTS




FIG. 6 V_Z = 12 THRU 82 VOLTS




FIG. 7 EFFECT OF ZENER VOLTAGE




FIG. 8 EFFECT OF ZENER CURRENT




FIG.9 CAPACITANCE CURVE




FIG. 10 TYPICAL PULSE RATING CURVE




FIG. 11 PULSE WAVEFORM





FIG. 12 PULSE WAVEFORM



Notice

Specifications of the products displayed herein are subject to change without notice. TSC or anyone on its behalf, assumes no responsibility or liability for any errors inaccuracies.

Information contained herein is intended to provide a product description only. No license, express or implied, to any intellectual property rights is granted by this document. Except as provided in TSC's terms and conditions of sale for such products, TSC assumes no liability whatsoever, and disclaims any express or implied warranty, relating to sale and/or use of TSC products including liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright, or other intellectual property right.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications. Customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify TSC for any damages resulting from such improper use or sale.