



PJW1NA80 / PJU1NA80 / PJD1NA80 / PJP1NA80

800V N-Channel MOSFET

Voltage

800 V

Current


1 A

Features

- $R_{DS(ON)}, V_{GS}@10V, I_D@0.5A < 16\Omega$
- High switching speed
- Improved dv/dt capability
- Low Gate Charge
- Low reverse transfer capacitance
- Lead free in compliance with EU RoHS 2011/65/EU directive.
- Green molding compound as per IEC61249 Std.
(Halogen Free)

Mechanical Data

- Case : TO-251AB , TO-220AB, SOT-223, TO-252 Package
- Terminals : Solderable per MIL-STD-750, Method 2026
- TO-251AB Approx. Weight : 0.0104 ounces, 0.297grams
- TO-220AB Approx. Weight : 0.067 ounces, 1.89 grams
- SOT-223 Approx. Weight : 0.043 ounces, 0.123grams
- TO-252 Approx. Weight : 0.0104 ounces, 0.297grams



Maximum Ratings and Thermal Characteristics ($T_A=25^\circ\text{C}$ unless otherwise noted)

PARAMETER		SYMBOL	TO-251AB	TO-220AB	TO-252	SOT-223	UNITS
Drain-Source Voltage		V_{DS}	800				V
Gate-Source Voltage		V_{GS}	+30				V
Continuous Drain Current		I_D	1			0.3	A
Pulsed Drain Current		I_{DM}	4			1.2	A
Single Pulse Avalanche Energy ^(Note 1)		E_{AS}	23				mJ
Power Dissipation	$T_C=25^\circ\text{C}$	P_D	34	45	34	3.3	W
	Derate above 25°C		0.27	0.36	0.27	0.026	W/ $^\circ\text{C}$
Operating Junction and Storage Temperature Range		T_J, T_{STG}	-55~150				$^\circ\text{C}$
Typical Thermal resistance							
-	Junction to Case	$R_{\theta JC}$	3.68	2.78	3.68	-	$^\circ\text{C}/\text{W}$
-	Junction to Ambient	$R_{\theta JA}$	110	62.5	110	37.9 ^(Note 4)	

- Limited only By Maximum Junction Temperature



PJW1NA80 / PJU1NA80 / PJD1NA80 / PJP1NA80

Electrical Characteristics (T_A=25 °C unless otherwise noted)

PARAMETER	SYMBOL	TEST CONDITION	MIN.	TYP.	MAX.	UNITS
Static						
Drain-Source Breakdown Voltage	BV _{DSS}	V _{GS} =0V, I _D =250uA	800	-	-	V
Gate Threshold Voltage	V _{GS(th)}	V _{DS} =V _{GS} , I _D =250uA	3.1	3.5	4.4	V
Drain-Source On-State Resistance	R _{DS(on)}	V _{GS} =10V, I _D =0.5A	-	12.5	16	Ω
Zero Gate Voltage Drain Current	I _{DSS}	V _{DS} =800V, V _{GS} =0V	-	-	1.0	uA
Gate-Source Leakage Current	I _{GSS}	V _{GS} =±30V, V _{DS} =0V	-	-	±100	nA
Diode Forward Voltage	V _{SD}	I _S =1A, V _{GS} =0V	-	-	1.4	V
Dynamic (Note 5)						
Total Gate Charge	Q _g	V _{DS} =640V, I _D =1A, V _{GS} =10V (Note 2,3)	-	6	-	nC
Gate-Source Charge	Q _{gs}		-	1.3	-	
Gate-Drain Charge	Q _{gd}		-	2.6	-	
Input Capacitance	C _{iss}	V _{DS} =25V, V _{GS} =0V, f=1.0MHZ	-	203	-	pF
Output Capacitance	C _{oss}		-	17	-	
Reverse Transfer Capacitance	C _{rss}		-	1	-	
Turn-On Delay Time	t _{d(on)}	V _{DD} =400V, I _D =1A, R _G =25Ω (Note 2,3)	-	8	-	ns
Turn-On Rise Time	t _r		-	15	-	
Turn-Off Delay Time	t _{d(off)}		-	13	-	
Turn-Off Fall Time	t _f		-	21	-	
Drain-Source Diode						
Maximum Continuous Drain-Source Diode Forward Current	I _S	---	-	-	1	A
Maximum Pulsed Drain-Source Diode Forward Current	I _{SM}	---	-	-	4	A
Reverse Recovery Time	t _{rr}	V _{GS} =0V, I _S =1A	-	160	-	ns
Reverse Recovery Charge	Q _{rr}	dI _F / dt=100A/us (Note 2)	-	0.3	-	uC

NOTES :

- L=30mH, I_{AS}=1.17A, V_{DD}=110V, R_G=25ohm, Starting T_J=25°C
- Pulse width≤300us, Duty cycle≤2%
- Essentially independent of operating temperature typical characteristics.
- R_{θJA} is the sum of the junction-to-case and case-to-ambient thermal resistance where the case thermal reference is defined as the solder mounting surface of the drain pins mounted on a 1 inch FR-4 with 2oz. square pad of copper.
- Guaranteed by design, not subject to production testing



PJW1NA80 / PJU1NA80 / PJD1NA80 / PJP1NA80

TYPICAL CHARACTERISTIC CURVES




Fig.1 Output Characteristics




Fig.2 Transfer Characteristics




Fig.3 On-Resistance vs. Drain Current




Fig.4 On-Resistance vs. Junction Temperature




Fig.5 Capacitance vs. Drain-Source Voltage




Fig.6 Source-Drain Diode Forward Voltage



PJW1NA80 / PJU1NA80 / PJD1NA80 / PJP1NA80

TYPICAL CHARACTERISTIC CURVES




Fig.7 Gate Charge




Fig.8 BV_{DSS} vs. Junction Temperature




Fig.9 Threshold Voltage Variation with Temperature




Fig.10 Maximum Safe Operating Area




Fig.11 Maximum Safe Operating Area




Fig.12 Maximum Safe Operating Area



PJW1NA80 / PJU1NA80 / PJD1NA80 / PJP1NA80

TYPICAL CHARACTERISTIC CURVES




Fig.13 PJU/PJD Normalized Transient Thermal Impedance vs. Pulse Width




Fig.14 PJP1NA80 Normalized Transient Thermal Impedance vs. Pulse Width








Fig.15 PJW1NA80 Normalized Transient Thermal Impedance vs. Pulse Width



PJW1NA80 / PJU1NA80 / PJD1NA80 / PJP1NA80

Packaging Information





PJW1NA80 / PJU1NA80 / PJD1NA80 / PJP1NA80

PART NO PACKING CODE VERSION

Part No Packing Code	Package Type	Packing type	Marking	Version
PJU1NA80_T0_00001	TO-251AB	80pcs / Tube	U1NA80	Halogen free
PJD1NA80_L2_00001	TO-252	3,000pcs / 13" reel	D1NA80	Halogen free
PJW1NA80_R2_00001	SOT-223	2,500pcs / 13" reel	1NA80	Halogen free
PJP1NA80_T0_00001	TO-220AB	50pcs / Tube	P1NA80	Halogen free



PJW1NA80 / PJU1NA80 / PJD1NA80 / PJP1NA80

Disclaimer

- Reproducing and modifying information of the document is prohibited without permission from Panjit International Inc..
- Panjit International Inc. reserves the rights to make changes of the content herein the document anytime without notification. Please refer to our website for the latest document.
- Panjit International Inc. disclaims any and all liability arising out of the application or use of any product including damages incidentally and consequentially occurred.
- Panjit International Inc. does not assume any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.
- Applications shown on the herein document are examples of standard use and operation. Customers are responsible in comprehending the suitable use in particular applications. Panjit International Inc. makes no representation or warranty that such applications will be suitable for the specified use without further testing or modification.
- The products shown herein are not designed and authorized for equipments requiring high level of reliability or relating to human life and for any applications concerning life-saving or life-sustaining, such as medical instruments, transportation equipment, aerospace machinery et cetera. Customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify Panjit International Inc. for any damages resulting from such improper use or sale.
- Since Panjit uses lot number as the tracking base, please provide the lot number for tracking when complaining.