



RB751S40X

SURFACE MOUNT SCHOTTKY DIODES

VOLTAGE 40 Volts **POWER** 30 mA



SOD-523 Unit : inch(mm)

FEATURES

- Extremely Fast Switching Speed
- Surface mount package ideally suited for automatic insertion
- Lead free in compliance with EU RoHS 2011/65/EU directive
- Green molding compound as per IEC61249 Std. . (Halogen Free)

MECHANICAL DATA

- Case : SOD-523 plastic
- Terminals : Solderable per MIL-STD-750,Method 2026
- Approx Weight : 0.0014 grams
- Marking : XR



ABSOLUTE RATINGS

| Parameter | Symbol | Value | Units |
|---|-----------------|-------------|---------------|
| Maximum Peak Reverse Voltage | V_{RRM} | 40 | V |
| Reverse DC Voltage | V_R | 30 | V |
| Average Forward Current | $I_{F(AV)}$ | 30 | mA |
| Peak Forward Surge Current : 8.3ms single half sine-wave superimposed on rated load | I_{FSM} | 200 | mA |
| Typical Junction Capacitance ($V_R=1V$, $f=1MHz$) | C_J | 2.5 | pF |
| Thermal Resistance, Junction to Ambient (Note 1) | $R_{\theta JA}$ | 750 | $^{\circ}C/W$ |
| Operating Junction and Storage Temperature Range | T_J, T_{STG} | -55 to +150 | $^{\circ}C$ |

Note : 1. Mounted on an FR4 PCB, single-sided copper, mini pad.



RB751S40X

ELECTRICAL CHARACTERISTICS ($T_J = 25^\circ\text{C}$ unless otherwise noted)

| Parameter | Symbol | Test Condition | Min. | Typ. | Max. | Units |
|-------------------------|--------|--|------|------|------|---------------|
| Forward Voltage | V_F | $I_F=1\text{mA}$ $T_J=25^\circ\text{C}$ | - | - | 0.37 | V |
| | | $I_F=1\text{mA}$ $T_J=125^\circ\text{C}$ | - | 0.19 | - | |
| Reverse Leakage Current | I_R | $V_R=30\text{V}$ | - | - | 0.5 | μA |




Fig.1 Forward Current Derating Curve




Fig.2 Typical Junction Capacitance




Fig.3 Typical Reverse Characteristics





Fig.4 Typical Forward Characteristics



RB751S40X

MOUNTING PAD LAYOUT



ORDER INFORMATION

- Packing information
T/R - 12K per 13" plastic Reel
T/R - 5K per 7" plastic Reel



RB751S40X

Part No_packing code_Version

RB751S40X_R1_00001

RB751S40X_R2_00001

For example :

RB500V-40_R2_00001



| Packing Code XX | | | | Version Code XXXXX | | |
|--------------------------------------|----------------------|----------------------------------|----------------------|---------------------------|----------------------|---------------------------------------|
| Packing type | 1 st Code | Packing size code | 2 nd Code | HF or RoHS | 1 st Code | 2 nd ~5 th Code |
| Tape and Ammunition Box (T/B) | A | N/A | 0 | HF | 0 | serial number |
| Tape and Reel (T/R) | R | 7" | 1 | RoHS | 1 | serial number |
| Bulk Packing (B/P) | B | 13" | 2 | | | |
| Tube Packing (T/P) | T | 26mm | X | | | |
| Tape and Reel (Right Oriented) (TRR) | S | 52mm | Y | | | |
| Tape and Reel (Left Oriented) (TRL) | L | PANASERT T/B CATHODE UP (PBCU) | U | | | |
| FORMING | F | PANASERT T/B CATHODE DOWN (PBCD) | D | | | |



RB751S40X

Disclaimer

- Reproducing and modifying information of the document is prohibited without permission from Panjit International Inc..
- Panjit International Inc. reserves the rights to make changes of the content herein the document anytime without notification. Please refer to our website for the latest document.
- Panjit International Inc. disclaims any and all liability arising out of the application or use of any product including damages incidentally and consequentially occurred.
- Panjit International Inc. does not assume any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.
- Applications shown on the herein document are examples of standard use and operation. Customers are responsible in comprehending the suitable use in particular applications. Panjit International Inc. makes no representation or warranty that such applications will be suitable for the specified use without further testing or modification.
- The products shown herein are not designed and authorized for equipments requiring high level of reliability or relating to human life and for any applications concerning life-saving or life-sustaining, such as medical instruments, transportation equipment, aerospace machinery et cetera. Customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify Panjit International Inc. for any damages resulting from such improper use or sale.
- Since Panjit uses lot number as the tracking base, please provide the lot number for tracking when complaining.